

SAFETY DATA SHEET

Creation Date 29-Jan-2010 Revision Date 06-May-2025 Revision Number 4

1. Identification

Product Name Dichloromethane, stabilized with ethanol

Cat No.: C12405

CAS No 75-09-2

Synonyms Methylene chloride; Methylene dichloride

Recommended Use Uses advised against Laboratory chemicals.

. This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing: (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

Details of the supplier of the safety data sheet

Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099 Tel: 800-343-0660

Fax: 800-322-4757

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2
Carcinogenicity Category 2
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

Label Elements

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
May cause cancer



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

∟yes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Contains a known or suspected endocrine disruptor. WARNING. Cancer - https://www.p65warnings.ca.gov/.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Methylene chloride	75-09-2	> 99.5
Ethyl alcohol	64-17-5	0.2

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression: Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal: Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular

system and the central nervous system

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point No information available Method - No information available

Autoignition Temperature 556 °C / 1033 °F

Explosion Limits

Upper 22 vol % **Lower** 13 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Phosgene. Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards210N/A

6. Accidental release measures

Personal Precautions
Environmental Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Prevent further leakage or spillage if safe to do so. Soak up with inert absorbent material.

Up

Keep in suitable, closed containers for disposal. Ventilate the area.

7. Handling and Storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store in

aluminum containers. Incompatible Materials. Strong oxidizing agents. Strong acids.

Amines. Aluminium. .

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methylene chloride	TWA: 50 ppm	(Vacated) TWA: 500 ppm	IDLH: 2300 ppm	TWA: 50 ppm
		(Vacated) STEL: 2000 ppm		
		(Vacated) Ceiling: 1000 ppm		
		TWA: 25 ppm		
		STEL: 125 ppm		
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm	STEL: 1000 ppm
		(Vacated) TWA: 1900 mg/m ³	REL = 1000 ppm (TWA)	
		TWA: 1000 ppm	$REL = 1900 \text{ mg/m}^3 (TWA)$	
		TWA: 1900 mg/m ³	, , ,	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location. Use only under a chemical fume

hood.

Personal Protective Equipment

Eye/face Protection Tight sealing safety goggles. Face protection shield.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweet

Odor Threshold No information available

pH Not applicable Insoluble in water

Melting Point/Range -97 °C / -142.6 °F

Boiling Point/Range 39 - 40 °C / 102.2 - 104 °F @ 760 mmHg

Flash Point No information available Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 22 vol %

 Lower
 13 vol %

Vapor Pressure 350 mbar @ 20 °C

Vapor Density 2.93 Specific Gravity 1.325

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature

Soluble in water

No data available

556 °C / 1033 °F

Decomposition Temperature > 120°C

Viscosity 0.43 mPa.s @ 20 °C

Molecular Formula C H2 Cl2
Molecular Weight 84.93

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under recommended storage conditions.

Conditions to Avoid Incompatible products. Excess heat.

Incompatible Materials Strong oxidizing agents, Strong acids, Amines, Aluminium,

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Phosgene, Hydrogen chloride gas

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methylene chloride	Methylene chloride > 2000 mg/kg (Rat)		53 mg/L (Rat) 6 h
-			76000 mg/m³ (Rat) 4 h
Ethyl alcohol	LD50 = 10470 mg/kg	Not listed	LC50 = 117-125 mg/l (4h)
	OECD 401 (Rat)		OECD 403 (rat)
	3450 mg/kg (Mouse)		20000 ppm/10H (rat)

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methylene chloride	75-09-2	Group 2A	Reasonably Anticipated	A3	Х	A3
Ethyl alcohol	64-17-5	Not listed	Known	A3	Not listed	A3

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program) Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial A1 - Known Human Carcinogen

Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen A5 - Not Suspected as a Human Carcinogen

No information available **Mutagenic Effects**

Mexico - Occupational Exposure Limits - Carcinogens

Reproductive Effects No information available.

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

Teratogenicity No information available.

Central nervous system (CNS) STOT - single exposure

STOT - repeated exposure None known

Aspiration hazard No information available

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression: Continued or high exposures by inhalation will cause anaesthetic effects. This may result in a loss of consciousness and could prove fatal: Causes formation of carbon monoxide in the blood. Carbon monoxide may cause adverse effects on the cardiovascular system and the central

nervous system

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methylene chloride	EC50:>660 mg/L/96h	Pimephales promelas:	EC50: 1 mg/L/24 h	EC50: 140 mg/L/48h
	_	LC50:193 mg/L/96h	EC50: 2.88 mg/L/15 min	_
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800 mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	_
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	

Dichloromethane, stabilized with ethanol

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methylene chloride	1.25
Ethyl alcohol	-0.32

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methylene chloride - 75-09-2	U080	-

14. Transport information

DOT

UN-No UN1593

Proper Shipping Name DICHLOROMETHANE

Hazard Class 6.1 Packing Group

<u>TDG</u>

UN-No UN1593

Proper Shipping Name DICHLOROMETHANE

Hazard Class 6.1 Packing Group III

<u>IATA</u>

UN-No UN1593

Proper Shipping Name DICHLOROMETHANE

Hazard Class 6.1 Packing Group

IMDG/IMO

UN-No UN1593

Proper Shipping Name DICHLOROMETHANE

Hazard Class 6.1 Packing Group III

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags	
Methylene chloride	75-09-2	X	ACTIVE	R	
Ethyl alcohol	64-17-5	Χ	ACTIVE	-	

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

Section 6(a) of the Toxic Substances Control Act (TSCA)

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/ product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed

in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

Component	CAS No	TSCA 12(b) - Notices of Export
Methylene chloride	75-09-2	Section 6

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methylene chloride	75-09-2	Χ	-	200-838-9	Χ	Χ	Χ	Χ	Χ	KE-23893
Ethyl alcohol	64-17-5	Х	-	200-578-6	Χ	Χ	Х	Х	Х	KE-13217

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Methylene chloride	75-09-2	> 99.5	0.1 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

CVVA (Clean Water Act)				
Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Methylene chloride	-	=	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methylene chloride	X		-

OSHA - Occupational Safety and

Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Methylene chloride	125 ppm STEL	-
	12.5 ppm Action Level	
	25 ppm TWA	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methylene chloride	1000 lb	-	1000 lb 454 kg

California Proposition 65

This product contains the following Proposition 65 chemicals. Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methylene chloride	75-09-2	Carcinogen	200 μg/day 50 μg/day	Carcinogen
Ethyl alcohol	64-17-5	Development (alcoholic beverages only)	-	Developmental Carcinogen
		Carcinogen		

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methylene chloride	X	X	X	X	X
Ethyl alcohol	X	Х	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methylene chloride	75-09-2	-	Use restricted. See entry 59. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Ethyl alcohol	64-17-5	-	-	-

Restricted to industrial use and to approved professionals.

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methylene chloride	75-09-2	Listed	Not applicable	Not applicable	Not applicable
Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methylene chloride	75-09-2	Not applicable	Not applicable	Not applicable	Annex I - Y45
Ethyl alcohol	64-17-5	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other II	nformation
--------------	------------

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 29-Jan-2010

 Revision Date
 06-May-2025

 Print Date
 06-May-2025

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS