

SAFETY DATA SHEET

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name <u>Toluene</u>

CAS No 108-88-3

Synonyms Tol; Methylbenzene

Product Code T313-4; T313SK-4

Address ThermoFisher Scientific Australia Pty Ltd

5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®

03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292

Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list.

Verify requirements related to using, handling and storing these substances. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice

for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 2

Health hazards

Aspiration Toxicity

Skin Corrosion/Irritation

Reproductive Toxicity

Specific target organ toxicity - (single exposure)

Specific target organ toxicity - (repeated exposure)

Category 2

Category 3

Specific target organ toxicity - (repeated exposure)

Category 2

Environmental hazards

Chronic aquatic toxicity Category 3

Label Elements

FSHT313 Version 2 21-Nov-2022 Page 1 / 11







Flame

Exclamation Mark

Health Hazard

Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear eye protection/ face protection

P271 - Use only outdoors or in a well-ventilated area

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P363 - Wash contaminated clothing before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

1	Component	CAS No	Weight %
	Toluene	108-88-3	<=100

Section 4 - First Aid Measures

FSHT313 Version 2 21-Nov-2022 Page 2 / 11

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

General Advice If symptoms persist, call a physician.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

Notes to Physician Treat symptomatically. Smallest quantities reaching the lungs through swallowing or

subsequent vomiting may result in lung edema or pneumonia. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use

FSHT313 Version 2 21-Nov-2022 Page 3 / 11

spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]
Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Toluene	STEL: 150 ppm	TWA: 20 ppm	TWA: 20 ppm	STEL: 100 ppm 15 min	TWA: 50 ppm (8
	STEL: 574 mg/m ³	TWA: 75 mg/m ³		STEL: 384 mg/m ³ 15	Stunden). AGW -
	TWA: 50 ppm	STEL: 100 ppm		min	exposure factor 2
	TWA: 191 mg/m ³	STEL: 377 mg/m ³		TWA: 50 ppm 8 hr	TWA: 190 mg/m³ (8
		Skin		TWA: 191 mg/m ³ 8 hr	Stunden). AGW -
				Skin	exposure factor 2
					TWA: 50 ppm (8
					Stunden). MAK
					TWA: 190 mg/m³ (8
					Stunden). MAK
					Höhepunkt: 100 ppm
					Höhepunkt: 380 mg/m ³
					Haut

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Toluene		0.03 mg/L (urine) end of			Toluene: 600 µg/L
		exposure or end of shift			whole blood
		(Toluene)			(immediately after
		0.3 mg/g creatinine			exposure)
		(urine) end of exposure			Toluene: 75 µg/L urine
		or end of shift			(end of shift)

FSHT313 Version 2 21-Nov-2022 Page 4/11

	(O-Cresol)		o-Cresol (after
			hydrolysis): 1.5 mg/L
			urine (for long-term
			exposures: at the end of
			the shift after several
			shifts)
			o-Cresol (after
			hydrolysis): 1.5 mg/L
			urine (end of shift)

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (Australian/New Zealand Standard

AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection Protective gloves

	Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
ı	Viton (R)	< 240 minutes	0.30 mm	AS/NZS 2161	Permeation rate 68 µg/cm2/min As tested
	. ,				under EN374-3 Determination of
					Resistance to Permeation by Chemicals
	Viton (R)	> 480 minutes	0.70 mm		•

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Repiratory ProtectionUse an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ

equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

OdoraromaticOdor Threshold1.74 ppm

FSHT313 Version 2 21-Nov-2022 Page 5/11

pH No information available Melting Point/Range -95 °C / -139 °F

Softening Point/Range
Softening Point

Boiling Point/Range111 °C / 231.8 °F@ 760 mmHgFlash Point4 °C / 39.2 °FMethod - No

Flash Point 4 °C / 39.2 °F Method - No information available Evaporation Rate 2.4 (Butyl acetate = 1.0)

Flammability (solid,gas)

Not applicable

Liquid

Lower 1.2 vol%

Lower 1.2 vol% Upper 7 vol%

Vapor Pressure 29 mbar @ 20 °C

Vapor Density 3.1 (Air = 1.0)

Specific Gravity / Density 0.866

Bulk Density Not applicable Liquid

Water Solubility practically insoluble 0.5 g/L @ 20°C

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowToluene2.73

Autoignition Temperature535 °C / 995 °FDecomposition TemperatureNo data availableViscosity0.6 mPa.s @ 20 °C

Explosive Properties Not explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

Other information

Molecular FormulaC7 H8Molecular Weight92.14

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products, Excess heat, Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases, Halogenated compounds.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2).

Hazardous Polymerization Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

	Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ī	Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation; Category 2 Test method OECD 404

FSHT313 Version 2 21-Nov-2022 Page 6/11

rabbit **Test species**

Observational endpoint Irritating to skin

Based on available data, the classification criteria are not met (c) serious eye damage/irritation;

(d) respiratory or skin sensitization:

Respiratory Based on available data, the classification criteria are not met Skin Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity: Category 2

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals

Developmental Effects Developmental effects have occurred in experimental animals

Possible risk of harm to the unborn child **Teratogenicity**

Category 3 (h) STOT-single exposure;

Results / Target organs Central nervous system (CNS)

Category 2 (i) STOT-repeated exposure;

Target Organs Liver, Kidney, Central nervous system (CNS), Blood, spleen, Neuropsychological effects,

Eves, Ears.

(j) aspiration hazard; Category 1

delayed

Symptoms / effects,both acute and Causes central nervous system depression: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h	EC50 = 19.7 mg/L 30
	5-7 mg/L LC50 96 h	(Daphnia magna)	static	min
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L,	(Pseudokirchneriella	
	28 mg/L LC50 96 h	48h Static (Daphnia	subcapitata)	
	12 mg/L LC50 96 h	magna)	EC50: > 433 mg/L, 96h	
			(Pseudokirchneriella	
			subcapitata)	

Readily biodegradable Persistence and Degradability Persistence is unlikely. **Persistence**

Component	Degradability
Toluene	86% (20d)
108-88-3 (<=100)	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants. **Bioaccumulative Potential** Bioaccumulation is unlikely

Component log Pow Bioconcentration factor (BCF)

FSHT313 Version 2 21-Nov-2022 Page 7/11

Toluene	2.73	90		
Mobility	The product contains volatile organic compounds (VOC) which will evaporate easily from all			
	surfaces. Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility			
Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors			
Persistent Organic Pollutant	This product does not contain any known or suspected substance			
Ozone Depletion Potential	This product does not contain any known or so	uspected substance		

Section 13 - Disposal Considerations

Waste from Residues/Unused **Products**

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN1294 **UN-No TOLUENE Proper Shipping Name**

Hazard Class Packing Group Ш

ADG

UN1294 UN-No **Proper Shipping Name TOLUENE Hazard Class**

Packing Group Ш

Com	ponent	Hazchem Code
Tol	uene	3YE
108-88-	3 (<=100)	

IATA

UN1294 **UN-No TOLUENE Proper Shipping Name**

Hazard Class Packing Group

No hazards identified **Environmental hazards**

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

FSHT313 Page 8/11 Version 2 21-Nov-2022

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Toluene - 108-88-3	Schedule 5 listed - including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semi-solid preparations, e) in preparations containing <=25% of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers each containing <=50 grams of adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of <=20 mL, or i) in other preparations when packed in containers with a capacity of
	<=2 mL
	Schedule 6 listed - except its derivatives; except in preparations containing <=50% of Toluene or Toluene and Xylene

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Toluene - 108-88-3	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Toluene - 108-88-3	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Toluene - 108-88-3	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

FSHT313 Version 2 21-Nov-2022 Page 9 / 11

SAFETY DATA SHEET

	Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
I	Toluene	X	Χ	203-625-9	-	X	Х	-	Х	Х	Х	X	KE-33936

Legend: X - Listed. '-' - Not Listed. KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their dispoal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories			
		of Wastes to Be Controlled			
Toluene - 108-88-3	Annex I - Y42	Y42 except Halogenated solvents			

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	. ,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	· · · · · · · · · · · · · · · · · · ·
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **TWA** - Time Weighted Average

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

NZIoC - New Zealand Inventory of Chemicals

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists Predicted No Effect Concentration (PNEC)

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

FSHT313 Version 2 21-Nov-2022 Page 10 / 11

SAFETY DATA SHEET

Ships

NZS 5433:2012 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%
WEL - Workplace Exposure Limit
DNEL - Derived No Effect Level
POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50% ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment **NOEC** - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Revision Date 21-Nov-2022 Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

FSHT313 Version 2 21-Nov-2022 Page 11 / 11