

Page 1/9 Creation Date 11-Feb-2010 Revision Date 26-Mar-2025 Version 3

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

 Perihalan Produk:
 Nickel wire

 Product Description:
 Nickel wire

 Cat No.:
 10250

 CAS No
 7440-02-0

 Molecular Formula
 Ni

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Label Elements



Signal Word Danger

Hazard Statements

Nickel wire Revision Date 26-Mar-2025

- H317 May cause an allergic skin reaction
- H351 Suspected of causing cancer
- H372 Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves

Response

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P308 + P313 IF exposed or concerned: Get medical advice/attention
- P362 + P364 Take off contaminated clothing and wash it before reuse

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxicity to Soil Dwelling Organisms

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %	
Nickel	7440-02-0	>95	

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Nickel wire Revision Date 26-Mar-2025

Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

None under normal use conditions.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Avoid dust formation. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Nickel wire Revision Date 26-Mar-2025

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Nickel		TWA: 1.5 mg/m ³	(Vacated) TWA: 1 mg/m ³
			TWA: 1 mg/m ³

Component	European Union	The United Kingdom Germany	
Nickel		STEL: 1.5 mg/m ³ 15 min	TWA: 0.03 mg/m³ (8 Stunden).
		TWA: 0.5 mg/m ³ 8 hr	AGW - exposure factor 8
		Skin	TWA: 0.006 mg/m ³ (8 Stunden).
			AGW - exposure factor 8

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eve Protection Wear safety glasses with side shields (or goggles)

Hand Protection Protective gloves

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Particulates filter conforming to EN 143

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls Prevent product from entering drains Do not allow material to contaminate ground water

system Local authorities should be advised if significant spillages cannot be contained

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Nickel wire Revision Date 26-Mar-2025

Information on basic physical and chemical properties

Appearance

Physical State Solid

Odor No information available
Odor Threshold No data available
pH No information available

Melting Point/Range 1455 °C / 2651 °F Softening Point No data available

Boiling Point/Range 2732 - 2837 °C / 4949.6 - 5138.6 @ 760 mmHg

°F

Flash Point No information available Method - No information available

Evaporation Rate Not applicable Solid

Flammability (solid,gas)

Explosion Limits

No information available

No data available

Vapor Pressure 1 mmHg @ 1810 °C

Vapor Density Not applicable Solid

Specific Gravity / Density

No data available

No data available

Water Solubility Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature No data available Decomposition Temperature No data available

Viscosity Not applicable Solid

Explosive Properties No information available Oxidizing Properties No information available

Molecular Formula Ni Molecular Weight 58.7

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

Nickel wire Revision Date 26-Mar-2025

Conditions to Avoid

Incompatible products. Excess heat. Avoid dust formation.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

DermalNo data availableInhalationNo data available

Component	LD50 Oral LD50 Dermal		LC50 Inhalation		
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h		

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available

Skin Category 1

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC	
Nickel			Cat. 1	Group 2B	

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Target Organs Kidney, Skin, Lungs, Blood.

Nickel wire Revision Date 26-Mar-2025

(j) aspiration hazard; Not applicable

Solid

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

The product contains following substances which are hazardous for the environment. **Ecotoxicity effects**

Contains a substance which is:. Very toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)	, ,	EC50 = 0.1 mg/L 72h EC50 = 0.18 mg/L 72h	

Persistence and degradability

Persistence

Degradability

Degradation in sewage

treatment plant

Insoluble in water.

Not relevant for inorganic substances.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

May have some potential to bioaccumulate Bioaccumulative potential

Mobility in soil Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water

solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

Nickel wire Revision Date 26-Mar-2025

IMDG/IMO Not regulated

Road and Rail Transport Not regulated

IATA Not regulated

No special precautions required **Special Precautions for User**

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Nickel	231-111-4	Х	X	Х	Х		Χ	Χ	KE-25818

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Nickel wire Revision Date 26-Mar-2025

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By Health, Safety and Environmental Department

Revision Date 26-Mar-2025

Revision Summary SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet