Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1/10 Creation Date 09-May-2012 Revision Date 07-Apr-2024 Version 5

ACR20939

Vinylmagnesium bromide, 0.7M solution in THF

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 乙烯基溴化镁(0.7M四氢呋喃溶液)

Product Description: VinyImagnesium bromide, 0.7M solution in THF

Cat No.: 209390000; 209391000; 209398000

Molecular Formula C2 H3 Br Mg

Supplier UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorLiquidAmberpungent

Emergency Overview

Highly flammable liquid and vapor. Suspected of causing cancer. May cause respiratory irritation. In contact with water releases flammable gases which may ignite spontaneously. Harmful if swallowed. Causes severe skin burns and eye damage. May cause drowsiness and dizziness. Reacts violently with water. May form explosive peroxides. Sensitivity to light. Moisture sensitive. Air sensitive.

Classification of the substance or mixture

Flammable liquids.	Category 2
Substances/mixtures which, in contact with water, emit flammable gases	Category 1
Acute Oral Toxicity	Category 4
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3

Label Elements

Vinylmagnesium bromide, 0.7M solution in THF



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H260 In contact with water releases flammable gases which may ignite spontaneously
- H351 Suspected of causing cancer
- H335 May cause respiratory irritation
- H302 Harmful if swallowed
- H314 Causes severe skin burns and eye damage
- H336 May cause drowsiness or dizziness

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P231 + P232 Handle and store contents under inert gas. Protect from moisture
- P240 Ground and bond container and receiving equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection

Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P310 - Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P402 + P404 - Store in a dry place. Store in a closed container

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable. Reacts violently with water, liberating extremely flammable gases. Reacts violently with water. May form explosive peroxides.

Health Hazards

Suspected of causing cancer. May cause respiratory irritation. Harmful if swallowed. Corrosive. Causes skin and eye burns. May cause drowsiness or dizziness.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water. . Is not likely mobile in the environment. Reacts violently with water.

Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Page 3 / 10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	90
Magnesium, bromoethenyl-	1826-67-1	10

SECTION 4. FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eve Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.

Inhalation

If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

Ingestion

Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

Most important symptoms and effects

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Causes central nervous system depression

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water, Foam,

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Page 4 / 10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep away from heat, sparks and flame. Protect from direct sunlight. Store at room temperature. Keep from any possible contact with water. Flammables area. Keep under nitrogen. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from water or moist air. Keep containers tightly closed in a dry, cool and well-ventilated place.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Tetrahydrofuran	TWA: 300 mg/m ³	TWA: 200 ppm TWA: 590 mg/m³	TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m³ STEL: 250 ppm STEL: 737 mg/m³

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Tetrahydrofuran	TWA: 50 ppm	(Vacated) TWA: 200	IDLH: 2000 ppm	STEL: 100 ppm 15 min	TWA: 50 ppm (8h)
	STEL: 100 ppm	ppm	TWA: 200 ppm	STEL: 300 mg/m ³ 15	TWA: 150 mg/m ³ (8h)
	Skin	(Vacated) TWA: 590	TWA: 590 mg/m ³	min	STEL: 100 ppm
		mg/m³	STEL: 250 ppm	TWA: 50 ppm 8 hr	(15min)
		(Vacated) STEL: 250	STEL: 735 mg/m ³	TWA: 150 mg/m ³ 8 hr	STEL: 300 mg/m ³
		ppm		Skin	(15min)
		(Vacated) STEL: 735			Skin
		mg/m³			
		TWA: 200 ppm			
		TWA: 590 mg/m ³			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Page 5 / 10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
--	---	-----------------	-----------------------	---

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Amber Liquid

Odor pungent

Page 6 / 10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

Odor Threshold No data available

pH No information availableMelting Point/Range No data available

Softening Point No data available
Boiling Point/Range No information available

Flash Point -17 °C / 1.4 °F Method - No information available

Evaporation Rate

Flammability (solid,gas)

No data available

Not applicable

Explosion Limits No data available

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density 0.980

Bulk Density Not applicable

Water Solubility Reacts violently with water Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowTetrahydrofuran0.45

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No data available
No data available

Explosive Properties

Oxidizing Properties No information available

Molecular FormulaC2 H3 Br MgMolecular Weight131.25

SECTION 10. STABILITY AND REACTIVITY

Stability May form explosive peroxides. Moisture sensitive. Air sensitive. Light sensitive. Reacts

violently with water, liberating extremely flammable gases.

Hazardous Reactions None under normal processing. Reacts violently with water.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Excess heat. Exposure to air. Exposure to light. Incompatible products. Exposure to moist

air or water. Exposure to moisture. Keep away from open flames, hot surfaces and sources

Liquid

Liquid

Vapors may form explosive mixtures with air

of ignition.

Materials to avoid Acids. Bases. Water. Alcohols.

Hazardous Decomposition Products Propene. Magnesium oxides. Hydrogen bromide. Carbon monoxide (CO). Carbon dioxide

(CO₂).

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity;

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h
			53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

Page 7/10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Tetrahydrofuran	Local Lymph Node Assay	mouse	non-sensitising
109-99-9 (90)	OECD Test Guideline 429		_

No data available (e) germ cell mutagenicity;

Component	Test method	Test species	Study result
Tetrahydrofuran	OECD Test Guideline 476	in vivo	negative
109-99-9 (90)	Gene cell mutation	Mammalian	
	OECD Test Guideline 473		
	Chromosomal aberration assay	in vitro	negative
		Mammalian	

(f) carcinogenicity; Category 2

Possible cancer hazard. May cause cancer based on animal data Limited evidence of a

carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

No data available (a) reproductive toxicity:

(3)						
Component	Test method	Test species / Duration	Study result			
Tetrahydrofuran	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm			
109-99-9 (90)						

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system

Central nervous system (CNS)

No data available (i) STOT-repeated exposure;

Target Organs No information available.

No data available (j) aspiration hazard;

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Causes central nervous system depression

SECTION 12. ECOLOGICAL INFORMATION

Reacts with water so no ecotoxicity data for the substance is available. **Ecotoxicity effects**

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Tetrahydrofuran	2160 mg/l LC50 = 96 h	EC50 48 h 3485 mg/l		
	Pimephales promelas	EC50: >10000 mg/L/24h		

Page 8/10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

Leuciscus idus: LC50:		
2820 mg/L/48h		

Persistence and Degradability

Persistence Degradability

Degradation in sewage treatment plant

No information available

Persistence is unlikely, based on information available.

Reacts with water.

Reacts violently with water.

Bioaccumulative Potential

Product does not bioaccumulate due to reaction with water; Bioaccumulation is unlikely

Component		log Pow	Bioconcentration factor (BCF)			
	Tetrahydrofuran	0.45	No data available			

Mobility in soil

Reacts violently with water Is not likely mobile in the environment

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information			
Tetrahydrofuran	Group III Chemical					
Porsistant Organic Pollutant	This product does not contain	any known or suspected subst	tance			

Persistent Organic Pollutant **Ozone Depletion Potential**

This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN3399

Proper Shipping Name Technical Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Vinylmagnesium bromide, Tetrahydrofuran

Hazard Class

4.3 3

Subsidiary Hazard Class

Packing Group

IMDG/IMO

UN-No

Proper Shipping Name Technical Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE Vinylmagnesium bromide, Tetrahydrofuran

Hazard Class

4.3 3 **Subsidiary Hazard Class Packing Group** I

Page 9/10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

IATA

UN-No UN3399

Organometallic substance, liquid, water-reactive, flammable **Proper Shipping Name**

Technical Shipping Name Vinylmagnesium bromide, Tetrahydrofuran

Hazard Class 4.3 **Subsidiary Hazard Class** 3 **Packing Group** ı

Special Precautions for User No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	goods GB	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Tetrahydrofuran	X	X	Х	Х	203-726-8	Х	Х	Х	Х	Х	Χ	KE-33454
Magnesium, bromoethenvl-	-	-	X	-	217-375-3	Х	-	-	Х	X	-	KE-03717

National Regulations

SECTION 16. OTHER INFORMATION

09-May-2012 **Creation Date Revision Date** 07-Apr-2024 **Revision Summary** Not applicable.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

DNEL - Derived No Effect Level

PNEC - Predicted No Effect Concentration

Page 10 / 10 Revision Date 07-Apr-2024

Vinylmagnesium bromide, 0.7M solution in THF

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

vPvB - very Persistent, very Bioaccumulative

Dangerous Goods Code

LD50 - Lethal Dose 50%

IMO/IMDG - International Maritime Organization/International Maritime MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Physical hazards On basis of test data Calculation method **Health Hazards Environmental hazards** Calculation method

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet