

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name n-Butyllithium, 1.6M solution in hexanes

Recommended Use Laboratory chemicals. No Information available Uses advised against

Product Code 181270000; 181271000; 181275000; 181278000

Address Thermo Fisher Scientific New Zealand Ltd

> 244 Bush Road, Albany. Auckland, New Zealand

CHEMTREC® Emergency Tel.

09 980 6780 or +64 9 980 6780

Telephone / Fax Numbers Tel: 09 980 6700

Fax: 09 980 6788

E-mail address ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

GHS Classification

Physical hazards

Category 2 Flammable liquids

Substances/mixtures which, in contact with water, emit flammable gases Category 1

Pyrophoric liquids Category 1

Health hazards

Aspiration Toxicity Category 1 Category 1 B Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Category 1 Category 2 Reproductive Toxicity Specific target organ toxicity - (single exposure) Category 3

Specific target organ toxicity - (repeated exposure) Category 2

Environmental hazards

Chronic aquatic toxicity Category 2

Label Elements

ACR18127 Version 4 16-May-2024 Page 1/11



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H250 Catches fire spontaneously if exposed to air
- H260 In contact with water releases flammable gases which may ignite spontaneously
- H304 May be fatal if swallowed and enters airways
- H314 Causes severe skin burns and eye damage
- H336 May cause drowsiness or dizziness
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P222 Do not allow contact with air
- P223 Do not allow contact with water
- P231 + P232 Handle and store contents under inert gas. Protect from moisture
- P233 Keep container tightly closed
- P240 Ground and bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P273 Avoid release to the environment

Response

- P302 + P334 IF ON SKIN: Immerse in cool water or wrap in wet bandages
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor
- P330 Rinse mouth
- P331 Do NOT induce vomiting
- P363 Wash contaminated clothing before reuse
- P370 + P378 In case of fire: Use limestone powder, sodium chloride or dry sand to extinguish
- P391 Collect spillage

Storage

- P402 + P404 Store in a dry place. Store in a closed container
- P422 Store contents under inert gas

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

This product does not contain any known or suspected endocrine disruptors

Reacts violently with water

Section 3 - Composition and Information on Ingredients

ACR18127 Version 4 16-May-2024 Page 2/11

 Component
 CAS No
 Weight %

 Hexane
 110-54-3
 85

 Butvl lithium
 109-72-8
 15

Section 4 - First Aid Measures

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

New Zealand Emergency Tel. CHEMTREC®

09 980 6780 or +64 9 980 6780

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Dry chemical. Limestone powder. Dry sand. approved class D extinguishers. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO2). Foam.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

ACR18127 Version 4 16-May-2024 Page 3 / 11

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors, Butane.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Advice on safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep away from heat, sparks and flame. Keep under nitrogen. Keep refrigerated. Flammables area. Corrosives area. Keep away from water or moist air. Keep container tightly closed in a dry and well-ventilated place.

Incompatible Materials

Strong oxidizing agents. Halogens.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACR18127 Version 4 16-May-2024 Page 4/11

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Hexane	TWA: 20 ppm	TWA: 20 ppm	TWA: 50 ppm	TWA: 72 mg/m ³
	TWA: 72 mg/m ³	TWA: 72 mg/m ³	Skin	TWA: 20 ppm
	_	_		STEL: 60 ppm
				STEL: 216 mg/m ³

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological	United Kingdom
			Exposure Indices	
Hexane	5 mg/L (urine) end of shift		0.5 mg/L	
	(2,5-Hexanedione)		Medium: urine	
			Time: end of shift	
			Determinant:	
			2,5-Hexanedione without	
			hydrolysis	

Appropriate engineering controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber, Viton (R).	See manufacturers	-	AS/NZS 2161	(minimum requirement)
	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Repiratory ProtectionUse an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 (or AUS/NZ equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

ACR18127 Version 4 16-May-2024 Page 5/11

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Liquid

Appearance Yellow

Odor
Odor Threshold
Petroleum distillates
No data available
No information available
Melting Point/Range
Softening Point
No data available

Boiling Point/Range 60 - 80 °C / 140 - 176 °F @ 760 mmHg **Flammability (liquid)** Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.2 Vol%

Upper 7.8 Vol%

Flash Point -21 °C / -5.8 °F Method - (based on components)

Autoignition Temperature

Decomposition Temperature

Viscosity

Water Solubility

Solubility in other solvents

240 °C / 464 °F

No data available

No data available

Reacts with water

No information available

Partition Coefficient (n-octanol/water)

Componentlog PowHexane4.11

Vapor Pressure 160 mbar @ 20 °C

Density / Specific Gravity 0.680

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

Other information

Explosive Properties Vapors may form explosive mixtures with air

Substances/mixtures which, in Emitted gas ignites spontaneously **contact with water, emit flammable** Gas(es) = Butane

gases

Section 10 - Stability and Reactivity

Reactivity Yes

Stability Water reactive. Reacts violently with water. Air sensitive.

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

Conditions to Avoid Incompatible products, Heat, flames and sparks, Exposure to moist air or water, Exposure

ACR18127 Version 4 16-May-2024 Page 6 / 11

to air, Exposure to moisture, Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials Strong oxidizing agents, Halogens.

Hazardous Decomposition Products Carbon monoxide (CO₂). Thermal decomposition can lead to release

of irritating gases and vapors. Butane.

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation Causes burns. May cause drowsiness and dizziness. May be harmful if inhaled.

Eyes Causes burns.

Skin Causes burns. May be harmful in contact with skin.

Ingestion Causes burns. Aspiration hazard. May be harmful if swallowed. Harmful if swallowed.

Potential for aspiration if swallowed.

Numerical measures of toxicity

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h	

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Reproductive Effects Possible risk of impaired fertility

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

ACR18127 Version 4 16-May-2024 Page 7 / 11

(i) STOT-repeated exposure; Category 2

Target Organs Eyes, Respiratory system, Skin, Gastrointestinal tract (GI), Central nervous system (CNS),

Liver, Peripheral Nervous System (PNS).

(j) aspiration hazard; Category 1

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects,both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. The product contains following substances which are hazardous for the

environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	9		

Terrestrial ecotoxicity There is no data for this product

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.

Degradation in sewage treatment

plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)		
Hexane	4.11	No data available		

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

Other adverse effects

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Do not allow into drains or watercourses or dispose of where ground or surface waters may

ACR18127 Version 4 16-May-2024 Page 8 / 11

Products be affected. Wastes, including emptied containers, are controlled wastes and should be

disposed of in accordance with all federal, E.P.A., state and local regulations. Assure

conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Disposal agencies or waste contractors must comply with the New Zealand Hazardous

Substances (Disposal) Regulations . Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical

enter the environment.

Section 14 - Transport Information

NZS 5433:2020

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Technical Shipping Name Hexane, Butyl lithium

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

IATA FORBIDDEN FOR IATA TRANSPORT

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

FORBIDDEN FOR IATA TRANSPORT

Technical Shipping Name Hexane, Butyl lithium

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

IMDG/IMO

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Technical Shipping Name Hexane, Butyl lithium

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

Component	IMDG Marine Pollutant
Hexane	IMDG regulated marine pollutant (Listed in the index)
110-54-3 (85)	

Environmental hazards Dangerous for the environment

Product is a marine pollutant according to the criteria set by IMDG/IMO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable, packaged goods

Special PrecautionsNo special precautions required. Please refer to the applicable dangerous goods regulations for additional information.

Additional information None known

Section 15 - Regulatory Information

ACR18127 Version 4 16-May-2024 Page 9 / 11

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	IMDG Marine Pollutant
Hexane			IMDG regulated marine pollutant (Listed in the index)

Authorisation/Restrictions according to EU REACH

Component	_ (REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Hexane	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
Hexane	110-54-3	Х	Х	203-777-6	438-390-3	-	KE-18626	X	Х
Butyl lithium	109-72-8	Х	Х	203-698-7	-	-	KE-04320	Х	Х

	Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
	Hexane	110-54-3	Х	ACTIVE	X	-	Х	Х	Х
Γ	Butyl lithium	109-72-8	X	ACTIVE	X	-	X	X	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

ACR18127 Version 4 16-May-2024 Page 10 / 11

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

<u>Legend</u>

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer NZS 5433:2020 - Transport of Dangerous Goods on Land

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% WEL - Workplace Exposure Limit DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water **vPvB** - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

AICS - Australian Inventory of Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

PNEC - Predicted No Effect Concentration

OECD - Organisation for Economic Co-operation and Development **IMO/IMDG** - International Maritime Organization/International Maritime

Dangerous Goods Code

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

LC50 - Lethal Concentration 50% **ATE** - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment **NOEC** - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data
Health Hazards Calculation method
Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Revision Date 16-May-2024

Revision Summary Update to GHS format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

ACR18127 Version 4 16-May-2024 Page 11 / 11