

according to Regulation (EC) No. 1907/2006

Revision Date 30-Nov-2024 Revision Number 4

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Cat No.: 38778

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH

Erlenbachweg 2, 76870 Kandel, Germany

Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300

**Swiss distributor -** Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

https://www.fishersci.ch/ch/en/customer-help-

support/forms/email-us.html

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

#### **Section 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Revision Date 30-Nov-2024

#### **Physical hazards**

Based on available data, the classification criteria are not met

#### **Health hazards**

Carcinogenicity Category 2 (H351)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Warning

#### **Hazard Statements**

H351 - Suspected of causing cancer Combustible liquid

#### **Precautionary Statements**

P201 - Obtain special instructions before use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

#### 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No
				1272/2008
Fuels, diesel, no. 2	68476-34-6	EEC No. 270-676-1	90.9	Carc. 2 (H351)
Butane, 1,1-thiobis-	544-40-1	EEC No. 208-870-5	9.10	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Full text of Hazard Statements: see section 16

## **Section 4: First aid measures**

#### 4.1. Description of first aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

#### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

## Section 5: Firefighting measures

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Combustible material. Containers may explode when heated.

#### **Hazardous Combustion Products**

None under normal use conditions.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Revision Date 30-Nov-2024

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **Section 7: Handling and storage**

#### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

**Technical Rules for Hazardous Substances (TRGS) 510** 

Storage Class (LGK) (Germany)

Storage Class/LGK 10

Switzerland - Storage of hazardous substances Storage class - SC 10/12

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

#### 7.3. Specific end use(s)

Use in laboratories

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Exposure limits**

List source(s):

Component	European Union	The United Kingdom	France	Belgium	Spain
Fuels, diesel, no. 2				TWA: 100 mg/m <sup>3</sup> 8 uren	
				Huid	

Component	Italy	Germany	Portugal	The Netherlands	Finland
Fuels, diesel, no. 2			TWA: 100 mg/m <sup>3</sup> 8		
			horas		
			Pele		

Revision Date 30-Nov-2024

#### **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Fuels, diesel, no. 2				DNEL = 2.91mg/kg
68476-34-6 ( 90.9 )				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Fuels, diesel, no. 2		DNEL = 4288mg/m <sup>3</sup>		$DNEL = 68.34 \text{mg/m}^3$
68476-34-6 ( 90.9 )				_

#### **Predicted No Effect Concentration (PNEC)**

No information available.

#### 8.2. Exposure controls

#### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection Long sleeved clothing.

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Revision Date 30-Nov-2024

Inspect gloves before use, observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task; Chemical compatability. Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

> are exceeded or if irritation or other symptoms are experienced Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water

system.

## Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Liquid **Physical State** 

**Appearance** Light brown

Petroleum distillates Odor No data available **Odor Threshold Melting Point/Range** No data available **Softening Point** No data available

**Boiling Point/Range** 171 - 315 °C / 339.8 - 599 °F

Flammability (liquid) Combustible liquid On basis of test data

Flammability (solid, gas) Not applicable Liquid

No data available **Explosion Limits** 

69 °C / 156.2 °F Method - No information available **Flash Point** 

500 °C / 932 °F **Autoignition Temperature Decomposition Temperature** No data available рΗ No information available **Viscosity** No data available Water Solubility No information available Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

**Vapor Pressure** No data available Density / Specific Gravity @ 20 °C 0.75 g/cm3 Not applicable **Bulk Density** Liquid **Vapor Density** No data available (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

**Explosive Properties** explosive air/vapour mixtures possible

## Section 10: Stability and reactivity

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous PolymerizationNo information available.Hazardous ReactionsNone under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Revision Date 30-Nov-2024

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

## **Section 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

DermalNo data availableInhalationNo data available

## Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Fuels, diesel, no. 2	-	LD50 > 2000 mg/kg (Rabbit)	LC50 = 5.4 mg/L (Rat)4 h LC50 = 3.6 mg/L (Rat)4 h
Butane, 1,1-thiobis-	LD50 = 2220 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

\_\_\_\_\_

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

(h) STOT-single exposure; No data available

No data available (i) STOT-repeated exposure;

None known. **Target Organs** 

No data available (j) aspiration hazard;

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

delayed

11.2. Information on other hazards

Assess endocrine disrupting properties for human health. This product does not contain any **Endocrine Disrupting Properties** 

known or suspected endocrine disruptors.

## **Section 12: Ecological information**

12.1. Toxicity

**Ecotoxicity effects** The product contains following substances which are hazardous for the environment. Toxic

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae		
Fuels, diesel, no. 2	LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)				
Butane, 1,1-thiobis-	LC50: = 3.58 mg/L, 96h flow-through (Pimephales promelas)				

12.2. Persistence and degradability No information available

Degradation in sewage Contains substances known to be hazardous to the environment or not degradable in waste

treatment plant water treatment plants.

12.3. Bioaccumulative potential No information available

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB No data available for assessment.

assessment

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

#### 12.7. Other adverse effects

**ALFAA38778** 

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

**Persistent Organic Pollutant** This product does not contain any known or suspected substance **Ozone Depletion Potential** This product does not contain any known or suspected substance

## **Section 13: Disposal considerations**

13.1. Waste treatment methods

Waste from Residues/Unused **Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Dispose of this container to hazardous or special waste collection point. **Contaminated Packaging** 

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

## **Section 14: Transport information**

IMDG/IMO Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es) 14.4. Packing group

ADR Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards No hazards identified

No special precautions required. 14.6. Special precautions for user

14.7. Maritime transport in bulk

according to IMO instruments

Not applicable, packaged goods

## **Section 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**ALFAA38778** 

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

	Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ī	Fuels, diesel, no. 2	68476-34-6	270-676-1	-	-	X	X	KE-17287	-	-
Ī	Butane, 1,1-thiobis-	544-40-1	208-870-5	-	-	Х	X	-	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Fuels, diesel, no. 2	68476-34-6	X	ACTIVE	X	-	X	Х	Х
Butane, 1,1-thiobis-	544-40-1	Х	ACTIVE	Χ	-	Х	Χ	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Fuels, diesel, no. 2	68476-34-6	-	Use restricted. See entry 75. (see link for restriction details)	-
Butane, 1,1-thiobis-	544-40-1	=	-	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Fuels, diesel, no. 2	68476-34-6	Not applicable	Not applicable
Butane, 1,1-thiobis-	544-40-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Fuels, diesel, no. 2	WGK2	

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Butane, 1.1-thiobis-WGK2

#### **Swiss Regulations**

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

#### 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

#### **Section 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3

H351 - Suspected of causing cancer

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 30-Nov-2024

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Shins

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Sulfur in Diesel Fuel standard solution, Specpure®, 20,000 µg/g (2.00%)

Prepared By Health, Safety and Environmental Department

Revision Date 30-Nov-2024 Revision Summary Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No. 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**

ALFAA38778