

SAFETY DATA SHEET

Creation Date 23-January-2013

Revision Date 16-January-2023

Revision Number 9

1. Identification

Product Name Lithium triethylborohydride, 1.7M solution in THF

Cat No. : AC450690000; AC450691000; AC450698000

Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor
Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Manufacturer

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 2	
Substances/mixtures which, in contact with water, emit flammable gases	Category 1	Gas(es) = Hydrogen
Pyrophoric liquids	Category 1	
Skin Corrosion/Irritation	Category 1 A	
Serious Eye Damage/Eye Irritation	Category 1	
Carcinogenicity	Category 2	
Specific target organ toxicity (single exposure)	Category 3	
Target Organs - Respiratory system, Central nervous system (CNS).		
Physical Hazards Not Otherwise Classified	Category 1	
Reacts violently with water		
May form explosive peroxides		

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Catches fire spontaneously if exposed to air

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness and dizziness

Suspected of causing cancer

Reacts violently with water

May form explosive peroxides

**Precautionary Statements****Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Do not allow contact with water

Keep container tightly closed

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not allow contact with air

Handle under inert gas. Protect from moisture

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

IF ON SKIN: Immerse in cool water or wrap

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER/doctor

Wash contaminated clothing before reuse

In case of fire: Use limestone powder, sodium chloride or dry sand to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store contents under inert gas

Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
-----------	--------	----------

Tetrahydrofuran	109-99-9	80
Lithium triethylhydroborate	22560-16-3	20

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Most important symptoms/effects	Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Causes central nervous system depression
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Dry sodium chloride. Limestone powder.
Unsuitable Extinguishing Media	Water, Carbon dioxide (CO ₂), Foam
Flash Point	-17 °C / 1.4 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Reacts violently with water. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Hydrogen. Carbon monoxide (CO). Carbon dioxide (CO₂). Oxides of boron. Lithium oxide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3Flammability
4Instability
2Physical hazards
W

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water.

7. Handling and storage

Handling

Handle under inert gas, protect from moisture. Do not allow contact with water. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe mist/vapors/spray.

Storage.

Keep under nitrogen. Keep away from water or moist air. Shelf life 12 months. Flammables area. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Incompatible Materials. Acids. Bases. Water. Alcohols. Bromine. oxygen.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWA/EV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
Tetrahydrofuran	TWA: 50 ppm TWA: 147 mg/m ³ STEL: 100 ppm STEL: 295 mg/m ³ Skin	TWA: 50 ppm STEL: 100 ppm Skin	TWA: 50 ppm STEL: 100 ppm Skin	TWA: 100 ppm TWA: 300 mg/m ³	TWA: 50 ppm STEL: 100 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 2000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 250 ppm STEL: 735 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	See manufacturers	-	Splash protection only
Nitrile rubber	recommendations		
Viton (R)			

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless to yellow
Odor	No information available
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	-17 °C / 1.4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	0.89
Solubility	Reacts violently with water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity

Reactive Hazard

Yes

Stability

May form explosive peroxides. Reacts violently with water. Moisture sensitive. Air sensitive. Pyrophoric: Spontaneously flammable in air.

Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Exposure to moist air or water. Exposure to moisture.
Incompatible Materials	Acids, Bases, Water, Alcohols, Bromine, oxygen
Hazardous Decomposition Products	Hydrogen, Carbon monoxide (CO), Carbon dioxide (CO ₂), Oxides of boron, Lithium oxide
Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing. Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity Limited evidence of a carcinogenic effect.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Tetrahydrofuran	109-99-9	Group 2B	Not listed	A3	X	A3
Lithium triethylhydroborate	22560-16-3	Not listed	Not listed	Not listed	Not listed	Not listed

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Causes central nervous system depression

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Tetrahydrofuran	Group III Chemical	Not applicable	Not applicable

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Tetrahydrofuran	Not listed	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	Not listed	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment.

Component	log Pow
Tetrahydrofuran	0.45

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Tetrahydrofuran - 109-99-9	U213	-

14. Transport information

DOT

UN-No UN3394
Proper Shipping Name consumer commodity Organometallic substance, liquid, pyrophoric, water-reactive
Technical Name Tetrahydrofuran, Lithium triethylhydroborate
Hazard Class 4.2
Subsidiary Hazard Class 3
Packing Group I

TDG

UN-No UN3394
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I

IATA

FORBIDDEN FOR IATA TRANSPORT
 UN-No UN3394
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
 FORBIDDEN FOR IATA TRANSPORT
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I

IMDG/IMO

UN-No UN3394
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Tetrahydrofuran	109-99-9	X	-	X	ACTIVE	203-726-8	-	-
Lithium triethylhydroborate	22560-16-3	-	-	-	-	245-076-8	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	KE-33454	X	X	X	X	X	X
Lithium triethylhydroborate	22560-16-3	X	KE-22601	-	-	X	-	X	-

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Tetrahydrofuran	Part 5, Individual Substances Part 4 Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Tetrahydrofuran	109-99-9	Listed	Not applicable	Not applicable	Not applicable
Lithium triethylhydroborate	22560-16-3	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Tetrahydrofuran	109-99-9	Not applicable	Not applicable	Not applicable	Not applicable

Lithium triethylhydroborate	22560-16-3	Not applicable	Not applicable	Not applicable	Not applicable
-----------------------------	------------	----------------	----------------	----------------	----------------

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	23-January-2013
Revision Date	16-January-2023
Print Date	16-January-2023
Revision Summary	This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS