

## **SAFETY DATA SHEET**

Revision Date 10-Sep-2024 Revision Number 4

## 1. Identification

Product Name Beryllium wire

Cat No.: 42471

**CAS No** 7440-41-7

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

### Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill. MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute oral toxicity

Acute Inhalation Toxicity - Dusts and Mists

Category 2
Skin Corrosion/Irritation

Category 2
Serious Eye Damage/Eye Irritation

Skin Sensitization

Carcinogenicity

Carcinogenicity

Category 1
Category 1
Category 1
Category 3

Target Organs - Respiratory system.

Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Lungs.

## Label Elements

Beryllium wire Revision Date 10-Sep-2024

#### Signal Word

Danger

#### **Hazard Statements**

Toxic if swallowed

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Fatal if inhaled

May cause respiratory irritation

May cause cancer by inhalation

Causes damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

#### Response

IF exposed or concerned: Get medical attention/advice

## Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

### Skin

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

## **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

#### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

WARNING. Cancer - https://www.p65warnings.ca.gov/.

## 3. Composition/Information on Ingredients

Beryllium wire Revision Date 10-Sep-2024

Component	CAS No	Weight %
Beryllium	7440-41-7	> 99

## 4. First-aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice. Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

None reasonably foreseeable. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and

feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical.

Unsuitable Extinguishing Media No information available

Flash Point No information available Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available

Specific Hazards Arising from the Chemical

Sensitivity to Static Discharge

Keep product and empty container away from heat and sources of ignition.

Not applicable

No information available

#### **Hazardous Combustion Products**

Beryllium oxide.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards400N/A

## 6. Accidental release measures

Personal Precautions Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust

Beryllium wire

formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe

areas

Environmental Precautions Should not be released into the environment. Do not allow material to contaminate ground

water system. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

7. Handling and storage

Handling Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face

protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical

assistance.

Storage. Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Incompatible

Materials. Acids. Bases. Halogens. Metals.

## 8. Exposure controls / personal protection

## **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Beryllium	TWA: 0.00005 mg/m <sup>3</sup>	(Vacated) TWA: 2 µg/m <sup>3</sup>	IDLH: 4 mg/m <sup>3</sup>	TWA: 0.00005 mg/m <sup>3</sup>
	_	Ceiling: 2 µg/m <sup>3</sup>	Ceiling: 0.0005 mg/m <sup>3</sup>	
		(Vacated) STEL: 25 µg/m³		
		(Vacated) Ceiling: 5 µg/m <sup>3</sup>		
		TWA: 0.2 μg/m <sup>3</sup>		
		STEL: 2 µg/m³		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations

and safety showers are close to the workstation location.

**Personal Protective Equipment** 

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended Filter type:** Particulates filter conforming to EN 143.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

#### Physical and chemical properties

Physical StateSolidAppearanceDark greyOdorOdorless

Odor Threshold No information available

Beryllium wire Revision Date 10-Sep-2024

pH No information available Melting Point/Range 1278 °C / 2332.4 °F

Boiling Point/Range 2970 °C / 5378 °F @ 5 mmHg

Flash Point No information available

Evaporation Rate Not applicable

Flammability (solid,gas) No information available

Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor Pressure1.85 mmHgVapor DensityNot applicable

Specific Gravity

No information available

Bulk Density1.85 @ 20°CSolubilityinsolublePartition coefficient; n-octanol/waterNo data available

Autoignition Temperature Not applicable

**Decomposition Temperature**No information available

Viscosity Not applicable

Molecular FormulaBeMolecular Weight9.01

## 10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable.

Conditions to Avoid Incompatible products.

Incompatible Materials Acids, Bases, Halogens, Metals

Hazardous Decomposition Products Beryllium oxide

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

## 11. Toxicological information

**Acute Toxicity** 

Product Information Component Information

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** No information available

Sensitization May cause sensitization by skin contact

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Beryllium	7440-41-7	Group 1	Known	A1	X	A1

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

NTP: (National Toxicity Program)

Known - Known Carcinogen

Beryllium wire

ACGIH: (American Conference of Governmental Industrial

Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

**Mutagenic Effects** No information available

**Reproductive Effects** No information available. No information available. **Developmental Effects Teratogenicity** No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure Lungs

No information available **Aspiration hazard** 

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

**Ecotoxicity** 

May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Persistence and Degradability Insoluble in water May persist

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Is not likely mobile in the environment due its low water solubility.

# 13. Disposal considerations

Chemical waste generators must determine whether a discarded chemical is classified as a **Waste Disposal Methods** 

hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

	Component	RCRA - U Series Wastes	RCRA - P Series Wastes
1	Beryllium - 7440-41-7	=	powder

14. Transport information
---------------------------

DOT Not regulated Not regulated TDG Not regulated IATA IMDG/IMO Not regulated

## 15. Regulatory information

United States of America Inventory

### Beryllium wire

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Beryllium	7440-41-7	X	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

#### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Beryllium	7440-41-7	Х	-	231-150-7	Χ	Χ		Х	Х	KE-02829

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Beryllium	7440-41-7	> 99	0.1 %	-

#### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)** 

OTTA (Olcail Hatel Act)				
Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Beryllium	-	-	X	X

## Clean Air Act

**OSHA** - Occupational Safety and

Not applicable

Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Beryllium	0.2 μg/m³ TWA	-
	0.1 μg/m³ Action Level	
	2.0 μg/m³ STEL	

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Beryllium	10 lb	-	10 lb

## Beryllium wire

	4.54 ka

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category	
Beryllium	7440-41-7	Carcinogen	0.1 μg/day	Carcinogen	

# U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Beryllium	X	X	Χ	X	X

**U.S. Department of Transportation** 

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Beryllium	7440-41-7	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Beryllium	7440-41-7	Not applicable	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

## Other International Regulations

	Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Į			Qualifying Quantities Qualifying Quantities			

## Beryllium wire

		for Major Accident Notification	for Safety Report Requirements		
Beryllium	7440-41-7	Not applicable	Not applicable	Not applicable	Annex I - Y20

16. Other information

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Revision Date 10-Sep-2024 Print Date 10-Sep-2024

**Revision Summary** New emergency telephone response service provider.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**