

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Ethanol absolute, 100%, denatured with 2% v/v cyclohexane**
Cat No. : **R13901**
REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Flammable liquids	Category 2 (H225)
<u>Health hazards</u>	
Aspiration Toxicity	Category 1 (H304)
<u>Environmental hazards</u>	
Chronic aquatic toxicity	Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331 - Do NOT induce vomiting
P405 - Store locked up
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethyl alcohol	64-17-5	EEC No. 200-578-6	98	Flam. Liq. 2 (H225)
Cyclohexane	110-82-7	203-806-2	2	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336)

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

				Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
--	--	--	--	--

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Cyclohexane	-	1	-

REACH registration number	-
---------------------------	---

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Hazardous Combustion Products

Carbon oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl alcohol		STEL: 3000 ppm 15 min STEL: 5760 mg/m ³ 15 min TWA: 1000 ppm 8 hr TWA: 1920 mg/m ³ 8 hr	TWA / VME: 1000 ppm (8 heures). TWA / VME: 1900 mg/m ³ (8 heures). STEL / VLCT: 5000 ppm. STEL / VLCT: 9500 mg/m ³ .	TWA: 1000 ppm 8 uren TWA: 1907 mg/m ³ 8 uren	STEL / VLA-EC: 1000 ppm (15 minutos). STEL / VLA-EC: 1910 mg/m ³ (15 minutos).
Cyclohexane	TWA: 200 ppm (8hr) TWA: 700 mg/m ³ (8hr)	STEL: 300 ppm 15 min STEL: 1050 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 350 mg/m ³ 8 hr	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 700 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 375 ppm. restrictive limit STEL / VLCT: 1300 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ .	TWA: 100 ppm 8 uren TWA: 350 mg/m ³ 8 uren	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 700 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl alcohol		TWA: 200 ppm (8 Stunden). AGW - exposure factor 4 TWA: 380 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 200 ppm (8 Stunden). MAK TWA: 380 mg/m ³ (8 Stunden). MAK Höhepunkt: 800 ppm Höhepunkt: 1520 mg/m ³	STEL: 1000 ppm 15 minutos	huid STEL: 1900 mg/m ³ 15 minuten TWA: 260 mg/m ³ 8 uren	TWA: 1000 ppm 8 tunteina TWA: 1900 mg/m ³ 8 tunteina STEL: 1300 ppm 15 minuutteina STEL: 2500 mg/m ³ 15 minuutteina
Cyclohexane	TWA: 100 ppm 8 ore. Time Weighted Average TWA: 350 mg/m ³ 8 ore. Time Weighted Average	TWA: 200 ppm (8 Stunden). AGW - exposure factor 4 TWA: 700 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 200 ppm (8 Stunden). MAK TWA: 700 mg/m ³ (8 Stunden). MAK Höhepunkt: 800 ppm Höhepunkt: 2800 mg/m ³	TWA: 200 ppm 8 horas TWA: 700 mg/m ³ 8 horas	STEL: 1400 mg/m ³ 15 minuten TWA: 700 mg/m ³ 8 uren	TWA: 100 ppm 8 tunteina TWA: 350 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 875 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethyl alcohol	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 3800	TWA: 1000 ppm 8 timer TWA: 1900 mg/m ³ 8 timer	STEL: 1000 ppm 15 Minuten STEL: 1920 mg/m ³ 15	TWA: 1900 mg/m ³ 8 godzinach	TWA: 500 ppm 8 timer TWA: 950 mg/m ³ 8 timer STEL: 625 ppm 15

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

	mg/m ³ 15 Minuten MAK-TMW: 1000 ppm 8 Stunden MAK-TMW: 1900 mg/m ³ 8 Stunden	STEL: 2000 ppm 15 minutter STEL: 3800 mg/m ³ 15 minutter	Minuten TWA: 500 ppm 8 Stunden TWA: 960 mg/m ³ 8 Stunden		minutter. value calculated STEL: 1187.5 mg/m ³ 15 minutter. value calculated
Cyclohexane	MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 2800 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 700 mg/m ³ 8 Stunden	TWA: 50 ppm 8 timer TWA: 172 mg/m ³ 8 timer STEL: 100 ppm 15 minutter STEL: 344 mg/m ³ 15 minutter	STEL: 800 ppm 15 Minuten STEL: 2800 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 700 mg/m ³ 8 Stunden	STEL: 1000 mg/m ³ 15 minutach TWA: 300 mg/m ³ 8 godzinach	TWA: 150 ppm 8 timer TWA: 525 mg/m ³ 8 timer STEL: 187.5 ppm 15 minutter. value calculated STEL: 656.25 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl alcohol	TWA: 1000 mg/m ³	TWA-GVI: 1000 ppm 8 satima. TWA-GVI: 1900 mg/m ³ 8 satima.	STEL: 1000 ppm 15 min		TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 3000 mg/m ³
Cyclohexane	TWA: 200 ppm TWA: 700.0 mg/m ³	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 700 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 700 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 2100 mg/m ³ 15 min	TWA: 200 ppm TWA: 700 mg/m ³	TWA: 700 mg/m ³ 8 hodinách. Ceiling: 2000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl alcohol	TWA: 500 ppm 8 tundides. TWA: 1000 mg/m ³ 8 tundides. STEL: 1000 ppm 15 minutites. STEL: 1900 mg/m ³ 15 minutites.		TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 3800 mg/m ³ 15 percekben. CK TWA: 1900 mg/m ³ 8 óraban. AK	TWA: 1000 ppm 8 klukkustundum. TWA: 1900 mg/m ³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3800 mg/m ³
Cyclohexane	TWA: 200 ppm 8 tundides. TWA: 700 mg/m ³ 8 tundides.	TWA: 200 ppm 8 hr TWA: 700 mg/m ³ 8 hr	TWA: 200 ppm TWA: 700 mg/m ³	TWA: 700 mg/m ³ 8 óraban. AK	TWA: 50 ppm 8 klukkustundum. TWA: 175 mg/m ³ 8 klukkustundum. Ceiling: 100 ppm Ceiling: 350 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl alcohol	TWA: 1000 mg/m ³	TWA: 500 ppm IPRD TWA: 1000 mg/m ³ IPRD STEL: 1000 ppm STEL: 1900 mg/m ³			TWA: 1000 ppm 8 ore TWA: 1900 mg/m ³ 8 ore STEL: 5000 ppm 15 minute STEL: 9500 mg/m ³ 15 minute
Cyclohexane	TWA: 23 ppm TWA: 80 mg/m ³	TWA: 200 ppm IPRD TWA: 700 mg/m ³ IPRD	TWA: 200 ppm 8 Stunden TWA: 700 mg/m ³ 8 Stunden	TWA: 200 ppm TWA: 700 mg/m ³	TWA: 200 ppm 8 ore TWA: 700 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl alcohol	TWA: 1000 mg/m ³ 2391 MAC: 2000 mg/m ³	Ceiling: 1920 mg/m ³ TWA: 500 ppm TWA: 960 mg/m ³	TWA: 960 mg/m ³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15 minutah STEL: 1920 mg/m ³ 15 minutah	Indicative STEL: 1000 ppm 15 minuter Indicative STEL: 1900 mg/m ³ 15 minuter TLV: 500 ppm 8 timmar. NGV TLV: 1000 mg/m ³ 8 timmar. NGV	
Cyclohexane	MAC: 80 mg/m ³	TWA: 200 ppm TWA: 700 mg/m ³	TWA: 200 ppm 8 urah TWA: 700 mg/m ³ 8 urah STEL: 2800 mg/m ³ 15 minutah STEL: 800 ppm 15 minutah	TLV: 200 ppm 8 timmar. NGV TLV: 700 mg/m ³ 8 timmar. NGV	TWA: 200 ppm 8 saat TWA: 700 mg/m ³ 8 saat

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Cyclohexane					total 1,2-Cyclohexanediol (after hydrolysis): 150 mg/g Creatinine urine (end of shift) total 1,2-Cyclohexanediol (after hydrolysis): 150 mg/g Creatinine urine (for long-term exposures: at the end of the shift after several shifts)

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 (98)				DNEL = 343mg/kg bw/day
Cyclohexane 110-82-7 (2)				DNEL = 2016mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 (98)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
Cyclohexane 110-82-7 (2)	DNEL = 1400mg/m ³	DNEL = 1400mg/m ³	DNEL = 700mg/m ³	DNEL = 700mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Cyclohexane 110-82-7 (2)	PNEC = 0.207mg/L	PNEC = 16.68mg/kg sediment dw	PNEC = 0.207mg/L	PNEC = 3.24mg/L	PNEC = 3.38mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
-----------	--------------	--------------------------	------------------------------	------------	-----

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Cyclohexane 110-82-7 (2)	PNEC = 0.207mg/L	PNEC = 16.68mg/kg sediment dw			
-------------------------------	------------------	-------------------------------------	--	--	--

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	-90 °C / -130 °F	
Softening Point	No data available	
Boiling Point/Range	78 °C / 172.4 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Explosion Limits	No data available	
Flash Point	13 °C / 55.4 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	Not applicable	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl alcohol	-0.35	
Cyclohexane	3.44	
Vapor Pressure	No data available	
Density / Specific Gravity	0.798	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	-	LC50 = 116.9 mg/L (Rat) 4 h LC50 = 133.8 mg/L (Rat) 4 h
Cyclohexane	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	LC50 > 32880 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available

Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment.
Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	LC50: 13400 - 15100 mg/L, 96h flow-through (Pimephales promelas) LC50: > 100 mg/L, 96h static (Pimephales promelas)	LC50: 9268 - 14221 mg/L, 48h (Daphnia magna) EC50: = 2 mg/L, 48h Static (Daphnia magna)	

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

	LC50: 12.0 - 16.0 mL/L, 96h static (Oncorhynchus mykiss)		
Cyclohexane	LC50: 48.87 - 68.76 mg/L, 96h static (Poecilia reticulata) LC50: 24.99 - 44.69 mg/L, 96h static (Lepomis macrochirus) LC50: 23.03 - 42.07 mg/L, 96h static (Pimephales promelas) LC50: 3.96 - 5.18 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.9 mg/l/48h	EC50 >500 mg/L/72h

Component	Microtox	M-Factor
Ethyl alcohol	= 34634 mg/L EC50 Photobacterium phosphoreum 30 min = 35470 mg/L EC50 Photobacterium phosphoreum 5 min	
Cyclohexane	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	1

12.2. Persistence and degradability

No information available

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Cyclohexane 110-82-7 (2)	77% (28d)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.35	No data available
Cyclohexane	3.44	83.15

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN1987
14.2. UN proper shipping name	ALCOHOLS, N.O.S.
Technical Shipping Name	Ethanol/cyclohexane
14.3. Transport hazard class(es)	3
14.4. Packing group	II

ADR

14.1. UN number	UN1987
14.2. UN proper shipping name	ALCOHOLS, N.O.S.
Technical Shipping Name	Ethanol/cyclohexane
14.3. Transport hazard class(es)	3
14.4. Packing group	II

IATA

14.1. UN number	UN1987
14.2. UN proper shipping name	ALCOHOLS, N.O.S.
Technical Shipping Name	Ethanol/cyclohexane
14.3. Transport hazard class(es)	3
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC),

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Japan (ENCS), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Cyclohexane	110-82-7	203-806-2	-	-	X	X	KE-18562	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Cyclohexane	110-82-7	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Cyclohexane	110-82-7	-	Use restricted. See item 57. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Cyclohexane	110-82-7	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
-----------	---------------------------------------	-------------------------

ALFAAR13901

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Ethyl alcohol	WGK1	
Cyclohexane	WGK2	

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Cyclohexane	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (98)		Group I	
Cyclohexane 110-82-7 (2)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways
H412 - Harmful to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

SAFETY DATA SHEET

Ethanol absolute, 100%, denatured with 2% v/v cyclohexane

Revision Date 22-Mar-2024

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By	Health, Safety and Environmental Department
Revision Date	22-Mar-2024
Revision Summary	New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet