

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Q133 SUPER JET PLUS [USE Q13347] 10L

Material number : Q13342C

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	amber, colourless
Odour	characteristic

GHS Classification

Skin corrosion : Category 1

Serious eye damage : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Corrosion

Exclamation
mark

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

H317 May cause an allergic skin reaction.

Precautionary statements

: **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium xylenesulphonate	1300-72-7	>= 10 - < 30
sodium dodecylbenzenesulfonate	25155-30-0	>= 5 - < 10
2-aminoethanol	141-43-5	>= 5 - < 10
sodium hydroxide	1310-73-2	>= 5 - < 10
tetrasodium ethylenediaminetetraacetate	64-02-8	>= 5 - < 10
Alcohols, C9-11, ethoxylated	68439-46-3	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 1 - < 5
Undecan-1-ol, ethoxylated	34398-01-1	>= 1 - < 5
undecan-1-ol	112-42-5	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact	: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration, contact time). Causes severe skin burns and eye damage. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Sulphur oxides Smoke

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

Specific extinguishing methods	Nitrogen oxides (NOx) : Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Neutralise with acid. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents Do not store near acids.

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-aminoethanol	141-43-5	STEL	6 ppm 15 mg/m ³	CA AB OEL
		TWA	3 ppm 7.5 mg/m ³	CA AB OEL
		TWA	3 ppm	CA BC OEL
		STEL	6 ppm	CA BC OEL
		TWAEV	3 ppm 7.5 mg/m ³	CA QC OEL
		STEV	6 ppm 15 mg/m ³	CA QC OEL
		TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
sodium hydroxide	1310-73-2	(c)	2 mg/m ³	CA AB OEL
		C	2 mg/m ³	CA BC OEL
		C	2 mg/m ³	CA QC OEL
		C	2 mg/m ³	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

Eye protection	: Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: amber, colourless
Odour	: characteristic
Odour Threshold	: No data available
pH	: 12.5 - 13
Melting point/freezing point	: No data available
Boiling point	: 100 °C
Flash point	: does not flash
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.158 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Acids Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes severe skin burns and eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

2-butoxyethanol

111-76-2

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,082 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

sodium dodecylbenzenesulfonate:

Acute oral toxicity : LD50 Oral Rat: 438 mg/kg

2-aminoethanol:

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

undecan-1-ol:

Acute oral toxicity : LD50 Oral Rat: 3,000 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 3,960 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

undecan-1-ol:

Classification: May cause sensitisation by skin contact.

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

Components:

tetrasodium ethylenediaminetetraacetate:

Exposure routes: Inhalation

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

sodium hydroxide :

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l
Exposure time: 96 h
Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):
152 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

2-aminoethanol :

Partition coefficient: n-octanol/water : log Pow: -1.31

undecan-1-ol :

Partition coefficient: n-octanol/water : log Pow: 4.384

log Pow: 4.72

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

sodium hydroxide :

Additional ecological information : Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
--

SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA

On TSCA Inventory

DSL

All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms



SAFETY DATA SHEET

Q133 SUPER JET PLUS [USE Q13347] 10L

Version 1.2

Revision Date 10/01/2023

Print Date 04/28/2025

Signal word : **Danger:**
Hazard statements : Causes severe skin burns and eye damage. May cause an allergic skin reaction.
Precautionary statements :
Prevention: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.2
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.