

#### To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name/designation** Getriebeöl, ATF DCT **Partno** A 001 989 85 03 13

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use

Transmission oil

## 1.3 Details of the supplier of the safety data sheet

#### Supplier

Mercedes-Benz USA, LLC. One Mercedes-Benz Dr. Sandy Springs, GA 30328-4312 +1 770 705 0600

#### Manufacturer

Mercedes-Benz AG

70546 Stuttgart Germany

Telephone +49 (0)711 17-0

## 1.4 Emergency telephone number

+49 (0)711 17-0 gms.daimler.com

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Remark

This mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

## 2.2 Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### product identifiers

Trade name/designation Getriebeöl, ATF DCT

## Precautionary statements

P102 Keep out of reach of children.

#### Special rules for supplemental label elements for certain mixtures

EUH210 Safety data sheet available on request.

## 2.3 Other hazards

#### Other adverse effects

Special danger of slipping by leaking/spilling product.



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition / information on ingredients**

#### 3.1 Substances

not applicable

## 3.2 Mixtures

## Description

Mixture of highly refined mineral oils and additives. Synthetic oil and additives.

## Hazardous ingredients

CAS No. EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]
verschieden*	low viscosity base oils (<20.5 mm²/s at 40°C)	0 - 90 %	Asp. Tox. 1 H304
1218787-32- 620-540-6 6	2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	0.1 - 0.25 %	Acute Tox. 4 H302 Skin Corr. 1C H314 Aquatic Acute 1 H400 M=10 Aquatic Chronic 1 H410 M=1
REACH No.	Substance name		
01-2119510877-33	2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol		

## Additional information

\* contains one or more of the following CAS numbers (REACH registration numbers): 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (012119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020163-82), 68649-12-7 (01-2119527646-33), 151006-60-9 (01-2119523580-47), 163149-28-8 (01-2119543695-30)

#### Remark

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

Remove contaminated, saturated clothing immediately. Never put product impregnated rags into clothing pockets

## Following inhalation

Provide fresh air.

In the event of symptoms refer for medical treatment.

## Following skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

## After eye contact

Remove contact lens

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### After ingestion

Do NOT induce vomiting. Seek medical advice immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### **Symptoms**

Oil acne/folliculitis

Ingestion may cause nausea, vomiting and/or diarrhoea.

#### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes for the doctor

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

#### Suitable extinguishing media

Foam

Extinguishing powder

Carbon dioxide (CO2)

Sand

Water spray jet

Water mist

## Unsuitable extinguishing media

High power water jet

## 5.2 Special hazards arising from the substance or mixture

## **Hazardous combustion products**

Fire gas of organic material has to be classed invariably as respiratory poison.

## 5.3 Advice for firefighters

## Special protective equipment for firefighters:

Adjust extinguishing measures to the environment.

In case of fire: Wear self-contained breathing apparatus.

## **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Contaminated fire-fighting water must be collected separately; it shall not run into the sewage system, aquatic environment or into the soil.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Avoid skin and eye contact.

Special danger of slipping by leaking/spilling product.

## For emergency responders

Avoid skin and eye contact

Special danger of slipping by leaking/spilling product.

#### 6.2 Environmental precautions

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter into surface water or drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not allow to enter into soil/subsoil.

## 6.3 Methods and material for containment and cleaning up

#### For containment

Take up with absorbent material (e.g. oil binder).

After taking up the material dispose according to regulation.



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling Protective measures

Avoid:

generation/formation of aerosols

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

This material is a potential static accumulator.

Do not heat up to temperatures close to the flash point.

Do not inhale vapours.

All work processes must always be designed so that the following is as low as possible:

Skin contact

Avoid:

Eye contact

Do not put any product-impregnated cleaning rags into your trouser pockets.

## Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff.

Keep away from food and drink.

Wash hands before breaks and after work.

Use protective skin cream before handling the product.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep/Store only in original container.

Keep container tightly closed.

Unsuitable material: PVC

#### Storage class

10 Combustible liquids that cannot be assigned to any of the above storage classes

## Materials to avoid

Do not store together with:

Oxidising agent

#### Further information on storage conditions

Keep container tightly closed and protected against effects of weather in a cool, appropriately aerated area.

Protect against:

UV-radiation/sunlight

Heat

Recommended storage temperature: room temperature.

#### 7.3 Specific end use(s)

#### Recommendation

See section 1.2

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

#### Occupational exposure limit values

CAS No. EC No. Substance name occupational exposure limit value

Ölnebel 5 [mg/m3]

Empfehlung



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### 8.2 Exposure controls

#### Appropriate engineering controls

#### Technical measures to prevent exposure

Sufficient ventilation and exhaustion.

## Personal protection equipment

#### Eye/face protection

Safety glasses recommended during transfer DIN EN 166

#### Hand protection

Glove materials data [type, thickness, breakthrough time/duration of use, permeation rate]: Nitrile rubber (protection index 6, >480 min, 0.4 mm)

Glove materials data [type, thickness, breakthrough time/duration of use, permeation rate]: PVC or fluoro rubber (Viton), > 0.4 mm, > 480min, EN 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN374.

#### **Body protection:**

Protective clothing

## Respiratory protection

aerosol or mist formation

high concentrations

Suitable respiratory protection apparatus:

Filtering device (full mask or mouthpiece) with filter:

AX

#### **Environmental exposure controls**

## Remark

See Section 6 see Section 7

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

## Physical state

liquid

#### Colour

amber

#### Odour

like:

Mineral oil

## Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:	not determined		
рН	in delivery state		not applicable
Melting point/freezing point	not determined		
Initial boiling point and boiling range	> 280 °C		
Flash point	202 °C	EN ISO 2592	Tolerance: ± 10%
Evaporation rate	not determined		
flammability	not determined		
Upper/lower flammability or explosive limits	Upper explosion limit 10 Vol-%		



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

	Value	Method	Source, Remark
Upper/lower flammability or explosive limits	Lower explosion limit 1 Vol-%		
Vapour pressure	< 0.5 Pa (20°C)	estimated	
Vapour density	> 1	estimated	
Density	0.848 (15°C)	DIN 51757	
Solubility(ies)	Water solubility (g/L)		practically insoluble
Partition coefficient: n-octanol/water	> 6		based on information from comparable products
Auto-ignition temperature	> 320 °C		
Decomposition temperature	not determined		
Viscosity	kinematic 31 mm²/s (40°C)	DIN 51562	Tolerance: ± 10%
Viscosity	kinematic 6.8 mm²/s (100°C)	DIN 51562	Tolerance: ± 10%
Explosive properties:			The product is not explosive
Oxidising properties	not determined		
Other information			
Further safety characteristics			
	Value	Method	Source, Remark
Pour point	-51 °C	DIN ISO 3016	Tolerance: +/- 10%

## Other safety information

none

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No hazardous reactions with proper storage and handling.

#### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.3 Possibility of hazardous reactions

Reactions with strong oxidising agents.

## 10.4 Conditions to avoid

Avoid temperatures above flash point. insolation High temperatures

## 10.5 Incompatible materials

Oxidising agent, strong

## 10.6 Hazardous decomposition products

Carbon monoxide Carbon dioxide Pyrolysis products, toxic

## **Additional information**

No risk of production of decomposition products when appropriately handled and stored



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

#### **Animal data**

	Effective dose	Method	Source, Remark
Acute oral toxicity	ATE > 5000 mg/kg Rat		
Acute dermal toxicity	ATE > 5000 mg/kg Rabbit		
Acute inhalation toxicity	not determined		

#### Assessment/classification

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

## Practical experience/human evidence

Frequent and prolonged contact with the skin may cause skin irritation.

## Assessment/classification

Based on available data, the classification criteria are not met.

#### Eye damage/irritation

#### Practical experience/human evidence

Repeated or prolonged contact with the eyes may cause eye irritation.

## Assessment/classification

Based on available data, the classification criteria are not met.

#### Sensitisation to the respiratory tract

## Assessment/classification

Based on available data, the classification criteria are not met.

#### Skin sensitisation

## Assessment/classification

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

## Assessment/classification

Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### Assessment/classification

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

## Assessment/classification

Based on available data, the classification criteria are not met.

## **Overall Assessment on CMR properties**

This product does not meet the criteria for classification in Categories 1A/1B.

#### STOT-single exposure

## STOT SE 1 and 2

## Assessment/classification

Based on available data, the classification criteria are not met.

#### STOT SE 3

## Irritation to respiratory tract

#### Assessment/classification

Based on available data, the classification criteria are not met.



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### **Narcotic effects**

#### Assessment/classification

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

#### Assessment/classification

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

## **Experimental data**

	Value	Method	Source, Remark	
Viscosity	kinematic 31 mm²/s (40°C)	DIN 51562	Tolerance: ± 10%	_
Viscosity	kinematic 6.8 mm²/s (100°C)	DIN 51562	Tolerance: ± 10%	

## Assessment/classification

Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

## **Aquatic toxicity**

	Effective dose	Method	Source, Remark
Acute (short-term) fish toxicity	LL50 > 100 mg/L		
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EL50 > 100 mg/L		
Chronic (long-term) toxicity to crustacea	not determined		
Acute (short-term) toxicity to aquatic algae and cyanobacteria	EL50 > 100 mg/L		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		

## Assessment/classification

Based on available data, the classification criteria are not met.

## 12.2 Persistence and degradability

	Value	Method	Source, Remark
Biodegradation			Not readily biodegradable (according to OECD criteria)

## Assessment/classification

Enthält Bestandteile mit potentieller Bioakkumulation.

## 12.3 Bioaccumulative potential

	Value	Method	Source, Remark
Partition coefficient: n-	> 6		based on information from
octanol/water			comparable products

## 12.4 Mobility in soil

## Assessment/classification

The material is presumed to be relatively immobile in the ground.

## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6 Other adverse effects

#### Additional ecotoxicological information

#### Additional information

Do not allow uncontrolled discharge of product into the environment.

The product floats on top of the water/sewage.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

## Waste codes/waste designations according to EWC/AVV

Waste code product	Waste name
130206 *	synthetic engine, gear and lubricating oils

## Appropriate disposal / Product

Dispose of waste according to applicable legislation.

#### Appropriate disposal / Package

Dispose of waste according to applicable legislation.

#### Remark

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number	-	-	-
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

## 14.6 Special precautions for user

No data available

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

For bulk shipments by sea, the regulations of MARPOL Annex 1 apply.

#### All transport carriers

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations

## Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-Wert: 0 %

#### Water hazard class (WGK)

obviously hazardous to water (WGK 2)

according to the Ordinance on Facilities for Handling Substances that are Hazardous to Water (AwSV)

Kenn-Nummer: 436



## A 001 989 85 03 13 Getriebeöl, ATF DCT

Print date 08.06.2020 Revision date 13.05.2020

Version 1

#### Restrictions of occupation

Observe national legislation regarding professional restrictions.

#### 15.2 Chemical Safety Assessment

Substance safety analysis was not performed for this mixture.

#### **SECTION 16: Other information**

### Indication of changes

Current safety data sheets are available at: http://gms.aftersales.daimler.com

#### Abbreviations and acronyms

See overview table at www.euphrac.eu

#### Key literature references and sources for data

Safety data sheets of suppliers

#### **Additional information**

Adhere to existing national and local rules referring to chemicals.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

## Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects