XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name XT-2002_5GL

Material number 00000000000509035

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Compliance Services - 877-428-9937 Telephone

Emergency telephone numbers

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. **Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear
Odour	mild

GHS Classification

Oxidizing liquids : Category 3 Acute toxicity (Inhalation) : Category 4 Acute toxicity (Dermal) : Category 4 Skin corrosion Category 1 Serious eye damage : Category 1

GHS label elements

Hazard pictograms



Flame over







Signal word : Danger

Hazard statements : H272 May intensify fire; oxidizer.

> H312 + H332 Harmful in contact with skin or if inhaled. H314 Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

P210 Keep away from heat.

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

P220 Keep/Store away from clothing/ combustible materials. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
nitric acid	7697-37-2	>= 10 - < 30
orthophosphoric acid	7664-38-2	>= 5 - < 10
sodium xylenesulphonate	1300-72-7	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

wounds from corrosion of the skin heal slowly and with

difficulty.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. Causes severe skin burns and eye damage. Harmful in contact with skin or if inhaled.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Nitrogen oxides (NOx)

Smoke

Carbon dioxide (CO2) Carbon monoxide Phosphorus compounds

Sulphur oxides

Specific extinguishing : Use extinguishing measures that are appropriate to local

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

methods circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

Storage temperature : 4.4 - 49 °C

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
nitric acid	7697-37-2	TWA	2 ppm	ACGIH
		STEL	4 ppm	ACGIH
		ST	4 ppm 10 mg/m3	NIOSH REL
		TWA	2 ppm 5 mg/m3	NIOSH REL
		TWA	2 ppm 5 mg/m3	OSHA Z-1
		TWA	2 ppm 5 mg/m3	OSHA P0
		STEL	4 ppm 10 mg/m3	OSHA P0
		PEL	2 ppm 5 mg/m3	CAL PEL
		STEL	4 ppm 10 mg/m3	CAL PEL
orthophosphoric acid	7664-38-2	TWA	1 mg/m3	ACGIH
		STEL	3 mg/m3	ACGIH
		TWA	1 mg/m3	NIOSH REL
		ST	3 mg/m3	NIOSH REL
		TWA	1 mg/m3	OSHA Z-1
		TWA	1 mg/m3	OSHA P0
		STEL	3 mg/m3	OSHA P0
		PEL	1 mg/m3	CAL PEL
		STEL	3 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear Odour : mild

Odour Threshold : No data available

pH : < 1

Melting point/freezing point : No data available

Boiling point : 104.44 °C

Flash point :

No data available

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 1.24 g/cm3

Bulk density : No data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available
Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : No data available

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Alkali metals

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. Causes severe skin burns and eye damage. Harmful in contact with skin or if inhaled.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : 12.03 mg/l

Exposure time: 4 h

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 1,203 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (PHOSPHORIC ACID, NITRIC ACID), 8, II

Transportation Regulation: IMDG (Vessel):

UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (PHOSPHORIC ACID, NITRIC ACID), 8, II

Transportation Regulation: IATA (Cargo Air):

UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (PHOSPHORIC ACID, NITRIC ACID), 8, II

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Transportation Regulation: IATA (Passenger Air):

UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (PHOSPHORIC ACID, NITRIC ACID), 8, II

Transportation Regulation: TDG (Canada):

UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (PHOSPHORIC ACID, NITRIC ACID),

8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
nitric acid	7697-37-2	1000	4008

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
nitric acid	7697-37-2	1000	4008

SARA 311/312 Hazards : Oxidiser (liquid, solid or gas)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : The following components are subject to reporting levels

established by SARA Title III, Section 302:

nitric acid 7697-37-2 24.9468 %

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

nitric acid 7697-37-2 24.9468 %

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

XT-2002 5GL

Print Date 04/27/2025 Version 3.1 Revision Date 10/01/2023

reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	3
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	ОХ

^{0 =} not significant, 1 = Slight,

HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,

^{2 =} Moderate, 3 = High

^{4 =} Extreme

^{2 =} Moderate, 3 = High 4 = Extreme, * = Chronic

XT-2002 5GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

OSHA - GHS Label Information:

Hazard pictograms







Corrosion

Signal word

Hazard statements May intensify fire; oxidizer. Harmful in contact with skin or if inhaled. Causes severe

skin burns and eye damage.

Precautionary statements

Prevention: Keep away from heat. Keep/Store away from clothing/ combustible materials. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/

protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.