



To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrant or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States)
The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team
Zep Inc.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

1. Identification

Product name: Subaru High Torque CVTF-LV (FCL-525ST)
 Recommended use and restrictions on use: General industrial application
 Manufacturer/Supplier: JXTG Nippon Oil & Energy USA Inc.
 Address: 20 N. Martingale Rd. Suite 325, Schaumburg, IL 60173
 Emergency telephone number: +1-847-413-2188

2. Hazards identification

Classification of the chemical in accordance with OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Hazard category	Category
Flammable liquids	No Classification
Acute toxicity (oral)	No Classification
Acute toxicity (dermal)	No Classification
Skin sensitizer	Category 1
Aspiration hazard	No Classification

Label elements

Pictograms:



Signal word: Warning
 Hazard statement: May cause allergic skin reaction
 Precautionary statements:

Prevention Do not handle until all safety precautions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not allow the eyes to become exposed to the product. Do not swallow the product.
 Contaminated work clothing should not be allowed out of the workplace.
 Avoid breathing dust/fume/gas/mist/vapours/spray.
 Wash hands thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

IF ON SKIN: Wash with plenty of soap and water.
 Take off contaminated clothing and wash before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.

Storage The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
 If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.

3. Composition/information on ingredients

Substance/Mixture: Mixture

Ingredients and Concentration

Chemical Name	Concentration wt. %	CAS#
Base Oil(s)	70-80	74869-22-0
Additives	<30	-

4. First-aid measures

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Cover the body with blankets to keep warm and quiet. If you feel unwell, seek medical advice.

Skin contact: Immediately flush skin with large amounts of water.
 Wash contaminated clothing before reuse.
 If skin irritation occurs: Get medical advice/attention.

Eye contact: Rinse with clean water carefully for several minutes. Remove contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical attention.

Ingestion: Do not induce vomiting. Drink [one glass] [two glasses] of water.
 Call a physician [or poison control center] immediately.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Most important symptoms/effects,
acute and delayed.

May cause allergic skin reaction. Dermatis. Rash.

5. Fire-fighting measures

Suitable extinguishing media:	Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, and dry sand are effective.
Unsuitable extinguishing media:	Use of straight stream of water can cause a risk of spreading fire.
Specific hazards arising from the chemical:	In some cases of fire, may release irritant gases. When burnt, may generate carbon monoxide and other toxic gases.
Specific extinguishing methods:	Spray water to the surrounding facilities for cooling. Keep unauthorized persons off the site of occurrence of fire and the surroundings. Even after extinction, cool containers thoroughly with plenty of water.
Special protective equipment and precautions for fire fighters:	Wear fire/flare resistant/retardant clothing. Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious protective equipment and gloves. Use air-breathing apparatus and protective clothing whenever necessary.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Wear protective equipment when working. Remove nearby potential ignition sources immediately. When mist is generated, use respiratory equipment to prevent inhalation of mist. Do not touch or walk through spillage. Pay attention to the site of spillage, which is slippery.
Environmental precautions:	Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to flow to street drains, sewer systems, and rivers. At sea, install oil spill containment booms to prevent spreading of spills and absorb with absorption mat or other proper materials.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Methods and materials for containment and cleaning up:	<p>In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper materials.</p> <p>In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty containers to the extent possible.</p>
Prevention of second accident:	<p>In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and spreading of spillage.</p> <p>Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and ventilate and clean the site and the surroundings.</p>

7. Handling and storage

Handling

Technical measures:	<p>Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor without justification.</p> <p>Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not drink.</p> <p>When mist is generated, use respiratory equipment to prevent inhalation of mist.</p> <p>In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.</p> <p>Avoid rough handling of containers such as falling, dropping, exposing to shock, and dragging.</p>
Ventilation requirements:	Maintain adequate ventilation when handling indoors.
Precautions:	<p>Wash hands and face thoroughly after handling.</p> <p>Be careful with fire.</p>
Precautions for safe handling:	<p>Avoid falling, dropping, exposing to shock, or dragging of containers.</p> <p>Wear protective gloves when opening containers to eliminate a risk of hand injury.</p>

Storage

Storage conditions:	<p>Store in a well ventilated, cool, dry, dark place, protecting from direct sunlight and keeping away from any potential ignition sources and high-temperature materials.</p> <p>Store tightly stopped after use to prevent possible contamination with dust and moisture.</p> <p>Preferably store locked up in a proper storage area.</p>
Safety adequate container materials:	Use spill-proof containers that are free of damage/corrosion.

SAFETY DATA SHEET

MSDS: A4190_E710USUS
 Date Prepared: 12/3/2018
 Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

8. Exposure controls/personal protection

Appropriate engineering controls: In case of mist generation, enclose the source of mist generation, or install a ventilation system.
 Install eye cleaning and body cleaning equipment near the handling site.

Control parameters

Chemical Name	U.S. - OSHA			ACGIH	
	Ceiling	STEL	TWA	TLV-STEL	TLV-TWA
Base Oil(s)	-ppm -mg/m ³	-ppm -mg/m ³	-ppm -mg/m ³	-ppm -mg/m ³	-ppm -mg/m ³

Personal protective equipment

Respiratory protection: Not needed under normal conditions, but wear a gas mask (against organic gases) whenever required.
 Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand protection.
 Eye/face protection: In case of exposure to splashes, wear ordinary type goggles.
 Skin protection: In case of handling over a prolonged period of time or in case of exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.
 Wash hands thoroughly after handling.

9. Physical and chemical properties

Product

Appearance: Liquid
 pH: No data.
 Melting point/freezing point: Pour Point $\leq -45(^{\circ}\text{C})$
 Flash point: $194(^{\circ}\text{C})$ Cleveland Open Cup
 Evaporation rate: No data.
 Flammability (solid, gas): Not applicable
 Auto-ignition temperature: Estimate $200-410(^{\circ}\text{C})$
 Vapor pressure: No data.
 Vapour density: No data.
 Density(g/cm³): $0.839(15^{\circ}\text{C})$
 Solubility: water : Insoluble.

SAFETY DATA SHEET

MSDS: A4190_E710USUS
 Date Prepared: 12/3/2018
 Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Partition coefficient: n- octanol/water: No data.

Decomposition temperature: No data.

Kinematic viscosity: >20.5 (mm²/sec) (40°C)

10. Stability and reactivity

Chemical stability: Stable when stored or preserved in a dark place at room temperature.

Possibility of hazardous reactions: Keep away from any possible contact with strong oxidizing agents.

Conditions to avoid: Contact with incompatible hazard substances
 Prolonged heating, open flames, and ignition sources

Incompatible materials: Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances.

Hazardous decomposition products: When burnt, may release carbon monoxide and other gases.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics: May cause allergic skin reaction. Dermatitis. Rash.

Delayed and immediate effects and also chronic effects from short- and long- term exposure:

Short term exposure:
 Potential immediate effects : No information
 Potential delayed effects : No information

Long term exposure:
 Potential immediate effects : No information
 Potential delayed effects : No information

Product

Acute toxicity (oral): For mixtures, hazard category was identified based on the classification criteria for mixtures.

Acute toxicity (dermal): For mixtures, hazard category was identified based on the classification criteria for mixtures.

Acute toxicity (inhalation): For mixtures, hazard category was identified based on the classification criteria for mixtures.

Skin corrosion/irritation: For mixtures, hazard category was identified based on the classification criteria for mixtures.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Serious eye damage/irritation:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Respiratory sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Skin sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Mutagenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Carcinogenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Reproductive toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Target organ effect/Single exposure:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Target organ effect/Multi exposure:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Respiratory toxic:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Other information:	

Ingredient

Base Oil(s)

Acute toxicity (oral):	LD50: > 5000 mg/kg[rat]
Acute toxicity (dermal):	LD50: > 2000 mg/kg[rabbit]
Acute toxicity (inhalation):	LC50: 2.18 mg/L[rat]
Serious eye damage/irritation:	Practically None
Skin sensitization:	None Buehler method [guinea pig]
Mutagenicity:	Ames Test:Negative
Carcinogenicity:	EU:Category 1 : R45 need not apply. (NOTE L is Applicable), IARC:3

12. Ecological information

Product

Ecotoxicity

Fish acute toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
----------------------	---

SAFETY DATA SHEET

MSDS: A4190_E710USUS
Date Prepared: 12/3/2018
Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Algae acute toxicity: For mixtures, hazard category was identified based on the classification criteria for mixtures.

Fish chronic toxicity: For mixtures, hazard category was identified based on the classification criteria for mixtures.

Algae chronic toxicity: For mixtures, hazard category was identified based on the classification criteria for mixtures.

Other impact :

Ingredient

Base Oil(s)

Ecotoxicity

Fish acute toxicity: 96hLC50: > 5000 mg/L[Oncorhynchus mykiss]

Daphnia acute toxicity: 48hEC50: > 1000 mg/L[Daphnia magna]

13. Disposal considerations

Disposal methods: Dispose of contents/container in accordance with local/regional/national/international regulations.
Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.
Before disposal of used container, remove contents completely.

14. Transport information

IATA UN number: Not regulated
 Proper Not regulated
 shipping name:

Packing group: Not regulated

IMDG UN number: Not regulated
 Proper Not regulated
 shipping name:

Packing group: Not regulated

Specific security precaution and condition of transportation: Transport containers without causing any significant friction or shaking.

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

15. Regulatory information

US California Proposition 65

None of the ingredients is listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA Title III)

None present or none present in regulated concentrations.

Australia(AICS) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
Canada(DSL) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
China(IECSC) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
EU(REACH) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
Korea(KECL) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
New Zealand(NZIoC) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
Philippines(PICCS) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
Taiwan(TCSI) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
USA(TSCA) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.

16. Other information

NFPA	Health hazard rating blue:0, Flammability hazard rating:1
HMIS	Health Ratings:0, Flammability Ratings:1
Date Prepared:	4/26/2018

SAFETY DATA SHEET

MSDS: A4190_E710USUS

Date Prepared: 12/3/2018

Date Revised: 2019/10/01

Product Name: Subaru High Torque CVTF-LV (FCL-525ST)

Disclaimer:

We at JXTG Nippon Oil & Energy Corporation have prepared the copyrighted Safety Data Sheet to provide reference information on the hazardous chemical product of interest for our customers/users to ensure secure and safe handling.

We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical application of the product of interest.

Consequently, the Safety Data Sheet is not intended to guarantee the safety of the product referenced to herein.