# **ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH**

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH

Material number : 00000000001039615

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

For SDS Information: Compliance Services - 877-428-9937For a Medical Emergency: 877-541-2016 Toll Free - All Calls RecordedFor a Transportation: CHEMTREC: 800-424-9300 - All Calls Recorded.EmergencyIn the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

| Appearance | Aerosol containing a liquefied gas |  |
|------------|------------------------------------|--|
| Colour     | opaque, white                      |  |
| Odour      | characteristic                     |  |

## **GHS Classification**

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas

**GHS** label elements

Hazard pictograms :



Gas cylinder

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use. Storage:

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

| Chemical name                                 | CAS-No.    | Concentration [%] |
|---|------------|-------------------|
| Distillates (petroleum), hydrotreated light   | 64742-47-8 | >= 5 - < 10       |
| Solvent naphtha (petroleum), medium aliph.    | 64742-88-7 | >= 5 - < 10       |
| propane                                       | 74-98-6    | >= 1 - < 5        |
| butane  | 106-97-8   | >= 1 - < 5        |
| Amides, tall-oil fatty, N,N-bis(hydroxyethyl) | 68155-20-4 | >= 1 - < 5        |
| sodium nitrite                                | 7632-00-0  | >= 0.1 - < 1      |

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

If skin irritation persists, call a physician.

If on clothes, remove clothes.

Wash off immediately with plenty of water for at least 15

minutes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

# **ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH**

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

delayed Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Silicon oxides

Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

acid binder, universal binder, sawdust).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Avoid exposure - obtain special instructions before use.

Do not breathe vapours or spray mist.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

| Components                                  | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---|------------|-------------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA                                 | 500 ppm<br>2,000 mg/m3                         | OSHA Z-1  |
|   |            | TWA                                 | 400 ppm<br>1,600 mg/m3                         | OSHA P0   |
|   |            | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1  |
|   |            | TWA (Mist)                          | 5 mg/m3  | OSHA P0   |
|   |            | TWA (Mist)                          | 5 mg/m3  | NIOSH REL |
|   |            | ST (Mist)                           | 10 mg/m3                                       | NIOSH REL |
|   |            | PEL (particulate)                   | 5 mg/m3  | CAL PEL   |
| propane                                     | 74-98-6    | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | NIOSH REL |
|   |            | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | OSHA Z-1  |
|   |            | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | OSHA P0   |
|   |            | PEL                                 | 1,000 ppm                                      | CAL PEL   |

# **ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH**

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

|        |          |      | 1,800 mg/m3 |           |
|--------|----------|------|-------------|-----------|
| butane | 106-97-8 | TWA  | 800 ppm     | NIOSH REL |
|        |          |      | 1,900 mg/m3 |           |
|        |          | TWA  | 800 ppm     | OSHA P0   |
|        |          |      | 1,900 mg/m3 |           |
|        |          | PEL  | 800 ppm     | CAL PEL   |
|        |          |      | 1,900 mg/m3 |           |
|        |          | STEL | 1,000 ppm   | ACGIH     |

# Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : opaque, white
Odour : characteristic
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available
Boiling point : Not applicable

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

: Extremely flammable aerosol.

liquid)

Upper explosion limit : No data available

# ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

Lower explosion limit : No data available Vapour pressure : No data available

Density : 0.95 g/cm3

Solubility(ies)

Water solubility dispersible Solubility in other solvents : not determined

: not determined Auto-ignition temperature

Thermal decomposition : No data available

Viscosity

: > 1000 mm2/s (40 °C) Viscosity, kinematic

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

Sodium oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

Aggravated Medical Condition

: None known.

Symptoms of Overexposure

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

## Carcinogenicity:

# ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

#### **Components:**

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Amides, tall-oil fatty, N,N-bis(hydroxyethyl):

Acute oral toxicity : LD50 Oral Rabbit: 2,200 mg/kg

LD50 Oral Mouse: 3,300 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 12,200 mg/kg

## Skin corrosion/irritation

#### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

## **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

#### Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

# **ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH**

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

Components:

butane:

Partition coefficient: n-

• •

: Pow: 2.89

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

# **ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH**

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to TSCA 12(b) export notification

requirements.

No substances are subject to a Significant New Use Rule.

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

sodium nitrite 7632-00-0

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

| Components     | CAS-No.   | Component RQ (lbs) | Calculated product RQ (lbs) |
|----------------|-----------|--------------------|-----------------------------|
| sodium nitrite | 7632-00-0 | 100                | *                           |

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, which is/are known to the State of California to cause cancer, and methanol, which is/are known to the State of California to cause birth defects or other

reproductive harm. For more information go to

www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

# **SECTION 16. OTHER INFORMATION**

Print Date 04/25/2025 Version 6.1 Revision Date 10/01/2023

## **Further information**

#### NFPA:

| HEALTH          | 1 |
|-----------------|---|
| FLAMMABILITY    | 4 |
| INSTABILITY     | 0 |
| SPECIAL HAZARD. |   |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

| HEALTH          | 1 |
|-----------------|---|
| FLAMMABILITY    | 4 |
| PHYSICAL HAZARD | 3 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms





Danger:

Gas cylinder

Signal word Hazard statements Precautionary statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

**Disposal:** Dispose of contents/container in accordance with local regulation.

| Version:       | 6.1        |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date:    | 04/25/2025 |

# SAFETY DATA SHEET ORIGINAL BIKE SPIRITS SPRAY CLEANER & POLISH

Version 6.1 Revision Date 10/01/2023 Print Date 04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.