

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014

Reviewed on 03/06/2014

ldentification

- · Product identifier
- · Trade name: Noxudol 300 S
- · Product number: 37300
- · **Product description** Anti Rust Compound, Vehicle Underbody Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Manufacturer: Auson AB Verkstadsgatan 3

S-434 42 Kungsbacka Sweden

www.auson.se

Phone: +46 300-562000 Fax: +46 300-562001

US Distributor: Soken Trade Corporation

12055 Sherman Way North Hollywood, CA USA www.noxudolusa.com Phone: (818) 308-8430 Fax: (818) 308-8428

· Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incident. Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 CCN701762 or +1 703-527-3887 (collect calls accepted)

Hazard(s) identification

· Classification of the substance or mixture



Health hazard

Suspected of causing cancer.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS08

- · Signal word Warning
- Hazard-determining components of labeling:

Carbon black

· Hazard statements

Suspected of causing cancer.

· Precautionary statements

Use personal protective equipment as required.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention.

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0 Fire = 1 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic Carc. 1B, H350	25-50%
8002-74-2	Paraffin waxes and Hydrocarbon waxes	15-35%
1333-86-4	Carbon black	≤ 2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Give large amounts of water. If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 3)

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 2)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep protective respiratory device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

 Components with 	limit values t	that require	monitoring a	it the workplace:
-------------------------------------	----------------	--------------	--------------	-------------------

8002-74-2 Paraffin waxes and Hydrocarbon waxes

REL Long-term value: 2 mg/m³
TLV Long-term value: 2 mg/m³

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³

*0.1 in presence of PAHs;See Pocket Guide Apps.A+C

TLV | Long-term value: 3* mg/m³

*inhalable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- · Breathing equipment: Not required.
- · Protection of hands:



OSHA Haz Com Standard 29 CFR 1910,1200, Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Highly viscous

Color: Black

· Odor: Mineral-oil-like · Odor threshold: Not determined.

· **pH-value:** Not determined.

Change in condition

Melting point/Melting range:
Boiling point/Boiling range:Not determined.
316 °C (601 °F)Flash point:140 °C (284 °F)Flammability (solid, gaseous):Not applicable.Ignition temperature:300 °C (572 °F)Decomposition temperature:Not determined.

· **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Not determined.

Vapor pressure: Not determined.

• **Density @ 20 °C (68 °F):** 0.96 g/cm³ (8.011 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic @ 20 °C (68 °F): 500650 mPas

(Contd. on page 5)

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 4)

Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 %

VOC content: 10.7 g/l / 0.09 lb/gl

Solids content: 98.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values	s that are relevant f	for classification:
------------------	-----------------------	---------------------

1333-86-4 Carbon black

Oral LD50 10000 mg/kg (rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic.

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1333-86-4	Carbon black	2B
14808-60-7	Quartz (SiO2)	1
· NTP (Natio	onal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 6)

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 5)

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

Packing group

DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

1333-86-4 Carbon black

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 7)

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

(Contd. of page 6)

· Chemicals known to cause reproductive to	oxicity for males:
None of the ingredients is listed.	
· Chemicals known to cause developmenta	l toxicity:
None of the ingredients is listed.	

· Carcinogenic categories

· EPA (Environmental Protection Agency) None of the ingredients is listed. · TLV (Threshold Limit Value established by ACGIH)

NIOSH Co.	(National Institute for Occupational Cafety and Houlth)	
14808-60-7	Quartz (SiO2)	A2
1333-86-4	Carbon black	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health) 1333-86-4 | Carbon black 14808-60-7 | Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration)

Corrosive to eyes

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling:

Carbon black

· Hazard statements

Suspected of causing cancer.

· Precautionary statements

Use personal protective equipment as required.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know		
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic Carc. 1B, H350	25-50%
8002-74-2	Paraffin waxes and Hydrocarbon waxes	15-35%

(Contd. on page 8)

OSHA Haz Com Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 03/06/2014 Reviewed on 03/06/2014

Trade name: Noxudol 300 S

		(Contd. of page 7
	Carbon black	≤ 2.5%
	& Carc. 2, H351; (1) Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
14808-60-7	Quartz (SiO2)	≤ 2.5%
	♦ Carc. 1A, H350; STOT RE 1, H372; ♦ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	
All ingredien	its are listed.	

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16 Other info</u>rmation

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 03/06/2014 / 5

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 1B: Carcinogenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* * Data compared to the previous version altered.

SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)