

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.

SAFETY DATA SHEET

1. Identification

Product identifier B55101 BVT PINA COLADA-DEODORIZER

Other means of identification

Product code 1000016680
Recommended use air freshener
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ACUITY HOLDINGS INC. dba AMREP

Address 11627 178 STREET NW

EDMONTON, AB T5S 1N6

Canada

Telephone General Assistance 1-905 669-9876

E-mail Not available.

Emergency phone number Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSensitization, skinCategory 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May cause an allergic skin reaction.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	70.384
Propane		74-98-6	12.616

Chemical name	Common name and synonyms	CAS number	%
Isopropyl Alcohol		67-63-0	1.999
Allyl Hexanoate		123-68-2	0.55
Lauryl methacrylate		142-90-5	0.175
Hexyl cinnamal		101-86-0	0.138
Other components below reports	able levels		14.13908

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact In case of eczema or other skin disorders: Seek medical attention and take along these

instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. May cause an allergic skin reaction. Dermatitis. Rash. Most important

symptoms/effects, acute and delaved

Indication of immediate

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2). Suitable extinguishing media

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods

containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Valu	ıes
Components	

Components	Туре	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
,	TWA	200 ppm
Canada. Alberta OELs (Occupatio	nal Health & Safety Code, Sch	nedule 1, Table 2)
Components	Туре	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	984 mg/m3
		400 ppm
	TWA	492 mg/m3
		200 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame		s for Chemical Substances, Occupational Health and
Components	Туре	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Canada. Manitoba OELs (Reg. 217	7/2006, The Workplace Safety	And Health Act)
Components	Type	Value
Components	. , po	3.3.3
Isobutane (CAS 75-28-5)	STEL	1000 ppm
	STEL STEL	
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS	STEL	1000 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0)	STEL STEL TWA	1000 ppm 400 ppm 200 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o	STEL STEL TWA	1000 ppm 400 ppm 200 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o	STEL STEL TWA f Exposure to Biological or Ch	1000 ppm 400 ppm 200 ppm nemical Agents)
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS	STEL STEL TWA If Exposure to Biological or Ch Type TWA STEL	1000 ppm 400 ppm 200 ppm nemical Agents) Value
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS	STEL STEL TWA f Exposure to Biological or Ch Type TWA	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry of	STEL STEL TWA If Exposure to Biological or Ch Type TWA STEL TWA	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm 400 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0)	STEL STEL TWA If Exposure to Biological or Ch Type TWA STEL TWA	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm 400 ppm 200 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry of	STEL STEL TWA If Exposure to Biological or Ch Type TWA STEL TWA STEL TWA of Labor - Regulation Respect	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm 400 ppm 200 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry of Components Isopropyl Alcohol (CAS	STEL STEL TWA of Exposure to Biological or Ch Type TWA STEL TWA of Labor - Regulation Respect Type STEL	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm 400 ppm 200 ppm 200 ppm ing the Quality of the Work Environment) Value 1230 mg/m3 500 ppm
Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control o Components Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Quebec OELs. (Ministry of Components Isopropyl Alcohol (CAS	STEL STEL TWA If Exposure to Biological or Ch Type TWA STEL TWA STEL TWA of Labor - Regulation Respect Type	1000 ppm 400 ppm 200 ppm nemical Agents) Value 800 ppm 400 ppm 200 ppm 200 ppm ing the Quality of the Work Environment) Value 1230 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) Components Value Type

Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas. Aerosol. Form Not available. Color Not available. Odor Not available. **Odor threshold** Not available. рH Not available. Melting point/freezing point

Initial boiling point and boiling

95.59 °F (35.33 °C) estimated

range

Flash point -99.4 °F (-73.0 °C) Propellant estimated

Evaporation rate Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

4 % estimated

(%)

Flammability limit - upper

12 % estimated

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

80.21 psig @70F estimated Vapor pressure

Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 835.13 °F (446.18 °C) estimated

Decomposition temperature Not available. Not available. **Viscosity**

Other information

Explosive properties Not explosive.

Heat of combustion (NFPA

30B)

39.38 kJ/g estimated

Oxidizing properties Not oxidizing. Percent volatile 97 % estimated Specific gravity 0.602 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. Incompatible materials No hazardous decomposition products are known. Hazardous decomposition

products

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation

Skin contact May cause an allergic skin reaction.

Direct contact with eyes may cause temporary irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components **Species Test Results**

Allyl Hexanoate (CAS 123-68-2)

Acute Dermal

LD50 Rabbit

820 mg/kg

Oral

LD50 Guinea pig 280 mg/kg

> Rat 218 mg/kg

Isobutane (CAS 75-28-5)

Acute

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

Components Species Test Results

Isopropyl Alcohol (CAS 67-63-0)

Acute Dermal

LD50 Rabbit 16.4 ml/kg, 24 Hours

Inhalation

LC50 Rat > 10000 ppm, 6 Hours

Oral

LD50 Rat 5.84 g/kg

Lauryl methacrylate (CAS 142-90-5)

Acute Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Propane (CAS 74-98-6)

Acute Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

658 mg/l/4h

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Isopropyl Alcohol (CAS 67-63-0)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

2-PROPANOL (CAS 67-63-0) Not classifiable as a human carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Isopropyl Alcohol (CAS 67-63-0)			
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours

^{*} Estimates for product may be based on additional component data not shown.

 Components
 Species
 Test Results

 Fish
 LC50
 Bluegill (Lepomis macrochirus)
 > 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Isobutane2.76Isopropyl Alcohol0.05Propane2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

product residues. This material and its container must be disposed of in a safe mariner (see

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Class 2.1
Subsidiary risk Label(s) None

Packing group Not applicable.

Not applicable.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable. Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Product name: B55101 BVT PINA COLADA-DEODORIZER

Country(s) or region Inventory name On inventory (yes/no)*

Korea Existing Chemicals List (ECL) New Zealand Inventory New Zealand No

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

05-22-2017 Issue date

Version # 01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.