

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Material number : 000000000001003236

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	gel
Colour	metallic, silver
Odour	oily

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 30
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 10 - < 30
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 10 - < 30
graphite	7782-42-5	>= 5 - < 10
aluminium	7429-90-5	>= 1 - < 5
Distillates (petroleum), hydrotreated light	64742-47-8	>= 1 - < 5
quartz (SiO ₂)	14808-60-7	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash off with soap and water. If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during	: Do not allow run-off from fire fighting to enter drains or water

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

firefighting	courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
graphite	7782-42-5	TWA (Respirable)	2 mg/m3	CA BC OEL
		TWAEV (Respirable fibres)	5 mg/m3	CA QC OEL
		TWAEV (Total fibres)	10 mg/m3	CA QC OEL
		TWAEV (respirable dust)	2 mg/m3	CA QC OEL
aluminium	7429-90-5	TWA (Dust)	10 mg/m3	CA AB OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
quartz (SiO2)	14808-60-7	TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWA (Respirable fraction)	0.1 mg/m3	CA ON OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

Eye protection	: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water. Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: gel
Colour	: metallic, silver
Odour	: oily
Odour Threshold	: not determined
pH	: Not applicable
Melting point/freezing point	: Not applicable
Boiling point	: No data available
Flash point	: > 204.4 °C Method: Cleveland open cup
Evaporation rate	: Not applicable
Upper explosion limit	: not determined
Lower explosion limit	: not determined
Vapour pressure	: < 0.01 hPa
Density	: 0.8 g/cm3
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: not determined
Viscosity	
Viscosity, kinematic	: > 10000 mm2/s (40 °C)

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides Organic Substances

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or skin irritation.
Overexposure may cause mild eye or skin irritation.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Group 1: Carcinogenic to humans

quartz (SiO₂)

14808-60-7

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

aluminium:

Acute oral toxicity : LD50 Rat: > 15,900 mg/kg

Acute inhalation toxicity : LC50 Rat: > 0.888 mg/l
Exposure time: 4 h

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen., Not classified due to product form (grease or paste) and classification route of entry (inhaled powder).

Reproductive toxicity

No data available

STOT - single exposure

No data available

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:
Naphtha (petroleum), hydrodesulfurized heavy

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA Not On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 45LB

Version 2.0

Revision Date 07/02/2024

Print Date 04/27/2025

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Not a hazardous substance or mixture.

Version:	2.0
Revision Date:	07/02/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.