

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

1. Identification

Product name: TOYOTA E-TRANSAXLE FLUID TE

Manufacturer/Supplier: ENEOS USA, Inc.

Address: 20 N. Martingale RD., Suite 325, Schaumburg, IL. 60173

Charge section: Lubricants Sales Dept.

TEL (Information):+1-847-413-2188)

Emergency Telephone 3E: 1-800-451-8346 Number (US and ID Number: 17406

Canada): Contact Available Time: 24/7/365

Recommended use and General industrial application

Recommended use and restrictions on use:

2. Hazards identification

Classification of the chemical in accordance with OSHA Hazard Communication Standard (29 CFR \S 1910.1200)

Hazard category Category

Flammable liquids

Acute toxicity (oral)

Acute toxicity (dermal)

Acute toxicity (dust, mist)

No Classification

No Classification

Aspiration hazard Category 1
Acute hazards to the aquatic environment Category 3

Chronic hazards to the aquatic environment Category $\boldsymbol{3}$

Label elements

Pictograms:



Signal word: Danger

Hazard statement: May be fatal if swallowed and enters airways

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

Precautionary statements:

Prevention Do not handle until all safety precautions have been read and

understood.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face

protection.



SDS: 49844-E81US Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Do not allow the eyes to become exposed to the product. Do not swallow the product.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If the eyes are exposed to the product: Rinse the eyes with plenty

of running water and immediately contact a physician.

IF ON SKIN: Wash with plenty of soap and water.

Storage The product must be stored in a cool, well-ventilated location

where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Store locked up.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulations.

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with

usage.

Emergency overview: PBT or vPvB: Not applicable

3. Composition/information on ingredients

3.1 Substances Not Applicable

3.2 Mixtures

Ingredients and Concentration

Chemical Name	Concentr ation wt.%	CAS#
Base 0il(s)	80-90	Trade Secret
Additives	<20	
Reaction product of alkylthioalcohol and substituted phosphorus compound	0. 1-0. 9	Trade Secret

4. First-aid measures

Inhalation: Cover the body with blankets to keep warm and quiet. If you feel

unwell, seek medical advice.

If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Skin contact: Wash contaminated clothing before reuse.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

If skin irritation occurs: Get medical advice/attention.

Immediately flush skin with large amounts of water.

Eye contact: Rinse with clean water carefully for several minutes. Remove

> contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical

attention.

Ingestion: Do NOT induce vomiting.

Do not induce vomiting. Drink [one glass] [two glasses] of water.

Call a physician [or poison control

center] immediately.

Most important symptoms/effects,

acute and delayed.

May cause allergic skin reaction. Dermatis. Rash.

Protection for first aid person: No information.

5. Fire-fighting measures

Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, Suitable extinguishing media:

and dry sand are effective.

Unsuitable extinguishing media: Use of straight stream of water can cause a risk of spreading

fire.

Specific hazards arising from the

chemical:

In some cases of fire, may release irritant gases.

When burnt, may generate carbon monoxide and other toxic gases.

Specific extinguishing methods: Spray water to the surrounding facilities for cooling.

Keep unauthorized persons off the site of occurrence of fire and

the surroundings.

Even after extinction, cool containers thoroughly with plenty of

Special protective equipment and precautions for fire fighters:

Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious

protective equipment and gloves.

Use air-breathing apparatus and protective clothing whenever

Wear fire/flame resistant/retardant clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency

Wear protective equipment when working.

procedures:

Remove nearby potential ignition sources immediately.

When mist is generated, use respiratory equipment to prevent

inhalation of mist.



SDS: 49844-E81US Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Do not touch or walk through spillage.

Pay attention to the site of spillage, which is slippery.

Environmental precautions: At sea, install oil spill containment booms to prevent spreading

of spills and absorb with absorption mat or other proper

materials.

Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to

flow to street drains, sewer systems, and rivers.

Avoid release to the environment.

Methods and materials for containment and cleaning up:

In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper

materials.

In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty

containers to the extent possible.

Prevention of second accident:

In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and

spreading of spillage.

Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely,

and ventilate and clean the site and the surroundings.

7. Handling and storage

Handling

Technical measures:

Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor

without justification.

Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not

When mist is generated, use respiratory equipment to prevent inhalation of mist.

In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.

Avoid rough handling of containers such as falling, dropping,

exposing to shock, and dragging.

Ventilation requirements:

Maintain adequate ventilation when handling indoors.

Precautions for safe

handling:

Avoid falling, dropping, exposing to shock, or dragging of containers.

Wash hands and face thoroughly after handling.

Be careful with fire.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Wear protective gloves when opening containers to eliminate a risk

of hand injury.

Contact avoidance: Use care to keep away from any possible contact with halogens,

strong acids, alkalis, and acidifying substances.

Contact with and storage in the same location of halogens, strong

acids, alkali and oxidized substances must be avoided.

After handling Wash hands thoroughly. Hygiene measures:

Storage

Storage conditions: Store in a well-ventilated, cool, dry, dark place, protecting from

direct sunlight and keeping away from any potential ignition

sources and high-temperature materials.

Store tightly stopped after use to prevent possible contamination

with dust and moisture.

Preferably, store locked up in a proper storage area.

Store locked up.

Use spill-proof containers that are free of damage/corrosion.

Safety adequate container materials:

8. Exposure controls/personal protection

In case of mist generation, enclose the source of mist generation, Appropriate engineering controls:

or install a ventilation system.

Install eye cleaning and body cleaning equipment near the handling

site.

Control parameters

Chemical Name	U.S OSHA			ACGIH	
Citemited Name		STEL	TWA	TLV-STEL	TLV-TWA
Base 0i1(s)	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3		-ppm 5mg/m3(Mi neral Oil Mist)
Reaction product of alkylthioalcohol and substituted phosphorus compound	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3

Personal protective equipment

Respiratory Not needed under normal conditions, but wear a gas mask (against

organic gases) whenever required. protection:

Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand

protection.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

> Eye/face protection: In case of exposure to splashes, wear ordinary type goggles.

Skin protection: In case of handling over a prolonged period or in case of exposure

to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.

Wash hands thoroughly after handling.

9. Physical and chemical properties

Product

Appearance: Liquid Form: Liquid Color: Light yellow Odor: Slight odor

Melting point/freezing Pour Point-50.0($^{\circ}$ C)

point:

Initial boiling point

and boiling range:

No data

Flammability (solid,

gas):

No data

Upper/lower No data

flammability or explosive limits:

Flash point: ≥150(°C)Cleveland Open Cup

Estimate 200-410 (°C) Auto-ignition

temperature:

No data. Decomposition

temperature:

pH: No data

 \leq 20.5 (mm2/sec) (40°C) Kinematic viscosity: Solubility: water: Insoluble.

No data. Partition coefficient:

n-octanol/water:

Vapour pressure: No data Density(g/cm3): 0.842 (15°C) Vapour density: No data. No data Particle

characteristics:

Relative density: No data. No data. Viscosity:



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

10. Stability and reactivity

Reactivity: Stable when stored or preserved in a dark place at room temperature.

Chemical stability: Stable when stored or preserved in a dark place at room temperature.

Possibility of hazardous Keep away

reactions:

Keep away from any possible contact with strong oxidizing agents.

Conditions to avoid: Contact with incompatible hazard substances

Prolonged heating, open flames, and ignition sources

Incompatible materials: Use care to keep away from any possible contact with halogens, strong acids,

alkalis, and acidifying substances.

Hazardous decomposition

products:

When burnt, may release carbon monoxide and other gases.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics:

May cause allergic skin reaction. Dermatitis. Rash.

Delayed and immediate effects and also chronic effects from short— and long— term

exposure:

Short term exposure:

Potential immediate effects: No information Potential delayed effects: No information

<u>Long term exposure:</u>

Potential immediate effects: No information Potential delayed effects: No information

Product

Acute toxicity (oral): No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (dermal): No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (inhalation): Classification not possible (Gas)

Classification not possible (Vapour)

No Classification (Dust/Mist)

For mixtures, hazard category was identified based on the

classification criteria for mixtures.



SDS: 49844-E81US Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Skin corrosion/irritation: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Serious eye damage/irritation: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory sensitization: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Skin sensitization: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Mutagenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Carcinogenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Reproductive toxicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Single

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Multi

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory toxic: Category 1

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Other information: No information for mixtures.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Ingredient
Base Oil(s)

Acute toxicity (oral): No Classification LC50:

> 5000 mg/kg[rat]

Acute toxicity (dermal): No Classification LC50:

> 5000 mg/kg[rat]

Acute toxicity (inhalation): Exempt classification (Gas)

Exempt classification (Vapour)
No Classification (Dust/Mist)

LC50:> 5 mg/L[rat]

Skin corrosion/irritation: No Classification

Serious eye damage/irritation: No Classification

Practically None

Respiratory sensitization: Classification not possible

Skin sensitization: No Classification

None Buehler method [guinea pig]

Mutagenicity: No Classification

Ames Test:Negative

Carcinogenicity: No Classification

EU: Category 2: R45 need not apply. (NOTE L is Applicable),

IARC:3

Reproductive toxicity: No Classification
Target organ effect/Single No Classification

exposure:

exposure:

Target organ effect/Multi No Classification

exposure:

Respiratory toxic: No Classification

Reaction product of alkylthioalcohol and substituted phosphorus compound

Acute toxicity (dermal): Category 5
Skin corrosion/irritation: Category 1B

12. Ecological information

Product

Ecotoxicity

Acute toxicity: Category 3

Fish acute toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Daphnia acute toxicity: No information.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

Algae acute toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Chronic toxicity: Category 3

Fish chronic toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Daphnia chronic toxicity: No information.

Algae chronic toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Persistence and degradability: No information available on mixtures

Bioaccumulative potential: No information for mixtures.

Mobility in soil: No information for mixtures.

Dangerous for the ozone layer: Classification not possible

Other impact: No information for mixtures.

Ingredient
Base Oil(s)

Ecotoxicity

Acute toxicity: No Classification

Fish acute toxicity: 96hLC50:> 5000 mg/L[Oncorhynchus mykiss]
Daphnia acute toxicity: 48hEC50:> 1000 mg/L[Daphnia magna]

Chronic toxicity: No Classification

Dangerous for the ozone layer: Classification not possible

Reaction product of alkylthioalcohol and substituted phosphorus compound

Ecotoxicity

Acute toxicity: Category 1
Chronic toxicity: Category 1

13. Disposal considerations

Disposal methods:

Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.

Before disposal of used container, remove contents completely.

Dispose of contents/container in accordance with local/regional/national/international regulations.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

14. Transport information

IATA UN Not regulated

 ${\tt classificatio}$

n:

UN number: Not regulated Proper Not regulated

shipping name:

Packing Not regulated

group:

IMDG UN Not regulated

classificatio

n:

UN number: Not regulated Proper Not regulated

shipping name:

Packing Not regulated

group:

Domestic restriction: No information.

Specific security Transport containers without causing any significant friction or shaking.

precaution and condition

of transportation:

15. Regulatory information

US California Proposition 65

This product can expose you to chemials including:

Methanol 10 (ppm)

Superfund Amendments and Reauthorization Act of 1986 (SARA TitleⅢ)

None present or none present in regulated concentrations.

Australia(AICS):
One or more components are not listed.
Canada(DSL):
One or more components are not listed.
China(IECSC):
One or more components are not listed.

EU(REACH): In the case where one or more components are not listed or, even if listed,

in the case of importing to the country or area concerned, an application or

notification is required.

Korea (K-REACH): In the case where one or more components are not listed or, even if listed,

in the case of importing to the country or area concerned, an application or

notification is required.



SDS: 49844-E81US

Date Prepared: 2022/04/19

Date Revised:

Product Name: TOYOTA E-TRANSAXLE FLUID TE

New Zealand(NZIoC):
One or more components are not listed.
Philippines(PICCS):
One or more components are not listed.
Taiwan(TCSI):
One or more components are not listed.
USA(TSCA):
All components are listed or exempted.*

*The exemption is only applied to ENEOS USA Inc.

16. Other information

NFPA Health hazard rating blue:0, Flammability hazard rating:1

HMIS Health Ratings:0, Flammability Ratings:1

Date Prepared: 2022/04/19
Reference No information.

Disclaimer: We at ENEOS Corporation have prepared the copyrighted Safety Data Sheet to

provide reference information on the hazardous chemical product of interest

for our customers/users to ensure secure and safe handling.

We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical

application of the product of interest.

Consequently, the Safety Data Sheet is not intended to guarantee the safety

of the product referenced to herein.