Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP CONCENTRATED DRIVEWAY & CONCRETE

CLEANER & DEGREASER 1GAL\_4CT

Material number : ZUCON128

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** 

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid	
Colour	purple	
Odour	ether-like	

## **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms

Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Precautionary statements : **Prevention:** 

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

CAS-No.	Concentration [%]	
68439-46-3	>= 1 - < 5	
111-76-2	>= 1 - < 5	
1310-73-2	>= 1 - < 5	
68081-81-2	>= 1 - < 5	
	68439-46-3 111-76-2 1310-73-2	

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Get medical attention immediately.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

Wash off immediately with plenty of water for at least 15

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

minutes.

If skin irritation persists, call a physician. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Take victim immediately to hospital.

Do not give milk or alcoholic beverages.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

	-			
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
2-butoxyethanol	111-76-2	TWA	20 ppm	CA AB OEL
-			97 mg/m3	ļ

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
			97 mg/m3	
		TWA	20 ppm	ACGIH
sodium hydroxide	1310-73-2	(c)	2 mg/m3	CA AB OEL
		С	2 mg/m3	CA BC OEL
		С	2 mg/m3	CA QC OEL
		С	2 mg/m3	ACGIH

### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyaceti c acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Appearance : liquid

Colour : purple
Odour : ether-like

Odour Threshold : No data available

pH : 13.5

Melting point/freezing point : No data available

Boiling point : 98.9 °C

Flash point

does not flash

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available
Density : 1.0230 g/cm3

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 6.6 mm2/s (20 °C)

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Oxidizing agents

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

This product contains sodium hydroxide or potassium hydroxide that may corrode some soft metals and may react

with tin, zinc, aluminum to form hydrogen gas.

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

**Potential Health Effects** 

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Alcohols, C9-11, ethoxylated:

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

#### Skin corrosion/irritation

### **Product:**

Remarks: Extremely corrosive and destructive to tissue.

### Serious eye damage/eye irritation

### **Product:**

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

## Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### **Aspiration toxicity**

No data available

## **Further information**

#### **Product:**

Remarks: No data available

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

**Components:** 

sodium hydroxide :

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h
Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: Not applicable

**Components:** 

sodium hydroxide:

Additional ecological

information

: Harmful to aquatic life.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYDROXIDE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

WHMIS - GHS Label Information:

Hazard pictograms

Corrosion

Signal word :

Hazard statements : Causes se

Precautionary statements

Causes severe skin burns and eye damage.

**Prevention:** Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

reuse.

Danger:

Storage: Store locked up.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	5.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.