Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : DSPLY ZEP FMNG WALL CLEANER QP_84CT LWS

Material number : ZUFWC1884NC

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas	
Colour	off-white, opaque	
Odour	ammoniacal	

GHS Classification

Gases under pressure : Liquefied gas

GHS label elements

Hazard pictograms :

Gas cylinder

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

and other ignition sources. No smoking.

P251 Pressurized container: Do not pierce or burn, even after

use.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 5
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
1-butoxypropan-2-ol	5131-66-8	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

: Effects may be delayed, symptoms may include minor eye or skin irritation.

delayed

Overexposure may cause mild eye or skin irritation.

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.
 Evacuate personnel to safe areas.
 Ensure adequate ventilation.
 Remove all sources of ignition.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

with pure water.

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : off-white, opaque

Odour : ammoniacal

Odour Threshold : No data available

pH : 10 - 11

Melting point/freezing point : No data available

Boiling point : 101.67 °C

Flash point

Not applicable

Evaporation rate : 1

n-Butyl Acetate = 1.0

Flammability (solid, gas,

liquid)

: The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : Not applicable

Relative vapour density : No data available

Density : No data available

Solubility(ies)

Water solubility : soluble in hot water, soluble in cold water

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined
Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 4.30 kJ/g

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Acids

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

butane:

Partition coefficient: n-

octanol/water **Components:**

: Remarks: No data available

Partition coefficient: n-: Pow: 2.89

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

octanol/water

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n- : Pow: 1

octanol/water

1-butoxypropan-2-ol:

Partition coefficient: n- : Pow: 1.2

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications

Revision Date 10/01/2023 Print Date 04/28/2025

noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms

Signal word Warning:

Hazard statements Contains gas under pressure; may explode if heated.

Precautionary statements Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

> Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this

Version 1.1 Revision Date 10/01/2023 Print Date 04/28/2025

document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.