## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name **ENFORCER BUG MAX FOGGER 6N2 36PK** 

Material number EBMFOG2

Manufacturer or supplier's details

Company Zep Commercial Sales & Service, a unit of Zep, Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

: Compliance Services - 877-428-9937 Telephone

#### **Emergency telephone numbers**

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. **Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas	
Colour	opaque, white	
Odour	characteristic	

#### **GHS Classification**

Flammable aerosols : Category 1 : Liquefied gas Gases under pressure Respiratory sensitisation Category 1

**GHS** label elements

Hazard pictograms





Gas cylinder



Signal word Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

P251 Pressurized container: Do not pierce or burn, even after

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P285 In case of inadequate ventilation wear respiratory protection.

Response:

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
propane	74-98-6	>= 20 - < 30
butane	106-97-8	>= 10 - < 20
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
alpha-cyano-3-phenoxybenzyl 3-(2,2-	52315-07-8	>= 0.1 - < 1
dichlorovinyl)-2,2-		
dimethylcyclopropanecarboxylate		

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If symptoms persist, call a physician.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

If skin irritation persists, call a physician.

In case of eye contact : Rinse with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and

: Use personal protective equipment.

Ensure adequate ventilation.

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

emergency procedures Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

Do not store near acids.

Store and keep away from bases and alkalies.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
		σκροσαίο	concentration	

# **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not smoke. When using do not eat or drink.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Appearance : Aerosol containing a liquefied gas

Colour : opaque, white
Odour : characteristic
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available
Boiling point : No data available

Flash point :

No data available

Evaporation rate : > 1

n-Butyl Acetate = 1.0

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.9604 g/cm3

Solubility(ies)

Water solubility : dispersible Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Acids Bases

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

**Aggravated Medical** 

Condition

Symptoms of Overexposure

: None known.

: Effects are immediate and delayed.

Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **Acute toxicity**

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate : 92.26 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

#### Skin corrosion/irritation

#### **Product:**

Result: No skin irritation

## Serious eye damage/eye irritation

### **Product:**

Remarks: May irritate eyes.

## Respiratory or skin sensitisation

#### **Components:**

alpha-cyano-3-phenoxybenzyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate: Classification: May cause sensitisation by inhalation.

## Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

### **Aspiration toxicity**

No data available

#### **Further information**

### **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

## Persistence and degradability

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water
Components:
butane:

: Remarks: No data available

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

## **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

This product is regulated under the United States Federal Insecticide, Fungicide and Rodenticide Act (FIFRA).

### Pesticide Labeling Information Required Under U.S. FIFRA Regulations

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label: CAUTION

Harmful if swallowed.

Causes moderate eve irritation.

Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Observe label precautions.

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

Respiratory or skin sensitisation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# **ENFORCER BUG MAX FOGGER 6N2 36PK**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **Further information**

#### NFPA:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



 $\Diamond$ 



Signal word

Hazard statements

Danger:

e Gas cylinder

Health hazard

. Dalių

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/ gas/ mist/ vapours/ spray. In case of inadequate ventilation wear respiratory protection.

Response: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122  $^{\circ}$ C

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ENFORCER BUG MAX FOGGER 6N2 36PK

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.