

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.

Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline Professional Series Intake Cleaner

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cleaner.

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA)

1-800-TEAMVAL (1-800-832-6825)

Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Serious eye damage : Category 1

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.

Causes serious eye damage.

Precautionary Statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Use only non-sparking tools.

Take precautionary measures against static discharge. Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PROPANOIC ACID, PROPYL ESTER	106-36-5	Flam. Liq. 2; H225	>=40.00 - < 50.00
		Acute Tox. 4; H332	
ETHANOL	64-17-5	Flam. Liq. 2; H225	>=5.00 - < 10.00
		Eye Irrit. 2A; H319	
		STOT SE 3; H336	
N,N-dimethyl 9-decenamide	1356964-77-6	Acute Tox. 4; H302	>=5.00 - < 10.00
		Skin Irrit. 2; H315	
		Eye Irrit. 2A; H319	
		STOT SE 3; H335	

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

ETHYL ACETATE	141-78-6	Flam. Liq. 2; H225	>=5.00 - < 10.00
		STOT SE 3; H336	
ETHOXYLATED ALCOHOL		Eye Irrit. 2B; H320	>=1.50 - < 5.00
QUATERNARY AMINE COMPOUND		Eye Dam. 1; H318	>=3.00 - < 5.00
GLYCERIN	56-81-5	Not a hazardous substance or mixture.	>=1.00 - < 1.50

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

IF INHALED: Call a POISON CENTER/ doctor if you feel

unwell.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

If on clothes, remove clothes.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

: No symptoms known or expected. Causes serious eye damage.

Valvoline	Page:
SAFETY DATA SHEET	Revision Date: 11/12/201
	Print Date: 7/24/201
	SDS Number: 00000027307
Valvoline Professional Series Intake Cleaner	Version: 3.
884526	

delayed

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Hydrocarbons

carbon dioxide and carbon monoxide

formaldehyde-like

Aldehydes

nitrogen oxides (NOx)

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Remove all sources of ignition. Use personal protective equipment.

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ETHANOL	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA P0
			1,900 mg/m3	
		PEL	1,000 ppm	CAL PEL
			1,900 mg/m3	
ETHYL ACETATE	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm	NIOSH REL
			1,400 mg/m3	
		TWA	400 ppm	OSHA Z-1
			1,400 mg/m3	
		TWA	400 ppm	OSHA P0
			1,400 mg/m3	
		PEL	400 ppm	CAL PEL
			1,400 mg/m3	
GLYCERIN	56-81-5	TWA	5 mg/m3	OSHA Z-1
			mist, respirable	
			fraction	
		TWA	15 mg/m3	OSHA Z-1
			mist, total dust	
		PEL	10 mg/m3	CAL PEL
			Mist - total	
			fraction	
		PEL	5 mg/m3	CAL PEL
			Mist - respirable	
			fraction	
		TWA	10 mg/m3	OSHA P0
			Mist - total dust	
		TWA	5 mg/m3	OSHA P0
			Mist - respirable	
			fraction	

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

In the case of vapour formation use a respirator with an

approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles and face shield when there is

potential for exposure of the eyes or face to liquid, vapor or

mist.

Maintain eye wash station in immediate work area.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : citrus

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : $> 95 \, ^{\circ}\text{F} / > 35 \, ^{\circ}\text{C}$

Flash point : 72 °F / 22 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : Expected 18 - 98 hPa

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.934 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

excessive heat

Incompatible materials : Acids

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Alkali metals aluminum Amines Ammonia Bases halogens

inorganic materials

Lead nitrates

Oxidizing agents

sodium strong alkalis

Zinc Peroxides

Hazardous decomposition

products No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 26.89 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

PROPANOIC ACID, PROPYL ESTER:

Acute oral toxicity : LD50 (Rat): 10,331 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute

inhalation toxicity, category 4.

Acute dermal toxicity : LD50 (Rabbit): > 14,128 mg/kg

ETHANOL:

Acute oral toxicity : LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC50 (Rat): 117 - 125 mg/l

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD Lo (Rabbit): 20 g/kg

N,N-dimethyl 9-decenamide:

Acute oral toxicity : LD50 (Rat): 550 mg/kg

Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 3.551 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

ETHYL ACETATE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 6000 ppm

Exposure time: 6 h
Test atmosphere: vapour

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

GLYCERIN:

Acute oral toxicity : LD50 (Rat): 12,600 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 570 mg/m3

Exposure time: 1 h
Test atmosphere: vapour

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 10,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components: ETHANOL:

Result : Slight, transient irritation

N,N-dimethyl 9-decenamide:

Method : OECD Test Guideline 439

Result : Irritating to skin.

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

ETHYL ACETATE:

Species : Rabbit

Result : Slight, transient irritation

GLYCERIN:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components: ETHANOL:

Result : Irritating to eyes.

N,N-dimethyl 9-decenamide:

Result : Irritating to eyes.

Method : OECD Test Guideline 437

ETHYL ACETATE:

Species : Rabbit

Result : Slight, transient irritation

ETHOXYLATED ALCOHOL:

Result : Mild eye irritation

QUATERNARY AMINE COMPOUND:

Result : Corrosive

GLYCERIN:

Species : Rabbit

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

N,N-dimethyl 9-decenamide:

Test Type : Local lymph node assay

Species : Mouse

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 429

ETHYL ACETATE:

Test Type : Maximisation Test

Result : Does not cause skin sensitisation.

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Germ cell mutagenicity

Not classified based on available information.

Components:

N,N-dimethyl 9-decenamide:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Method: OECD Test Guideline 474

Result: negative

ETHYL ACETATE:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

GLYCERIN:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components: ETHANOL:

Assessment : May cause drowsiness or dizziness.

N,N-dimethyl 9-decenamide:

Exposure routes : Inhalation

Target Organs : Respiratory Tract

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Assessment : May cause respiratory irritation.

ETHYL ACETATE:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Acute aquatic toxicity Category 2; Toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

ETHANOL:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12,000 - 16,000

mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

N,N-dimethyl 9-decenamide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 7.5 mg/l

Exposure time: 96 h

Test Type: flow-through test Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.8 mg/l

Exposure time: 48 h

Test Type: flow-through test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 6.3 mg/l

End point: Biomass Exposure time: 96 h

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Test Type: static test

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (microalgae)): 1.1

mg/l

End point: Biomass Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOEC (Danio rerio (zebra fish)): >= 0.71 mg/l

Exposure time: 35 d

Test Type: flow-through test

Method: OECD Test Guideline 210

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): > 0.37 mg/l

Exposure time: 21 d
Test Type: semi-static test

Method: OECD Test Guideline 211

ETHYL ACETATE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 - 250

mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia (water flea)): 154 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia (water flea)): 2.4 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

ETHOXYLATED ALCOHOL:

Ecotoxicology Assessment Short-term (acute) aquatic

hazard

: Toxic to aquatic life.

QUATERNARY AMINE COMPOUND:

Ecotoxicology Assessment

Short-term (acute) aquatic : Toxic t

hazard

: Toxic to aquatic life.

Valvoline	Page: 15
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

Long-term (chronic) aquatic

hazard

: Toxic to aquatic life with long lasting effects.

GLYCERIN:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia magna (Water flea)): 1,955 mg/l

Exposure time: 48 h Test Type: static test

Persistence and degradability

N,N-dimethyl 9-decenamide:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 63.93 % Exposure time: 28 d

Method: OECD Test Guideline 301B

ETHYL ACETATE:

Biodegradability : Result: Readily biodegradable.

GLYCERIN:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 94 % Exposure time: 1 d

No data available

Bioaccumulative potential

ETHANOL:

Partition coefficient: n-

: log Pow: -0.31

octanol/water

N,N-dimethyl 9-decenamide:

Partition coefficient: n- : log Pow: 3.17 (30 °C)

octanol/water pH: 6.69

ETHYL ACETATE:

Bioaccumulation : Species: Green algae (Chlorella fusca vacuolata)

Bioconcentration factor (BCF): 13,500

Exposure time: 24 h Concentration: 0.05 mg/l

Method: Static

Partition coefficient: n-

octanol/water

: log Pow: 0.68

GLYCERIN:

Partition coefficient: n-

octanol/water

: log Pow: -1.76

Valvoline.	Page: 16
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

No data available
Mobility in soil
No data available
Other adverse effects
No data available
Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.,

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

KEGGEATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

		· 			
UN	1993	FLAMMABLE LIQUID, N.O.S.	3	II	LIMITED
		(PROPANOIC ACID, PROPYL ESTER)			QUANTITY

CFR_RAIL_C

UN	1993	FLAMMABLE LIQUID, N.O.S.	3	II	LIMITED
		(PROPANOIC ACID, PROPYL			QUANTITY
		ESTER)			
		·		·	

	тм	Valvol	line.		Page: 17
SAF	ETY D	ATA SHEET		Revis	sion Date: 11/12/2018
<u> </u>					Print Date: 7/24/2019
				SDS Nu	ımber: 000000273071
Valvoli	ne Profes	sional Series Intake Cleaner		Version: 3.5	
884526	6				
J.S. DO UN	<mark>OT - INLAI</mark> 1993	ND WATERWAYS FLAMMABLE LIQUID, N.O.S.	3	II	LIMITED
		(PROPANOIC ACID, PROPYL ESTER)			QUANTITY
	OAD_C				LIMITED
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II	LIMITED QUANTITY
ΓDG_R	AIL_C				
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II	LIMITED QUANTITY
TDG IN	IWT C				
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II	LIMITED QUANTITY
NTERN	IATIONAL	_ MARITIME DANGEROUS GOOI	DS		
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II	LIMITED QUANTITY
NTERN	IATIONAL	_ AIR TRANSPORT ASSOCIATIO	N - CARGO		
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	11	

1141 - 1111	AIIOIIAL	AIN INAMOI ONI ACCOMATIC	M OAKOO	
UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	FLAMMABLE LIQUID, N.O.S.	3	II
		(PROPANOIC ACID, PROPYL		
		ESTER)		

MX_DG

UN	1993	FLAMMABLE LIQUID, N.O.S. (PROPANOIC ACID, PROPYL ESTER)	3	II

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Valvoline	Page: 18
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

		_
Marine pollutant	no	
Marine politicarit	110	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
ETHYL ACETATE	141-78-6	5000	76221	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory


TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

Valvoline	Page: 19
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

SECTION 16. OTHER INFORMATION

Further information Revision Date: 11/12/2018



NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IA

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Valvoline.	Page: 20
SAFETY DATA SHEET	Revision Date: 11/12/2018
	Print Date: 7/24/2019
	SDS Number: 000000273071
Valvoline Professional Series Intake Cleaner	Version: 3.5
884526	

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System