

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : RAIN-X FOR WHEELS

Material number : 000000000007600048

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	red
Odour	slight

GHS Classification

Skin irritation : Category 2

Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Corrosion

Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H318 Causes serious eye damage.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	$\geq 10 - < 30$
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	61789-40-0	$\geq 5 - < 10$
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	61789-77-3	$\geq 1 - < 5$
Propane-1,2-diol, propoxylated	25322-69-4	$\geq 1 - < 5$
propane-1,2-diol	57-55-6	$\geq 1 - < 5$
acetic acid	64-19-7	$\geq 1 - < 5$

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove to fresh air immediately. Get medical attention immediately.
- If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash contaminated clothing before re-use.
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Give small amounts of water to drink.
Do NOT induce vomiting.

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye damage.
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Dry powder
Carbon dioxide (CO₂)
Water spray jet

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
Chlorine compounds
Nitrogen oxides (NO_x)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.

Environmental precautions : Prevent product from entering drains.

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Do not breathe vapours or spray mist.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
Observe label precautions.

Materials to avoid : Oxidizing agents
Do not freeze.
Strong bases
Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
Propane-1,2-diol, propoxylated	25322-69-4	TWA (aerosol)	10 mg/m3	US WEEL
propane-1,2-diol	57-55-6	TWA	10 mg/m3	US WEEL
acetic acid	64-19-7	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		ST	15 ppm	NIOSH REL

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

			37 mg/m3	
		TWA	10 ppm 25 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	OSHA Z-1
		TWA	10 ppm 25 mg/m3	OSHA P0
		PEL	10 ppm 25 mg/m3	CAL PEL
		STEL	15 ppm 37 mg/m3	CAL PEL
		C	40 ppm	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Appearance	: liquid
Colour	: red
Odour	: slight
Odour Threshold	: No data available
pH	: 3.8 - 4.5, 100 %(as aqueous solution)
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: does not flash
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 0.995 - 1.105
Density	: No data available
Solubility(ies)	
Water solubility	: soluble in cold water, soluble in hot water
Solubility in other solvents	: Not applicable
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Strong bases
Hazardous decomposition	: Carbon dioxide (CO ₂)

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

products

Carbon monoxide
Chlorocarbons
Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

OSHA

2-butoxyethanol 111-76-2
No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 104.76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

acetic acid:

Acute oral toxicity : LD50 Oral Rat: 3,310 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

propane-1,2-diol :

Partition coefficient: n-octanol/water : log Pow: -1.07

acetic acid :

Partition coefficient: n-octanol/water : log Pow: -0.17

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetic acid	64-19-7	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Skin corrosion or irritation

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Serious eye damage or eye irritation

SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

2-butoxyethanol	111-76-2	10.5 %
-----------------	----------	--------

California Prop. 65



WARNING: This product can expose you to chemicals including dichloroacetic acid, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL

This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.

TSCA

On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Corrosion

Signal word

: **Danger:**

Hazard statements

: Causes skin irritation. Causes serious eye damage.

Precautionary statements

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Version:	3.3
Revision Date:	10/01/2023

SAFETY DATA SHEET

RAIN-X FOR WHEELS

Version 3.3

Revision Date 10/01/2023

Print Date 04/27/2025

Print Date:	04/27/2025
-------------	------------

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.