

# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Material number : 000000000001033570

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear, colourless
Odour	characteristic

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Flame



Gas cylinder



Health hazard

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after

# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

use.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 50
propane	74-98-6	>= 30 - < 50
butane	106-97-8	>= 20 - < 30
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	>= 3 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
If skin irritation persists, call a physician.  
Wash off with plenty of water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
Immediately flush eye(s) with plenty of water.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

#### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke  
Silicon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Take precautionary measures against static discharges.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Keep in a dry, cool and well-ventilated place.  
No smoking.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
		PEL (particulate)	5 mg/m <sup>3</sup>	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm	OSHA P0

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

			1,800 mg/m3	
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

**Engineering measures** : effective ventilation in all processing areas

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Safety glasses

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : clear, colourless

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : Not applicable

Boiling point : Not applicable

Flash point

:  
No data available

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

Evaporation rate	: < 1
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.785 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 46.7 kJ/g

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Extremes of temperature and direct sunlight. Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Potential Health Effects

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

##### Components:

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

#### Skin corrosion/irritation

##### Product:

Remarks: May cause skin irritation and/or dermatitis.

#### Serious eye damage/eye irritation

##### Product:

Remarks: May irritate eyes.

# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks: Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

##### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

### Mobility in soil

No data available



# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

### Other adverse effects

No data available

#### Product:

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications

## SAFETY DATA SHEET

### MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Aspiration hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:

HEALTH	3
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms

:



Flame



Gas cylinder



Health hazard

Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
May be fatal if swallowed and enters airways.

Precautionary statements

:

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET

## MISTY GLIDE SILICONE LUBRICANT 16N10 12CT

Version 4.2

Revision Date 10/01/2023

Print Date 04/25/2025

---

Version:	4.2
Revision Date:	10/01/2023
Print Date:	04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.