ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name ZEP CARB SPRAY_16N12_12CT

Material number 000000000001047446

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Compliance Services - 877-428-9937 Telephone

Emergency telephone numbers

For SDS Information Compliance Services - 877-428-9937

For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	clear
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1 : Compressed gas Gases under pressure Eye irritation : Category 2A Reproductive toxicity : Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity -

repeated exposure

(Inhalation)

: Category 2

GHS label elements

Hazard pictograms









Health hazard

Exclamation mark

Signal word : Danger

: H222 Extremely flammable aerosol. Hazard statements

H280 Contains gas under pressure; may explode if heated.

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 - < 30
toluene	108-88-3	>= 5 - < 10
carbon dioxide	124-38-9	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Get medical attention immediately.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression,

resulting in headache, nausea and/or dizziness.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

firefighting courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

or throw into fire even after use. Do not spray on flames or red-hot objects.

4/14

No smoking.

ZEP CARB SPRAY_16N12_12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Do not store near acids.

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control Basis parameters / Permissible concentration	
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm	NIOSH REL
			590 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			2,400 mg/m3	
		TWA	750 ppm	OSHA P0
			1,800 mg/m3	
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm	CAL PEL
			1,780 mg/m3	07.2.2
		С	3,000 ppm	CAL PEL
		PEL	500 ppm	CAL PEL
			1,200 mg/m3	
Distillates (petroleum),	64742-47-8	TWA	500 ppm	OSHA Z-1
hydrotreated light			2,000 mg/m3	
		TWA	400 ppm	OSHA P0
			1,600 mg/m3	
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		(particulate)		
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			375 mg/m3	
		ST	150 ppm	NIOSH REL
			560 mg/m3	
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm	OSHA P0
			375 mg/m3	
		STEL	150 ppm 560 mg/m3	OSHA P0
		PEL	10 ppm	CAL PEL
			37 mg/m3	J

ZEP CARB SPRAY_16N12_12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

		C	500 ppm	CAL PEL
		STEL	150 ppm	CAL PEL
			560 mg/m3	
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm	NIOSH REL
			9,000 mg/m3	
		ST	30,000 ppm	NIOSH REL
			54,000 mg/m3	
		TWA	5,000 ppm	OSHA Z-1
			9,000 mg/m3	
		TWA	10,000 ppm	OSHA P0
			18,000 mg/m3	
		STEL	30,000 ppm	OSHA P0
			54,000 mg/m3	
		PEL	5,000 ppm	CAL PEL
			9,000 mg/m3	
		STEL	30,000 ppm	CAL PEL
			54,000 mg/m3	

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH BEI
				last shift		
				of		
				workwee		
				k		
METHYLBENZENE		Toluene	Urine	End of	0.03 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
METHYLBENZENE		o-Cresol	Urine	End of	0.3.mg/g	ACGIH BEI
				shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. The use of skin protection is not normally required; however, good industrial

hygiene practice suggests the use of gloves or other

appropriate skin protection whenever working with chemicals, and especially if prolonged or frequent contact is possible or

likely.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : No special protection is required.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : clear

Odour : solvent-like

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point

Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

: Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

Density : 0.8 g/cm3

Solubility(ies)

Water solubility : partly soluble
Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 33.98 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression,

resulting in headache, nausea and/or dizziness.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

ZEP CARB SPRAY_16N12_12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

toluene:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

oomoont. m

: Remarks: No data available

octanol/water Components:toluene :

Partition coefficient: n-

: Pow: 2.73

octanol/water

Mobility in soil

No data available

Other adverse effects

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

Components: toluene :

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications

ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

toluene 108-88-3 9.975 %

California Prop. 65



WARNING: This product can expose you to chemicals including toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

Revision Date 10/01/2023

Print Date 04/27/2025

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

^{0 =} not significant, 1 =Slight,

HMIS III:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms









Gas cylinder

Health hazard

Signal word Hazard statements

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

^{2 =} Moderate, 3 = High

^{4 =} Extreme

SAFETY DATA SHEET ZEP CARB SPRAY 16N12 12CT

Version 2.2 Revision Date 10/01/2023 Print Date 04/27/2025

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/ container to an approved waste disposal plant.

Version:	2.2
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.