# **ZEP TIME SAVER 55GL**

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP TIME SAVER\_55GL

Material number : 00000000000201785

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

### **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Colour	amber, clear
Odour	characteristic

# **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms

Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:** 

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2-phenoxyethanol	122-99-6	>= 5 - < 10
2-aminoethanol	141-43-5	>= 5 - < 10
sodium xylenesulphonate	1300-72-7	>= 5 - < 10
Alcohols, C9-11, ethoxylated	68439-46-3	>= 1 - < 3
1-butoxypropan-2-ol	5131-66-8	>= 1 - < 3
Sodium metasilicate (disodium salt)	6834-92-0	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Sulphur oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

# **ZEP TIME SAVER 55GL**

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-aminoethanol	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1
		STEL	6 ppm 15 mg/m3	OSHA P0
		TWA	3 ppm 8 mg/m3	OSHA P0
		PEL	3 ppm 8 mg/m3	CAL PEL
		STEL	6 ppm 15 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber, clear
Odour : characteristic
Odour Threshold : No data available

pH : 12.5 - 13.5Boiling point :  $100 \, ^{\circ}\text{C}$ Flash point :  $> 93.3 \, ^{\circ}\text{C}$ 

Method: closed cup

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 1.056 g/cm3

Solubility(ies)

# **ZEP TIME SAVER 55GL**

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

Water solubility : soluble in cold water, soluble in hot water

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 7 mm2/s (20 °C)

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke). Organic Substances

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

**Aggravated Medical** 

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

# SAFETY DATA SHEET ZEP TIME SAVER 55GL

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

Product:

Acute oral toxicity : Acute toxicity estimate : 3,986 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 188.46 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

2-aminoethanol:

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

Sodium metasilicate (disodium salt):

Acute oral toxicity : LD50 Rat: 1,153 mg/kg

Skin corrosion/irritation

**Product:** 

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

**Product:** 

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

# **ZEP TIME SAVER 55GL**

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water Components:

2-aminoethanol :

Partition coefficient: n- : log Pow: -1.31

octanol/water

1-butoxypropan-2-ol:

Partition coefficient: n- : Pow: 1.2

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

# SAFETY DATA SHEET ZEP TIME SAVER 55GL

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life.

The GHS H401 statement "Toxic to aquatic life" noted

above is an Acute Aquatic Toxicity Category 2

classification. Although the product has the potential to harm the environment, it is not classified as a marine pollutant or regulated under transportation regulations.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

### NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

# **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2,2'-iminodiethanol	111-42-2	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-phenoxyethanol 122-99-6 8.9975 %

## California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, ethylbenzene, which is/are known to the State of California to cause cancer. For more

information go to www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

# **SAFETY DATA SHEET ZEP TIME SAVER\_55GL**

Print Date 04/27/2025 Version 6.1 Revision Date 10/01/2023

**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

# **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

## **Further information**

## NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

<sup>0 =</sup> not significant, 1 =Slight,

## HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

# **OSHA - GHS Label Information:**

Hazard pictograms



<sup>2 =</sup> Moderate, 3 = High

<sup>4 =</sup> Extreme

# SAFETY DATA SHEET ZEP TIME SAVER 55GL

Version 6.1 Revision Date 10/01/2023 Print Date 04/27/2025

Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

**Prevention:** Wash skin thoroughly after handling. Wear protective gloves/ protective

clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	6.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.