

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY STAINLESS STEEL CLEANER

Material number : 000000000001001541

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street  
Edmonton, Alberta T5S 1N6  
Canada

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview


Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin sensitisation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 60
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 30
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
Oils, sweet orange (terpenes and terpenoids)	68647-72-3	>= 0.1 - < 1
citral	5392-40-5	>= 0.1 - < 1

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

	If on clothes, remove clothes.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time). Causes skin irritation. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
-----------------------	--------------------------------------

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

protective equipment and emergency procedures	Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Always replace cap after use. Do not breathe vapours or spray mist.
Conditions for safe storage	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
------------	---------	----------------------------------	----------------------------------	-------

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

			concentration	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses  
Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 4,136 hPa (21 °C)
Relative vapour density	: No data available
Density	: 0.856 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 46.27 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous	: Vapours may form explosive mixture with air.

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

reactions	No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides Smoke

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time). Causes skin irritation. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### Acute toxicity

##### Product:

Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
-----------------------	---

##### Components:

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

##### **Distillates (petroleum), hydrotreated light:**

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

### Skin corrosion/irritation

#### Product:

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

### Respiratory or skin sensitisation

#### Product:

Remarks: Causes sensitisation.

#### Components:

##### **Oils, sweet orange (terpenes and terpenoids):**

Classification: May cause sensitisation by skin contact.

##### **citral:**

Classification: May cause sensitisation by skin contact.

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:



# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Remarks: No data available

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

##### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

##### Components:

##### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

##### **citral :**

Partition coefficient: n-octanol/water : log Pow: 2.9 (25 °C)  
Method: OECD Test Guideline 117

#### Mobility in soil

No data available

#### Other adverse effects

No data available

##### Product:

Additional ecological information : No data available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

---

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

### SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

<b>DSL</b>	All components of this product are on the Canadian DSL
<b>TSCA</b>	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

---

### SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

# SAFETY DATA SHEET


## MISTY STAINLESS STEEL CLEANER

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
May cause an allergic skin reaction.

Precautionary statements

:

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

**Response:** IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.