

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY SI-DRY SILICONE LUBRICANT

Material number : 000000000001033585

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | colourless |
| Odour | hydrocarbon-like |

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

Hazard pictograms

:



Flame



Gas cylinder



Health hazard



Exclamation mark

Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|--|------------|-------------------|
| acetone | 67-64-1 | $\geq 30 - < 60$ |
| Distillates (petroleum), light distillate hydrotreating process, low-boiling | 68410-97-9 | $\geq 10 - < 30$ |
| butane | 106-97-8 | $\geq 10 - < 30$ |
| propane | 74-98-6 | $\geq 5 - < 10$ |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
Get medical attention.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Wash contaminated clothing before re-use.
Remove contaminated clothing and shoes.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Effects are dependent on exposure (dose, concentration, contact time).
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

SECTION 5. FIREFIGHTING MEASURES

| | |
|---|---|
| Suitable extinguishing media | : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon dioxide (CO2) Carbon monoxide Smoke Silicon oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. |

SECTION 7. HANDLING AND STORAGE

| | |
|-------------------------|---|
| Advice on safe handling | : Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. |
|-------------------------|---|

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Always replace cap after use.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
Keep in a dry, cool and well-ventilated place.

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|----------|----------------------------------|---|-----------|
| acetone | 67-64-1 | TWA | 500 ppm 1,200 mg/m3 | CA AB OEL |
| | | STEL | 750 ppm 1,800 mg/m3 | CA AB OEL |
| | | TWA | 250 ppm | CA BC OEL |
| | | STEL | 500 ppm | CA BC OEL |
| | | STEV | 1,000 ppm 2,380 mg/m3 | CA QC OEL |
| | | TWAEV | 500 ppm 1,190 mg/m3 | CA QC OEL |
| | | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| butane | 106-97-8 | TWA | 1,000 ppm | CA AB OEL |
| | | TWA | 600 ppm | CA BC OEL |

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

| | | | | |
|---------|---------|-------|--------------------------|-----------|
| | | STEL | 750 ppm | CA BC OEL |
| | | TWAEV | 800 ppm 1,900 mg/m3 | CA QC OEL |
| | | STEL | 1,000 ppm | ACGIH |
| propane | 74-98-6 | TWA | 1,000 ppm | CA AB OEL |
| | | TWA | 1,000 ppm | CA BC OEL |
| | | TWAEV | 1,000 ppm 1,800 mg/m3 | CA QC OEL |
| | | TWA | 1,000 ppm | CA ON OEL |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|--|---------------------------|-----------|
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

| | |
|--|--------------------------------------|
| Appearance | : Aerosol containing a liquefied gas |
| Colour | : colourless |
| Odour | : hydrocarbon-like |
| Odour Threshold | : No data available |
| pH | : Not applicable |
| Melting point/freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Evaporation rate | : > 1 |
| Flammability (solid, gas, liquid) | : Extremely flammable aerosol. |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Density | : No data available |
| Solubility(ies) | |
| Water solubility | : partly soluble |
| Solubility in other solvents | : not determined |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : 39.79 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. |

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Effects are dependent on exposure (dose, concentration, contact time).
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity: IARC

Group 2B: Possibly carcinogenic to humans

Distillates (petroleum), light distillate hydrotreating process, low-boiling 68410-97-9

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

| |
|--|
| Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|--|

| |
|--|
| Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity |
|--|

| |
|--|
| Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity |
|--|

| |
|--|
| Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity |
|--|

| |
|--|
| Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity |
|--|

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

:
Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get

SAFETY DATA SHEET

MISTY SI-DRY SILICONE LUBRICANT

Version 1.1

Revision Date 10/01/2023

Print Date 04/25/2025

medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

| | |
|----------------|------------|
| Version: | 1.1 |
| Revision Date: | 10/01/2023 |
| Print Date: | 04/25/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.