AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : AAP SPRAY SEALANT PEACH_15GL

Material number : H29945

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	light yellow
Odour	like fruit

GHS Classification

Flammable liquids : Category 3
Skin irritation : Category 2
Serious eye damage : Category 1

GHS label elements

Hazard pictograms



Corrosion

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

AAP SPRAY SEALANT PEACH 15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration [%]
111-76-2	>= 10 - < 30
68604-75-1	>= 10 - < 30
1643-20-5	>= 5 - < 10
61789-40-0	>= 1 - < 5
67-63-0	>= 1 - < 5
3332-27-2	>= 1 - < 5
	111-76-2 68604-75-1 1643-20-5 61789-40-0

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

AAP SPRAY SEALANT PEACH 15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

If symptoms persist, call a physician.

If on clothes, remove clothes.

Wash contaminated clothing before re-use.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

Continue rinsing eyes during transport to hospital.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Chlorine compounds

Specific extinguishing : Use extinguishing measures that are appropriate to local

AAP SPRAY SEALANT PEACH 15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

methods circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Materials to avoid : Oxidizing agents

Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm 97 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200.mg/g Creatinine	ACGIH BEI
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow
Odour : like fruit

Odour Threshold : No data available

pH : 6.0 - 7.0

Melting point/freezing point : Not applicable
Boiling point : 104.44 °C
Flash point : 59.4 °C

Method: TCC

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.975 g/cm3

Solubility(ies)

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

Water solubility : completely soluble
Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : not determined
Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 19.4 mm2/s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides Chlorine

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2 hydrogen peroxide 7722-84-1

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,518 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 38.6 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,442 mg/kg

Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Components:

N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

N,N-dimethyltetradecylamine N-oxide:

Remarks: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

N,N-dimethyltetradecylamine N-oxide:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and

other aquatic invertebrates

: Remarks: No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water **Components**:

: Remarks: No data available

AAP SPRAY SEALANT PEACH 15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

propan-2-ol:

Partition coefficient: n-

octanol/water

: log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (ETHYLENE GLYCOL MONOBUTYL ETHER), 3, III

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ETHYLENE GLYCOL MONOBUTYL ETHER), 3, III

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (ETHYLENE GLYCOL MONOBUTYL ETHER), 3, III

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (ETHYLENE GLYCOL MONOBUTYL ETHER), 3, III

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (ETHYLENE GLYCOL MONOBUTYL ETHER), 3, III

AAP SPRAY SEALANT PEACH 15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylene oxide	75-21-8	10	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
	10-0-0	(/	(100)
2-chloroethanol	107-07-3	500	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Skin corrosion or irritation

SARA 302 : The following components are subject to reporting levels

established by SARA Title III, Section 302:

2-chloroethanol 107-07-3 0.75 %

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-butoxyethanol 111-76-2 11.9992 %

California Prop. 65



WARNING: This product can expose you to chemicals including ethylene oxide, dichloroacetic acid, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to

www.P65Warnings.ca.gov.

AAP SPRAY SEALANT PEACH_15GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/28/2025

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	3
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

^{0 =} not significant, 1 = Slight,

HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

^{2 =} Moderate, 3 = High

^{4 =} Extreme

AAP SPRAY SEALANT PEACH_15GL

Revision Date 10/01/2023 Print Date 04/28/2025

Hazard pictograms





Signal word Hazard statements Precautionary statements

Danger: Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection. Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry

chemical or alcohol-resistant foam to extinguish. Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.