Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP PERIMETER 20N18OZ_12CT

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas	
Colour	white	
Odour	alcohol-like, amine-like	

GHS Classification

Flammable aerosols : Category 2
Gases under pressure : Liquefied gas
Skin corrosion : Category 1B
Serious eye damage : Category 1

GHS label elements

Hazard pictograms







Gas cylinder

Signal word : Danger

Hazard statements : H223 Flammable aerosol.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements : **Prevention**:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
2-aminoethanol	141-43-5	>= 1 - < 5
2-butoxyethanol	111-76-2	>= 1 - < 5
ethanol	64-17-5	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Do not leave the victim unattended.

Show this safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

In case of skin contact : Wash off with soap and water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with

difficulty.

If on clothes, remove clothes.

Wash off immediately with plenty of water for at least 15

minutes.

Wash contaminated clothing before re-use.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If in eyes, rinse with water for 15 minutes.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

regulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep in a cool, well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Storage temperature : 4.4 - 49 °C

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
	07.00.0	T)A/A	concentration	
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm	CA QC OEL
		0121	1,230 mg/m3	ON GO OLL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
	11.11	TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm	CA QC OEL
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
2-aminoethanol	141-43-5	STEL	6 ppm	CA AB OEL
			15 mg/m3	
		TWA	3 ppm 7.5 mg/m3	CA AB OEL
		TWA	3 ppm	CA BC OEL
		STEL	6 ppm	CA BC OEL
		TWAEV	3 ppm 7.5 mg/m3	CA QC OEL
		STEV	6 ppm 15 mg/m3	CA QC OEL
		TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm	CA QC OEL
			1,880 mg/m3	0,1,00000
		TWA	1,000 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
p		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 mg/ms	CA ON OEL
		1 1 1 1 1 1	1,000 ppill	OA ON OEL

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI
2-BUTOXYETHANOL	111-76-2	Butoxyaceti c acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : white

Odour : alcohol-like, amine-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Boiling point : No data available

Flash point

Not applicable

Evaporation rate : < 1

n-Butyl Acetate = 1.0

Flammability (solid, gas,

liquid)

: Flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : No data available

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Alkali metals

Copper Strong acids

Hazardous decomposition

products

: Carbon oxides

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

ethanol 64-17-5

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

2-aminoethanol:

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water Components: propan-2-ol:

Partition coefficient: n-

: log Pow: 0.05

octanol/water butane:

Partition coefficient: n-

: Pow: 2.89

octanol/water **2-aminoethanol**:

Partition coefficient: n-

: log Pow: -1.31

octanol/water

ethanol:

Partition coefficient: n-

: Remarks: No data available

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Revision Date 10/01/2023 Print Date 04/27/2025

Hazard pictograms







Signal word Danger: Hazard statements Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin

irritation. Causes serious eye damage.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly

after handling. Wear protective gloves/ eye protection/ face protection. **Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.