

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP DYNA 170° 55GL

Material number : 000000000000017985

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	colourless
Odour	hydrocarbon-like

#### GHS Classification

Flammable liquids : Category 4  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

and other ignition sources. No smoking.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 90 - <= 100

The exact percentages of disclosed substances are withheld as trade secrets.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

- Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical  
Carbon dioxide (CO<sub>2</sub>)  
Foam
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
		PEL (particulate)	5 mg/m <sup>3</sup>	CAL PEL

- Engineering measures** : effective ventilation in all processing areas

#### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Hand protection	
Material	: Protective gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: colourless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: > 213 °C
Flash point	: 78 - 85 °C Method: closed cup
Evaporation rate	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 0.6 %(V)
Vapour pressure	: 0.066 hPa
Relative vapour density	: No data available
Density	: 0.815 g/cm3
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Viscosity

Viscosity, kinematic : 5.5 mm<sup>2</sup>/s

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : Carbon oxides  
Organic Substances

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.  
Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

##### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

##### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

by NTP.

### Acute toxicity

#### Product:

Acute dermal toxicity : Acute toxicity estimate : 2,778 mg/kg  
Method: Calculation method

#### Components:

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

### Skin corrosion/irritation

#### Product:

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks: Severe eye irritation

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

Remarks: Solvents may degrease the skin.

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

##### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

##### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.



# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.  
No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Aspiration hazard

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

---

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

### Further information

#### NFPA:

HEALTH	2
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep cool.

# SAFETY DATA SHEET

## ZEP DYNA 170° 55GL

Version 2.1

Revision Date 10/01/2023

Print Date 04/27/2025

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.