## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A07870 ZEP 40 LV\_2CS 20N18

Material number : EC3229012

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

## **Emergency telephone numbers**

For SDS Information: Compliance Services - 877-428-9937For a Medical Emergency: 877-541-2016 Toll Free - All Calls RecordedFor a Transportation: CHEMTREC: 800-424-9300 - All Calls Recorded.EmergencyIn the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	mint-like

#### **GHS Classification**

Gases under pressure : Liquefied gas

**GHS** label elements

Signal word

Hazard pictograms :



Gas cylinder Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P251 Pressurized container: Do not pierce or burn, even after

use. Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

olace.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

## Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 5
ethanol	64-17-5	>= 1 - < 5
propane	74-98-6	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Do not leave the victim unattended.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : If in eyes, rinse with water for 15 minutes.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

delayed

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

# A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

Water spray jet Carbon dioxide (CO2) Alcohol-resistant foam

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition.
Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

For personal protection see section 8.

# A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the application area.

Do not breathe vapours or spray mist.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

No smoking.

Materials to avoid : Strong oxidizing agents

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Eye wash bottle with pure water

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : white
Odour : mint-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available Boiling point : No data available

Flash point :

Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

: Not classified as a flammability hazard

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : No data available

Solubility(ies)

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

# A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Components:** 

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

Components: butane :

Partition coefficient: n-

octanol/water

ethanol:

Partition coefficient: n-

octanol/water

: Remarks: No data available

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

: Pow: 2.89

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

SARA 302 : The following components are subject to reporting levels

established by SARA Title III, Section 302:

## A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

# A07870 ZEP 40 LV\_2CS 20N18

Revision Date 10/01/2023 Print Date 04/28/2025 Version 2.3

### **Further information**

#### NFPA:

HEALTH	1
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Warning: Contains gas under pressure; may explode if heated.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

**Storage:** Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.3
Revision Date:	10/01/2023
Print Date:	04/28/2025

# SAFETY DATA SHEET A07870 ZEP 40 LV 2CS 20N18

Version 2.3 Revision Date 10/01/2023 Print Date 04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.