

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP BMF ASPHALT RELEASE AGENT\_60GL

Material number : 000000000000436986

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	amber, brown
Odour	characteristic

#### GHS Classification

Eye irritation : Category 2B

#### GHS label elements

Signal word : Warning

Hazard statements : H320 Causes eye irritation.

Precautionary statements : **Prevention:**  
P264 Wash skin thoroughly after handling.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

Substance / Mixture : Mixture

### Hazardous components

No hazardous ingredients

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with plenty of water.  
Remove contaminated clothing and shoes.  
If symptoms persist, call a physician.  
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Do NOT induce vomiting.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes eye irritation.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

Hazardous combustion products	: Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Nitrogen oxides (NO <sub>x</sub> )
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Standard procedure for chemical fires. Cool containers/tanks with water spray.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Material can create slippery conditions. Use non-slip safety shoes in areas where spills or leaks can occur. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Use only in area provided with appropriate exhaust ventilation.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Materials to avoid	: Oxidizing agents Store and keep away from, oxidizing agents and acids.
Packaging material	: Suitable material: Mild steel

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
urea	57-13-6	TWA	10 mg/m3	US WEEL

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses with side-shields

Face-shield

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Do not enter confined spaces unless adequately ventilated.

Do not enter confined spaces without a safety observer monitoring activities from outside the vessel.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: amber, brown

Odour

: characteristic

Odour Threshold

: No data available

pH

: 8 - 9

Melting point/freezing point

: -20 °C

Boiling point

: > 100 °C

Flash point

: > 205 °C

Evaporation rate

: 1

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: < 22.6 hPa (20 °C)
Relative vapour density	: Not applicable
Density	: 1.1 - 1.2 g/cm3 (19.6 °C)
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 200 mm2/s (40 °C)

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Contact with incompatible materials. Heat, flames and sparks.
Incompatible materials	: Strong acids Oxidizing agents
Hazardous decomposition products	: Carbon oxides Carbon dioxide (CO2) Nitrogen oxides (NOx)

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed.

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

Symptoms may include irritation, redness, pain, and rash.  
Effects are dependent on exposure (dose, concentration, contact time).

Causes eye irritation.

Review section 2 of SDS to see all potential hazards.

Treat symptomatically. Symptoms may be delayed.

### Carcinogenicity:

#### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Acute toxicity

#### Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

### Skin corrosion/irritation

#### Product:

Remarks: May cause skin irritation in susceptible persons.

### Serious eye damage/eye irritation

#### Product:

Result: Mild eye irritation

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:

Remarks: No data available

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Readily biodegradable

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

- TSCA list** : No substances are subject to a Significant New Use Rule.
- No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act



# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
pentasodium triphosphate	7758-29-4	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## ZEP BMF ASPHALT RELEASE AGENT\_60GL

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

### Further information

#### NFPA:

<b>HEALTH</b>	<b>0</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>INSTABILITY</b>	<b>0</b>
<b>SPECIAL HAZARD.</b>	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme

#### HMIS III:

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Signal word : **Warning:**  
Hazard statements : Causes eye irritation.  
Precautionary statements :  
**Prevention:** Wash skin thoroughly after handling.  
**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Version:	4.0
Revision Date:	03/06/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations

## **SAFETY DATA SHEET**

### **ZEP BMF ASPHALT RELEASE AGENT\_60GL**

Version 4.0

Revision Date 03/06/2024

Print Date 04/27/2025

to determine the suitability and applicability of the information for their particular purposes.  
This SDS has been prepared by the Compliance Services organization supporting this  
manufacturer, supplier or distributor.