

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Material number : 000000000001050849

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	copper
Odour	solvent-like

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Eye irritation : Category 2A  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :



Flame



Gas cylinder



Exclamation mark



Health hazard

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

H304 May be fatal if swallowed and enters airways.

Precautionary statements

: **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

**Response:**

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 20 - < 30
acetone	67-64-1	>= 10 - < 20
propane	74-98-6	>= 5 - < 15
heptane	142-82-5	>= 5 - < 10
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10
copper	7440-50-8	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled

: Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.

## SAFETY DATA SHEET

### ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

In case of skin contact	: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye irritation. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

---

#### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and	: Use personal protective equipment. Ensure adequate ventilation.
--	--

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

- emergency procedures      Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions      : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up      : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling      : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.
- Conditions for safe storage      : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid      : Keep away from oxidizing agents and strongly acid or alkaline materials.  
soft metals

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
copper	7440-50-8	TWA (dusts and mists)	1 mg/m3	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3	OSHA Z-1
		TWA (Dust and mist)	1 mg/m3	ACGIH
		TWA	0.2 mg/m3	ACGIH

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

		(Fumes)		
		TWA (Dust)	1 mg/m3	NIOSH REL
		TWA (Mist)	1 mg/m3	NIOSH REL
		TWA (dusts and mists)	1 mg/m3	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3	OSHA Z-1
		PEL (Fumes)	0.1 mg/m3	CAL PEL

### Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.  
Safety goggles

Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : copper

Odour : solvent-like

## SAFETY DATA SHEET

### ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0.87 - 0.89 g/cm <sup>3</sup> (25 °C)
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, kinematic	: No data available

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.  Do not expose to temperatures above: 50 °C
Incompatible materials	: soft metals Strong acids and strong bases Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Potential Health Effects

## SAFETY DATA SHEET

### ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes serious eye irritation.  
May be fatal if swallowed and enters airways.  
Review section 2 of SDS to see all potential hazards.  
Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

##### Components:

###### **acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l  
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

###### **heptane:**

Acute inhalation toxicity : LC50 Rat: 103 mg/l  
Exposure time: 4 h

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l



# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

**copper:**

Acute oral toxicity : LD50 Rat: 300 - 500 mg/kg

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

### Skin corrosion/irritation

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

### Serious eye damage/eye irritation

**Product:**

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

##### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

##### Components:

##### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

##### **heptane :**

Partition coefficient: n-octanol/water : log Pow: 5

#### Mobility in soil

No data available

#### Other adverse effects

No data available

##### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethylene oxide	75-21-8	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Serious eye damage or eye irritation

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

### SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

copper	7440-50-8	7.499 %
--------	-----------	---------

### California Prop. 65



WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

DSL  
TSCA

All components of this product are on the Canadian DSL  
On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

---

## SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

### Further information

#### NFPA:

HEALTH	1
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme


#### HMIS III:

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	1

0 = not significant, 1 =Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Danger:**  
: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.  
: **Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection.  
: **Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.  
: **Storage:** Store in a well-ventilated place. Keep cool.

# SAFETY DATA SHEET

## ZEP GROOVY COPPER ANTI-SEIZE LUBRICANT 6CS 20N15

Version 1.1

Revision Date 04/29/2024

Print Date 04/25/2025

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	04/29/2024
Print Date:	04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.