

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP PRESERVE NC TOOL RENTAL_12CS

Material number : TR31501

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| | |
|------------|-------------------------------------|
| Appearance | Aerosol containing a compressed gas |
| Colour | amber |
| Odour | solvent-like |

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1
Carcinogenicity : Category 2

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

H351 Suspected of causing cancer.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|--|---------------|-------------------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | >= 30 - < 50 |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | >= 20 - < 30 |
| 1,2,4-trimethylbenzene | 95-63-6 | >= 5 - < 10 |
| 2-ethylhexan-1-ol | 104-76-7 | >= 3 - < 5 |
| Distillates (petroleum), straight-run middle | 64741-44-2 | >= 3 - < 5 |
| Aromatic Hydrocarbons (C9 - C10) | Not Available | >= 3 - < 5 |
| ethanol | 64-17-5 | >= 3 - < 5 |
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | >= 3 - < 5 |

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

| | | |
|----------------|----------|------------------|
| carbon dioxide | 124-38-9 | $\geq 3 - < 5$ |
| 3-ethyltoluene | 620-14-4 | $\geq 1 - < 3$ |
| mesitylene | 108-67-8 | $\geq 1 - < 3$ |
| 4-ethyltoluene | 622-96-8 | $\geq 1 - < 3$ |
| cumene | 98-82-8 | $\geq 0.1 - < 1$ |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on clothes, remove clothes.
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
Immediately flush eyes for at least 15 minutes. Get medical attention.
- If swallowed : Keep respiratory tract clear.
Take victim immediately to hospital.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Symptoms may include irritation, redness, pain, and rash.
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.

Effects are dependent on exposure (dose, concentration, contact time).
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

| | |
|---|---|
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon dioxide (CO ₂) Carbon monoxide Smoke |
| Specific extinguishing methods | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. |

SECTION 7. HANDLING AND STORAGE

| | |
|-------------------------|---|
| Advice on safe handling | : Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, |
|-------------------------|---|

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Keep in a dry, cool and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|----------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA | 500 ppm 2,000 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |
| | | PEL (particulate) | 5 mg/m3 | CAL PEL |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Inhalable fraction) | 5 mg/m3 | ACGIH |
| 1,2,4-trimethylbenzene | 95-63-6 | TWA | 25 ppm 125 mg/m3 | NIOSH REL |
| ethanol | 64-17-5 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm | ACGIH |
| | | PEL | 1,000 ppm 1,900 mg/m3 | CAL PEL |
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | TWA (Inhalable fraction and | 10 ppm | ACGIH |

SAFETY DATA SHEET**ZEP PRESERVE NC TOOL RENTAL_12CS**

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

| | | | | |
|----------------|----------|--------|----------------------------|-----------|
| | | vapor) | | |
| carbon dioxide | 124-38-9 | TWA | 5,000 ppm | ACGIH |
| | | STEL | 30,000 ppm | ACGIH |
| | | TWA | 5,000 ppm 9,000 mg/m3 | NIOSH REL |
| | | ST | 30,000 ppm 54,000 mg/m3 | NIOSH REL |
| | | TWA | 5,000 ppm 9,000 mg/m3 | OSHA Z-1 |
| | | TWA | 10,000 ppm 18,000 mg/m3 | OSHA P0 |
| | | STEL | 30,000 ppm 54,000 mg/m3 | OSHA P0 |
| | | PEL | 5,000 ppm 9,000 mg/m3 | CAL PEL |
| | | STEL | 30,000 ppm 54,000 mg/m3 | CAL PEL |
| mesitylene | 108-67-8 | TWA | 25 ppm 125 mg/m3 | NIOSH REL |
| | | TWA | 25 ppm | ACGIH |
| | | TWA | 25 ppm 125 mg/m3 | OSHA P0 |
| | | PEL | 25 ppm 125 mg/m3 | CAL PEL |
| cumene | 98-82-8 | TWA | 50 ppm | ACGIH |
| | | TWA | 50 ppm 245 mg/m3 | NIOSH REL |
| | | TWA | 50 ppm 245 mg/m3 | OSHA Z-1 |
| | | TWA | 50 ppm 245 mg/m3 | OSHA P0 |
| | | PEL | 50 ppm 245 mg/m3 | CAL PEL |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---------------------------------------|
| Appearance | : Aerosol containing a compressed gas |
| Colour | : amber |
| Odour | : solvent-like |
| Odour Threshold | : No data available |
| pH | : Not applicable |
| Melting point/freezing point | : Not applicable |
| Boiling point | : No data available |
| Flash point | : No data available |
| Evaporation rate | : < 1 |
| Flammability (solid, gas, liquid) | : Extremely flammable aerosol. |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Density | : 0.85 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : > 20 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | : Carbon oxides |

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

| | |
|------------------------------|--|
| Aggravated Medical Condition | : None known. |
| Symptoms of Overexposure | : Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions. Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed. |

Carcinogenicity:

| | | |
|--------------|--|---------|
| IARC | Group 2B: Possibly carcinogenic to humans | |
| | cumene | 98-82-8 |
| ACGIH | Confirmed animal carcinogen with unknown relevance to humans | |
| | ethanol | 64-17-5 |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. | |
| NTP | Reasonably anticipated to be a human carcinogen | |
| | cumene | 98-82-8 |

Acute toxicity

Product:

| | |
|---------------------------|---|
| Acute oral toxicity | : Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : Acute toxicity estimate : 29.31 mg/l Exposure time: 4 h |

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

2-ethylhexan-1-ol:

Acute oral toxicity : LD50 Oral Rat: 3,730 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 3,000 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

Components:

Distillates (petroleum), straight-run middle:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

2-ethylhexan-1-ol :

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

Partition coefficient: n-octanol/water : Pow: 2.9

ethanol :

Partition coefficient: n-octanol/water : Remarks: No data available

2-(2-butoxyethoxy)ethanol :

Partition coefficient: n-octanol/water : Pow: 1

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|-----------|-----------------------|--------------------------------|
| xylenes | 1330-20-7 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation
Carcinogenicity

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|---------------------------|----------|----------|
| 1,2,4-trimethylbenzene | 95-63-6 | 5.1184 % |
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | 3.2959 % |

California Prop. 65

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025



WARNING: This product can expose you to chemicals including cumene, ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

Further information

NFPA:

| | |
|-----------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 4 |
| INSTABILITY | 0 |
| SPECIAL HAZARD. | |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

| | |
|-----------------|----|
| HEALTH | 3* |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Flame

Gas cylinder

Health hazard

Exclamation
mark

Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Suspected of causing cancer.

Precautionary statements

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin

SAFETY DATA SHEET

ZEP PRESERVE NC TOOL RENTAL_12CS

Version 5.1

Revision Date 10/01/2023

Print Date 04/28/2025

irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

| | |
|----------------|------------|
| Version: | 5.1 |
| Revision Date: | 10/01/2023 |
| Print Date: | 04/28/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.