

To Our Customers:

The attached Safety Data Sheet (SDS) was prepared by the vendor of the product you purchased through one of our divisions. We used the manufacturer's electronic document directly or scanned a paper copy and generated a file for our automated SDS delivery system.

All statements, technical information, and recommendations contained therein are solely that of the manufacturer of the product. We at Zep Inc. did not verify the accuracy and completeness of the statements and do not warrantee or guarantee the information. We provide vendor SDSs to assist our customers in their compliance efforts. The attached document is in compliance with one of the respective country regulatory requirements noted below:

The OSHA Hazard Communication Standard (in the United States) The Hazardous Products Regulations (in Canada)

We made every effort to deliver all of the information prepared by the manufacturer. We cannot anticipate all conditions under which this information will be used. If you have any questions about the statements on the SDS, please contact the company shown on the document.

Zep Inc. assumes no liability or responsibility for loss or damage resulting from the improper use or handling of this product, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the manufacturer's product label and Safety Data Sheet.

Sincerely,

Product Stewardship Team Zep Inc.

SAFETY DATA SHEET

1. Identification

Product identifier B64001 KONK 504 LIVESTOCK RED,400G

Other means of identification

Product code 1000016744

Recommended use coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ACUITY HOLDINGS INC. dba AMREP

Address 11627 178 STREET NW

EDMONTON, AB T5S 1N6

Canada

Telephone General Assistance 1-905 669-9876

E-mail Not available.

Emergency phone number Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated

area. Wear eye protection/face protection.

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isopropyl Alcohol		67-63-0	68.376
Propane		74-98-6	13.78

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	6.22
Acetic acid		64-19-7	1.4
Other components below	reportable levels		10.22404

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Most important symptoms/effects, acute and

Ingestion

symptoms/effects, acute and delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

	40011			
US.	ACGIH	i Ihresh	iold Lin	nit Values

Components	Туре	Value	
Acetic acid (CAS 64-19-7)	STEL	15 ppm	
	TWA	10 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Canada. Alberta OELs (Occupatio	onal Health & Safety Code, Sch	nedule 1, Table 2)	
Components	Туре	Value	
Acetic acid (CAS 64-19-7)	STEL	37 mg/m3	
		15 ppm	
	TWA	25 mg/m3	
		10 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	984 mg/m3	
07-00-07		400 ppm	
	TWA	492 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Canada. British Columbia OELs. (Occupational Exposure Limit	s for Chemical Substances, Occupational	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame	Occupational Exposure Limit	• •	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components	(Occupational Exposure Limit nded)	s for Chemical Substances, Occupational	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components	(Occupational Exposure Limit nded) Type	Value 15 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS	(Occupational Exposure Limitended) Type STEL	s for Chemical Substances, Occupational	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS	(Occupational Exposure Limitended) Type STEL TWA	Value 15 ppm 10 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0)	(Occupational Exposure Limitended) Type STEL TWA STEL TWA STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21)	(Occupational Exposure Limitended) Type STEL TWA STEL TWA STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21) Components	(Occupational Exposure Limitended) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21) Components	(Occupational Exposure Limitended) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21) Components Acetic acid (CAS 64-19-7)	(Occupational Exposure Limitended) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 217 Components Acetic acid (CAS 64-19-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS	(Occupational Exposure Limitended) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm 10 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 217 Components Acetic acid (CAS 64-19-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS	(Occupational Exposure Limits nded) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA STEL TWA STEL STEL STEL TWA STEL STEL TWA STEL	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm 10 ppm 10 ppm 10 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21) Components Acetic acid (CAS 64-19-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control of Canada.)	(Occupational Exposure Limits nded) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm 10 ppm 10 ppm 10 ppm 10 ppm 10 ppm 1000 ppm 400 ppm 200 ppm	Health and
, ,	(Occupational Exposure Limits nded) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm 10 ppm 10 ppm 10 ppm 10 ppm 10 ppm 1000 ppm 400 ppm 200 ppm	Health and
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame Components Acetic acid (CAS 64-19-7) Isopropyl Alcohol (CAS 67-63-0) Canada. Manitoba OELs (Reg. 21) Components Acetic acid (CAS 64-19-7) Isobutane (CAS 75-28-5) Isopropyl Alcohol (CAS 67-63-0) Canada. Ontario OELs. (Control of Canada.)	(Occupational Exposure Limits nded) Type STEL TWA STEL TWA 7/2006, The Workplace Safety Type STEL TWA STEL TWA	Value 15 ppm 10 ppm 400 ppm 200 ppm And Health Act) Value 15 ppm 10 ppm 10 ppm 200 ppm 200 ppm 200 ppm 200 ppm	Health and

Product name: B64001 KONK 504 LIVESTOCK RED,400G

SDS CANADA

Canada. Ontario OELs.	(Control of Ex	posure to Biologica	I or Chemical Agents)

Components	Туре	Value
Isobutane (CAS 75-28-5)	TWA	800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
,	TWA	200 ppm
Canada. Quebec OELs. (Ministry	of Labor - Regulation Respect	ing the Quality of the Work Environment)
Components	Туре	Value
Acetic acid (CAS 64-19-7)	STEL	37 mg/m3
,		15 ppm
	TWA	25 mg/m3
		10 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1230 mg/m3
•		500 ppm
	TWA	983 mg/m3
		400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3

Biological limit values

ACGIH Biological Exposure Indices

Components Value Determinant Specimen Sampling Time
Isopropyl Alcohol (CAS 40 mg/l Acetone Urine * 67-63-0)

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

1000 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point -156.0 °F (-104.4 °C) propellant estimated

SDS CANADA

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.1 % estimated

(%)

Flammability limit - upper

(%)

11.5 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 804.26 °F (429.03 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.727 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components Species Test Results

Acetic acid (CAS 64-19-7)

Acute Oral

LD50 Mouse 4960 mg/kg

Rat 3310 mg/kg

Components **Species Test Results** Isobutane (CAS 75-28-5) **Acute** Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l Isopropyl Alcohol (CAS 67-63-0) **Acute Dermal** LD50 Rabbit 16.4 ml/kg, 24 Hours Inhalation LC50 Rat > 10000 ppm, 6 Hours Oral LD50 Rat 5.84 g/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes

Rat

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Isopropyl Alcohol (CAS 67-63-0)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

2-PROPANOL (CAS 67-63-0) Not classifiable as a human carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

1355 mg/l 658 mg/l/4h

ComponentsSpeciesTest ResultsAcetic acid (CAS 64-19-7)AquaticCrustaceaEC50Daphnia47 mg/L, 48 HoursFishLC50Bluegill (Lepomis macrochirus)75 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Components Species Test Results

Isopropyl Alcohol (CAS 67-63-0)

Aquatic

 Algae
 IC50
 Algae
 1000.0001 mg/L, 72 Hours

 Crustacea
 EC50
 Daphnia
 13299 mg/L, 48 Hours

 Fish
 LC50
 Bluegill (Lepomis macrochirus)
 > 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Acetic acid
 -0.17

 Isobutane
 2.76

 Isopropyl Alcohol
 0.05

 Propane
 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

^{*} Estimates for product may be based on additional component data not shown.

Allowed with restrictions. Cargo aircraft only

IMDG

UN number UN1950 **AEROSOLS UN** proper shipping name Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Packing group

Not applicable.

Environmental hazards

Marine pollutant No. F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code



15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region Inventory name On inventory (yes/no)*

Europe European Inventory of Existing Commercial Chemical No

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Philippines

Philippine Inventory of Chemicals and Chemical Substances

No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 04-28-2017

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names