## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP HI PH 2601 VEHICLE WASH 55GL

Material number : J53385

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

| Appearance | liquid       |
|------------|--------------|
| Colour     | amber, clear |
| Odour      | mild         |

## **GHS Classification**

Skin corrosion : Category 1
Serious eye damage : Category 1
Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

**GHS** label elements

Hazard pictograms :



Health hazard

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or

repeated exposure if inhaled.

Precautionary statements : **Prevention**:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P314 Get medical advice/ attention if you feel unwell. P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

| Chemical name                           | CAS-No.    | Concentration [%] |
|---|------------|-------------------|
| 2-aminoethanol                          | 141-43-5   | >= 10 - < 30      |
| 2-butoxyethanol                         | 111-76-2   | >= 5 - < 10       |
| tetrasodium ethylenediaminetetraacetate | 64-02-8    | >= 5 - < 10       |
| Alcohols, C9-11, ethoxylated            | 68439-46-3 | >= 5 - < 10       |
| sodium xylenesulphonate                 | 1300-72-7  | >= 5 - < 10       |
| Sodium metasilicate (disodium salt)     | 6834-92-0  | >= 1 - < 5        |
| sodium dodecylbenzenesulfonate          | 25155-30-0 | >= 1 - < 5        |

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

If on skin, rinse well with water. If on clothes, remove clothes.

Wash contaminated clothing before re-use.

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

> Alcohol-resistant foam Carbon dioxide (CO2)

Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Sulphur oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid exposure - obtain special instructions before use.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

No smoking.

Materials to avoid : Oxidizing agents

Do not store near acids.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

| Components     | CAS-No.  | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|----------------|----------|-------------------------------------|--|-----------|
| 2-aminoethanol | 141-43-5 | TWA                                 | 3 ppm  | ACGIH     |
|                |          | STEL                                | 6 ppm  | ACGIH     |
|                |          | TWA                                 | 3 ppm  | NIOSH REL |

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

|                 |          |      | 8 mg/m3             |           |
|-----------------|----------|------|---------------------|-----------|
|                 |          | ST   | 6 ppm<br>15 mg/m3   | NIOSH REL |
|                 |          | TWA  | 3 ppm<br>6 mg/m3    | OSHA Z-1  |
|                 |          | STEL | 6 ppm<br>15 mg/m3   | OSHA P0   |
|                 |          | TWA  | 3 ppm<br>8 mg/m3    | OSHA P0   |
|                 |          | PEL  | 3 ppm<br>8 mg/m3    | CAL PEL   |
|                 |          | STEL | 6 ppm<br>15 mg/m3   | CAL PEL   |
| 2-butoxyethanol | 111-76-2 | TWA  | 20 ppm              | ACGIH     |
|                 |          | TWA  | 5 ppm<br>24 mg/m3   | NIOSH REL |
|                 |          | TWA  | 50 ppm<br>240 mg/m3 | OSHA Z-1  |
|                 |          | TWA  | 25 ppm<br>120 mg/m3 | OSHA P0   |
|                 |          | PEL  | 20 ppm<br>97 mg/m3  | CAL PEL   |

#### **Biological occupational exposure limits**

| Component       | CAS-No.  | Control      | Biological | Sampling  | Permissible   | Basis     |
|-----------------|----------|--------------|------------|-----------|---------------|-----------|
|                 |          | parameters   | specimen   | time      | concentration |           |
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic | Urine      | End of    | 200.mg/g      | ACGIH BEI |
|                 |          | acid (BAA)   |            | shift (As | Creatinine    |           |
|                 |          |              |            | soon as   |               |           |
|                 |          |              |            | possible  |               |           |
|                 |          |              |            | after     |               |           |
|                 |          |              |            | exposure  |               |           |
|                 |          |              |            | ceases)   |               |           |

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Rubber gloves

Neoprene gloves Nitrile rubber

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Face-shield

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber, clear

Odour : mild

Odour Threshold : No data available

pH : 13 - 14

Melting point/freezing point : No data available

Boiling point : 100 °C Flash point : 93.3 °C

Method: closed cup

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1.090 g/cm3

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 12.1 mm2/s (20.0 °C)

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Acids

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke). Nitrogen oxides (NOx)

Sulphur oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : 2,276 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 49.67 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 4,901 mg/kg

Method: Calculation method

**Components:** 

2-aminoethanol:

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

Sodium metasilicate (disodium salt):

Acute oral toxicity : LD50 Rat: 1,153 mg/kg

sodium dodecylbenzenesulfonate:

Acute oral toxicity : LD50 Oral Rat: 438 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

**Product:** 

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

#### STOT - repeated exposure

#### **Components:**

#### tetrasodium ethylenediaminetetraacetate:

Exposure routes: Inhalation

Assessment: May cause damage to organs through prolonged or repeated exposure.

## **Aspiration toxicity**

No data available

#### **Further information**

#### **Product:**

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

#### **Product:**

Partition coefficient: n-

: Remarks: No data available

octanol/water <u>Components:</u> **2-aminoethanol**:

Partition coefficient: n-

: log Pow: -1.31

octanol/water

## Mobility in soil

No data available

#### Other adverse effects

No data available

## **ZEP HI PH 2601 VEHICLE WASH 55GL**

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GÓODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

| Components                     | CAS-No.    | Component RQ (lbs) | Calculated product RQ (lbs) |
|--------------------------------|------------|--------------------|-----------------------------|
| sodium dodecylbenzenesulfonate | 25155-30-0 | 1000               | *                           |

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-butoxyethanol 111-76-2 7.8791 %

## California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, ethylbenzene, which is/are known to the State of California to cause cancer. For more

information go to www.P65Warnings.ca.gov.

#### The components of this product are reported in the following inventories:

All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

Print Date 04/28/2025 Revision Date 10/01/2023

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:

| HEALTH          | 3 |
|-----------------|---|
| FLAMMABILITY    | 1 |
| INSTABILITY     | 0 |
| SPECIAL HAZARD. |   |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

| HEALTH          | 3* |
|-----------------|----|
| FLAMMABILITY    | 1  |
| PHYSICAL HAZARD | 0  |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms

Signal word





Danger:

Hazard statements Causes severe skin burns and eye damage. May cause damage to organs through

prolonged or repeated exposure if inhaled.

Precautionary statements Prevention: Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin

thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or

# SAFETY DATA SHEET ZEP HI PH 2601 VEHICLE WASH 55GL

Version 5.1 Revision Date 10/01/2023 Print Date 04/28/2025

hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Get medical advice/ attention if you feel unwell. Wash contaminated clothing before reuse.

**Disposal:** Dispose of contents/container in accordance with local regulation.

| Version:       | 5.1        |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date:    | 04/28/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.