

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP BRAKE FLUSH (VOC)_55GL

Material number : L93585

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	colourless
Odour	hydrocarbon-like

GHS Classification

Flammable liquids : Category 2
Eye irritation : Category 2A
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P235 Keep cool.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 80 - <= 100
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

	Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. Wash off with soap and water. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes. Wash contaminated clothing before re-use.
In case of eye contact	: If in eyes, rinse with water for 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are dependent on exposure (dose, concentration, contact time). Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. May cause drowsiness or dizziness. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm 1,200 mg/m3	CA AB OEL
		STEL	750 ppm 1,800 mg/m3	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m3	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m3	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Personal protective equipment

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection	
Material	: Protective gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: colourless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: 55.5 °C
Flash point	: < -18 °C
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.77 g/cm3
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Auto-ignition temperature : not determined
Thermal decomposition : No data available
Viscosity
Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Vapours may form explosive mixture with air.
Conditions to avoid : Heat, flames and sparks.
Extremes of temperature and direct sunlight.
Incompatible materials : Oxidizing agents
Strong acids
Alkaline materials
Hazardous decomposition products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration, contact time).
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
May cause drowsiness or dizziness.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity: IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.
The GHS H401 statement "Toxic to aquatic life" noted above is an Acute Aquatic Toxicity Category 2 classification. Although the product has the potential to harm the environment, it is not classified as a marine pollutant or regulated under transportation regulations.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, HEPTANE), 3, II

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):
UN1993, FLAMMABLE LIQUID, N.O.S., (ACETONE, HEPTANE), 3, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):
UN1993, Flammable liquid, n.o.s., (ACETONE, HEPTANE), 3, II

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):
UN1993, Flammable liquid, n.o.s., (ACETONE, HEPTANE), 3, II

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):
UN1993, Flammable liquids, n.o.s., (ACETONE, HEPTANE), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

SAFETY DATA SHEET

ZEP BRAKE FLUSH (VOC)_55GL

Version 2.0

Revision Date 12/15/2023

Print Date 04/28/2025

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms

:



Flame



Exclamation mark

Signal word

: **Danger:**

Hazard statements

: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

:

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	12/15/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.