# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT Material name

Material number 00000000001047933

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Compliance Services - 877-428-9937 Telephone

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. **Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

| Appearance | Aerosol containing a liquefied gas |
|------------|------------------------------------|
| Colour     | opaque, light brown                |
| Odour      | solvent-like                       |

### **GHS Classification**

Flammable aerosols : Category 1 : Liquefied gas Gases under pressure Aspiration hazard Category 1

**GHS** label elements

Hazard pictograms





Gas cylinder



Danger

Signal word

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

| Chemical name  | CAS-No.    | Concentration [%] |
|--|------------|-------------------|
| Distillates (petroleum), hydrotreated light            | 64742-47-8 | >= 70 - < 90      |
| propane  | 74-98-6    | >= 5 - < 10       |
| Solvent naphtha (petroleum), heavy aliph.              | 64742-96-7 | >= 5 - < 10       |
| butane   | 106-97-8   | >= 5 - < 10       |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | >= 1 - < 3        |

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended. Get medical attention immediately.

If inhaled : If inhaled, remove to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : Remove contaminated clothing and shoes.

Wash contaminated clothing before reuse. Wash off immediately with plenty of water. If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids.

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person. DO NOT induce vomiting unless directed to do so by a

physician or poison control center. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

Further information

methods

: Cool containers/tanks with water spray.

: For safety reasons in case of fire, cans should be stored separately in closed containments.

Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Components with workplace control parameters

| Components                                  | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---|------------|-------------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA                                 | 500 ppm<br>2,000 mg/m3                         | OSHA Z-1  |
|   |            | TWA                                 | 400 ppm<br>1,600 mg/m3                         | OSHA P0   |
|   |            | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1  |
|   |            | TWA (Mist)                          | 5 mg/m3  | OSHA P0   |
|   |            | TWA (Mist)                          | 5 mg/m3  | NIOSH REL |
|   |            | ST (Mist)                           | 10 mg/m3                                       | NIOSH REL |
|   |            | PEL (particulate)                   | 5 mg/m3  | CAL PEL   |
| propane                                     | 74-98-6    | TWA                                 | 1,000 ppm                                      | NIOSH REL |

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

|  |            |                                | 1,800 mg/m3              |           |
|--|------------|--------------------------------|--------------------------|-----------|
|  |            | TWA                            | 1,000 ppm<br>1,800 mg/m3 | OSHA Z-1  |
|  |            | TWA                            | 1,000 ppm<br>1,800 mg/m3 | OSHA P0   |
|  |            | PEL                            | 1,000 ppm<br>1,800 mg/m3 | CAL PEL   |
| butane   | 106-97-8   | TWA                            | 800 ppm<br>1,900 mg/m3   | NIOSH REL |
|  |            | TWA                            | 800 ppm<br>1,900 mg/m3   | OSHA P0   |
|  |            | PEL                            | 800 ppm<br>1,900 mg/m3   | CAL PEL   |
|  |            | STEL                           | 1,000 ppm                | ACGIH     |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist)                     | 5 mg/m3                  | OSHA Z-1  |
|  |            | TWA<br>(Inhalable<br>fraction) | 5 mg/m3                  | ACGIH     |

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles

with pure water.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : opaque, light brown

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

Odour : solvent-like

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : No data available Boiling point : No data available

Flash point :

Not applicable

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.810 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 47.28 kJ/g

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Aspiration may cause pulmonary oedema and pneumonitis.

Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **Acute toxicity**

**Product:** 

Acute dermal toxicity : Acute toxicity estimate : 3,465 mg/kg

Method: Calculation method

## **Components:**

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

#### Skin corrosion/irritation

### **Product:**

Remarks: May irritate skin.

### Serious eye damage/eye irritation

### **Product:**

Remarks: May irritate eyes.

### Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

# Reproductive toxicity

No data available

### STOT - single exposure

No data available

# STOT - repeated exposure

No data available

# **Aspiration toxicity**

### **Product:**

May be fatal if swallowed and enters airways.

#### **Further information**

## **Product:**

Remarks: Solvents may degrease the skin.

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

No data available

### Persistence and degradability

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water
Components:
butane:

: Remarks: No data available

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Gases under pressure Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

#### The components of this product are reported in the following inventories:

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Revision Date 10/01/2023 Print Date 04/27/2025

DSL All components of this product are on the Canadian DSL

**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

# **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:

| HEALTH          | 3 |
|-----------------|---|
| FLAMMABILITY    | 4 |
| INSTABILITY     | 0 |
| SPECIAL HAZARD. |   |

<sup>0 =</sup> not significant, 1 = Slight,

#### HMIS III:

| HEALTH          | 3 |
|-----------------|---|
| FLAMMABILITY    | 4 |
| PHYSICAL HAZARD | 1 |

<sup>0 =</sup> not significant, 1 = Slight,

### **OSHA - GHS Label Information:**

<sup>2 =</sup> Moderate, 3 = High

<sup>4 =</sup> Extreme

<sup>2 =</sup> Moderate, 3 = High 4 = Extreme, \* = Chronic

# **ZEP PENETRATING LUBRICANT SPRAY 16N12 12CT**

Version 3.2 Revision Date 10/01/2023 Print Date 04/27/2025

Hazard pictograms







Flores

Gas cylinder

Health hazar

Signal word : Danger:

Hazard statements : Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Precautionary statements :

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

 $\textbf{Response:} \ \mathsf{IF} \ \mathsf{SWALLOWED:} \ \mathsf{Immediately} \ \mathsf{call} \ \mathsf{a} \ \mathsf{POISON} \ \mathsf{CENTER/doctor.} \ \mathsf{Do} \ \mathsf{NOT}$ 

induce vomiting.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

°F.

Disposal: Dispose of contents/container in accordance with local regulation.

| Version:       | 3.2        |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date:    | 04/27/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.