# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP VINYL CLEANER 20N18 12CT

Material number : 00000000000023401

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

# **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas	
Colour	clear, colourless	
Odour	pleasant	

#### **GHS Classification**

Gases under pressure : Liquefied gas

**GHS** label elements

Hazard pictograms :

Gas cylinder

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Storage:** 

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2-butoxyethanol	111-76-2	>= 3 - < 5
butane	106-97-8	>= 3 - < 5
ethanol	64-17-5	>= 3 - < 5
propane	74-98-6	>= 1 - < 3
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Get medical attention if symptoms occur.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 5 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.
 Evacuate personnel to safe areas.
 Ensure adequate ventilation.
 Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

application area.

Dispose of rinse water in accordance with local and national

regulations.

Provide sufficient air exchange and/or exhaust in work rooms.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

No smoking.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm	NIOSH REL
			24 mg/m3	
		TWA	50 ppm	OSHA Z-1
			240 mg/m3	
		TWA	25 ppm	OSHA P0
			120 mg/m3	
		PEL	20 ppm	CAL PEL
			97 mg/m3	
butane	106-97-8	TWA	800 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	800 ppm	OSHA P0
			1,900 mg/m3	
		PEL	800 ppm	CAL PEL
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA P0
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm	CAL PEL
			1,900 mg/m3	
propane	74-98-6	TWA	1,000 ppm	NIOSH REL
			1,800 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			1,800 mg/m3	

# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

TWA	1,000 ppm 1,800 mg/m3	OSHA P0
PEL	1,000 ppm 1,800 mg/m3	CAL PEL

#### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI
		acid (BAA)		shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles

include: eye wash stations or showers, or eye wash bottles

with pure water.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : clear, colourless

Odour : pleasant

Odour Threshold : No data available pH : Not applicable

# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Melting point/freezing point : No data available

Boiling point : 101.11 °C

Flash point

Not applicable

Evaporation rate : '

n-Butyl Acetate = 1.0

Flammability (solid, gas,

liquid)

: The product is not flammable.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 1 g/cm3

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

: Carbon oxides

products

Nitrogen oxides (NOx)

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

sodium nitrite 7632-00-0

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2-butoxyethanol 111-76-2

ethanol 64-17-5

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 32.19 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h

# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Test atmosphere: vapour

#### Skin corrosion/irritation

#### **Product:**

Remarks: May irritate skin.

#### Serious eye damage/eye irritation

#### **Product:**

Remarks: May irritate eyes.

# Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

# STOT - single exposure

No data available

### STOT - repeated exposure

No data available

#### **Aspiration toxicity**

No data available

## **Further information**

#### **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

No data available

# Persistence and degradability

No data available

# **Bioaccumulative potential**

## **Product:**

# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Partition coefficient: n-

octanol/water **Components:** 

: Remarks: No data available

butane :

Partition coefficient: n-

octanol/water

: Pow: 2.89

ethanol:
Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available **Product:** 

Fioduct.

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: Not applicable

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

# **ZEP VINYL CLEANER 20N18 12CT**

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

sodium nitrite 7632-00-0

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-butoxyethanol 111-76-2 4.6598 %

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

# **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:

HEALTH	1
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

<sup>0 =</sup> not significant, 1 = Slight,

#### HMIS III:

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

<sup>2 =</sup> Moderate, 3 = High

<sup>4 =</sup> Extreme

# SAFETY DATA SHEET ZEP VINYL CLEANER 20N18 12CT

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Hazard pictograms

Gas cylinder

Signal word : Warning:

Hazard statements : Contains gas under pressure; may explode if heated.

Precautionary statements

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

°F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.