SAFETY DATA SHEET ZEP DYNA 143 20GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP DYNA 143 20GL

Material number : 00000000000036650

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | liquid |
|------------|----------------------|
| Colour | colourless |
| Odour | solvent-like, slight |

GHS Classification

Flammable liquids : Category 4
Aspiration hazard : Category 1

GHS label elements

Signal word

Hazard pictograms :

Health hazard

Health hazar
: Danger

Hazard statements : H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---|------------|-------------------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | >= 90 - <= 100 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician. Remove contact lenses. Protect unharmed eve.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

and effects, both acute and delayed

: Aspiration may cause pulmonary oedema and pneumonitis.

Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects may be delayed, symptoms may include minor eye or

skin irritation.

May be fatal if swallowed and enters airways.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical Dry sand

Unsuitable extinguishing

media

: High volume water jet

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|------------|-------------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA | 500 ppm 2,000 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |
| | | PEL (particulate) | 5 mg/m3 | CAL PEL |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : solvent-like, slight
Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : No data available
Boiling point : 192 - 211 °C

Flash point : 61.66 °C

Method: Pensky-Martens closed cup

Evaporation rate : 0.14

n-Butyl Acetate = 1.0

Upper explosion limit : 7.0 %(V)

Lower explosion limit : 0.7 %(V)

Vapour pressure : 0.43 hPa (20 °C)

Relative vapour density : No data available

Density : 0.79 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET ZEP DYNA 143 20GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Aspiration may cause pulmonary oedema and pneumonitis.

Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects may be delayed, symptoms may include minor eye or

skin irritation.

May be fatal if swallowed and enters airways. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

SAFETY DATA SHEET

ZEP DYNA 143 20GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

SAFETY DATA SHEET

ZEP DYNA 143 20GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

| HEALTH | 1 |
|-----------------|---|
| FLAMMABILITY | 2 |
| INSTABILITY | 0 |
| SPECIAL HAZARD. | |

^{0 =} not significant, 1 = Slight,

HMIS III:

| HEALTH | 1 |
|-----------------|---|
| FLAMMABILITY | 2 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word Hazard statements Precautionary statements

: Combustible liquid. May be fatal if swallowed and enters airways.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/ eye protection/ face protection. **Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT

10/11

^{2 =} Moderate, 3 = High

^{4 =} Extreme

SAFETY DATA SHEET ZEP DYNA 143 20GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

| Version: | 3.1 |
|----------------|------------|
| Revision Date: | 10/01/2023 |
| Print Date: | 04/27/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.