MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY ANTI-SEIZE COMPOUND

Material number : 00000000001003267

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	gel
Colour	silver, metallic
Odour	oily

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 10 - < 20
graphite	7782-42-5	>= 5 - < 10

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

aluminium	7429-90-5	>= 3 - < 5
Silicon, amorphous	112945-52-5	>= 3 - < 5
Distillates (petroleum), hydrotreated light	64742-47-8	>= 1 - < 3
quartz (SiO2)	14808-60-7	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : If in eyes, rinse with water for 15 minutes.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Carbon dioxide (CO2) Alcohol-resistant foam

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling Do not breathe vapours or spray mist.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Observe label precautions.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
graphite	7782-42-5	TWA (Respirable)	2.5 mg/m3	NIOSH REL
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
aluminium	7429-90-5	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable fraction)	1 mg/m3	ACGIH
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2	OSHA Z-3
		TWA	6 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
quartz (SiO2)	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : gel

Colour : silver, metallic

Odour : oily

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : No data available Boiling point : No data available

Flash point : 204.44 °C

Evaporation rate : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : 12(Air = 1.0)

Density : 0.8 g/cm3

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : > 1000 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes serious eye irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

quartz (SiO2) 14808-60-7

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

aluminium:

Acute oral toxicity : LD50 Rat: > 15,900 mg/kg

Acute inhalation toxicity : LC50 Rat: > 0.888 mg/l

Exposure time: 4 h

Silicon, amorphous:

Acute oral toxicity : LD50 Oral Rat: 3,160 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Product:

Carcinogenicity -Assessment

: Not classifiable as a human carcinogen., Not classified due to product form (liquid) and classification route of entry (inhaled powder).

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

octanol/water

Partition coefficient: n- : Remarks: No data available

Mobility in soil

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Phosphoric acid, trisodium salt, dodecahydrate	10101-89-0	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including Cadmium, lead, sodium 2-biphenylate, which is/are known to the State of California to cause cancer, and Cadmium, lead, methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

DSL All components of this product are on the Canadian DSL

Not On TSCA Inventory **TSCA**

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	1
FLAMMABILITY	1
INSTABILITY	0

^{0 =} not significant, 1 =Slight,

HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0

^{0 =} not significant, 1 = Slight,

OSHA - GHS Label Information:

Not a hazardous substance or mixture.

Version:	2.0

^{2 =} Moderate, 3 = High

^{4 =} Extreme

^{2 =} Moderate, 3 = High 4 = Extreme, * = Chronic

SAFETY DATA SHEET MISTY ANTI-SEIZE COMPOUND

Version 2.0 Revision Date 07/02/2024 Print Date 04/27/2025

Revision Date:	07/02/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.