Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP SLIDE_5GL

Material number : 00000000000086935

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid	
Colour	clear, colourless, light yellow	
Odour	slight, hydrocarbon-like	

GHS Classification

Flammable liquids : Category 3
Skin irritation : Category 2
Eye irritation : Category 2A

Specific target organ toxicity -

single exposure

: Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms







Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary statements : **Prevention**:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

and keep comfortable for breatning. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Naphtha (petroleum), heavy alkylate	64741-65-7	>= 30 - < 60
Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 60

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

> Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

> for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

: Effects are dependent on exposure (dose, concentration,

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat.

Aspiration may cause pulmonary oedema and pneumonitis.

Causes serious eye irritation.

Causes skin irritation.

May cause respiratory irritation.

May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing : High volume water jet

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

media

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Silicon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline

materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless, light yellow

Odour : slight, hydrocarbon-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point : $179.44 \,^{\circ}\text{C}$ Flash point : $55.6 \,^{\circ}\text{C}$

Method: closed cup

Evaporation rate : < 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.781 g/cm3

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : Not applicable

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available
Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : 13.7 mm2/s (20 °C) Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat.

Aspiration may cause pulmonary oedema and pneumonitis.

Causes serious eye irritation.

Causes skin irritation.

May cause respiratory irritation.

May be fatal if swallowed and enters airways. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 3,643 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,775 mg/kg

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Method: Calculation method

Components:

Naphtha (petroleum), heavy alkylate:

Acute oral toxicity : LD50 Oral Rat: > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal Rat: > 2,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1993, Flammable liquid, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms







Signal word : Danger:

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Hazard statements

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Precautionary statements

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.