# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT

**DEGREASER** 

Material number 000000000001041563

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	liquid
Colour	clear, amber, brown
Odour	solvent-like

#### **GHS Classification**

Flammable liquids : Category 3 Skin irritation : Category 2 Serious eye damage : Category 1 Carcinogenicity : Category 2

Specific target organ toxicity -

: Category 3 (Respiratory system, Central nervous system)

single exposure

Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms









Corrosion Health hazard

Signal word : Danger

H226 Flammable liquid and vapour. Hazard statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

#### Precautionary statements

#### : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P235 Keep cool.

#### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
1,2,4-trimethylbenzene	95-63-6	>= 10 - < 20
Kerosine (petroleum), hydrodesulfurized	64742-81-0	>= 10 - < 20
Aromatic Hydrocarbons (C9 - C10)	Not Available	>= 10 - < 20
Alcohols, C12-16, ethoxylated	68551-12-2	>= 5 - < 10
oleic acid	112-80-1	>= 5 - < 10
3-ethyltoluene	620-14-4	>= 5 - < 10
Alcohols, C9-11, ethoxylated	68439-46-3	>= 5 - < 10
mesitylene	108-67-8	>= 3 - < 5
4-ethyltoluene	622-96-8	>= 3 - < 5
1,2,3-trimethylbenzene	526-73-8	>= 1 - < 3
propylbenzene	103-65-1	>= 1 - < 3
2-ethyltoluene	611-14-3	>= 1 - < 3
xylenes	1330-20-7	>= 1 - < 3
cumene	98-82-8	>= 0.1 - < 1
ethylbenzene	100-41-4	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

Keep eye wide open while rinsing.

If swallowed : Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

: Effects are dependent on exposure (dose, concentration,

contact time).

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

delayed Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline

materials.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
mesitylene	108-67-8	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
		PEL	25 ppm 125 mg/m3	CAL PEL
1,2,3-trimethylbenzene	526-73-8	TWA	25 ppm 125 mg/m3	NIOSH REL
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm	CAL PEL

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

			655 mg/m3	
		С	300 ppm	CAL PEL
		PEL	100 ppm 435 mg/m3	CAL PEL
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL

#### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
ETHYLBENZENE	100-41-4	Sum of mandelic acid and phenyl glyoxylic	Urine	End of shift (As soon as possible after	0.15.g/g creatinine	ACGIH BEI
		acid		exposure ceases)		
ETHYLBENZENE		Ethylbenzen e	In end- exhaled air	Not critical		ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : clear, amber, brown

Odour : solvent-like

Odour Threshold : No data available pH : Not applicable Melting point/freezing point : No data available

Boiling point : 154.44 °C Flash point : 45.0 °C

Method: closed cup

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : not determined
Relative vapour density : No data available
Density : 0.882 g/cm3

Solubility(ies)

Water solubility : emulsifiable

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : 6.3 mm2/s (20 °C)

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Symptoms of Overexposure

Aggravated Medical

Condition

: None known.

: Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

cumene 98-82-8 ethylbenzene 100-41-4

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

cumene 98-82-8

**Acute toxicity** 

**Product:** 

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 56.19 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

#### Components:

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

#### Skin corrosion/irritation

#### **Product:**

Remarks: Irritating to skin.

#### **Components:**

oleic acid:

Species: human skin Exposure time: 72 h Result: Mild skin irritation

### Serious eye damage/eye irritation

#### **Product:**

Remarks: May cause irreversible eye damage.

#### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

### Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **Aspiration toxicity**

No data available

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **Further information**

#### **Product:**

Remarks: Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

Components: xylenes:

Partition coefficient: n-

octanol/water ethylbenzene:

Partition coefficient: n-

octanol/water

: Pow: 3.12

: Pow: 3.6

#### Mobility in soil

No data available

#### Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: No data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: Not applicable

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (ALIPHATIC PETROLEUM NAPHTHA), 3, III

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

# ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

 1,2,4-trimethylbenzene
 95-63-6
 18.1465 %

 ethylbenzene
 100-41-4
 0.3085 %

California Prop. 65



WARNING: This product can expose you to chemicals including cumene, ethylbenzene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other

reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

**DSL** This product contains one or more components that are listed on the

Canadian NDSL. All other components are on the Canadian DSL.

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:** 

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **Further information**

#### NFPA:

HEALTH	3
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Health hazard





Signal word

Hazard statements

Danger:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

# SAFETY DATA SHEET ZEP PROFESSIONAL SELF-EMULSIFYING SOLVENT DEGREASER

Version 5.1 Revision Date 10/01/2023 Print Date 04/27/2025

water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Keep cool. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	5.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.