Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP TWISTER! ULTRA 20N15 12CT

Material number 000000000000652101

# Manufacturer or supplier's details

Company : Zep Inc.

Address 11627 - 178 Street

Edmonton, Alberta T5S 1N6

Canada

Telephone Compliance Services - 877-428-9937

# **Emergency telephone numbers**

For SDS Information Compliance Services - 877-428-9937

For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded

For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** 

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	Aerosol containing a liquefied gas		
Colour	light brown		
Odour	solvent-like		

### **GHS Classification**

Flammable aerosols : Category 2 Gases under pressure : Liquefied gas

**GHS** label elements

Hazard pictograms



Gas cylinder

Signal word Warning

Hazard statements : H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

Flame

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

Precautionary statements : **Prevention**:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use. Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 80 - <= 100
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 1 - < 5

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended. Get medical attention if symptoms occur.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

Sweep up or vacuum up spillage and collect in suitable container for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use. Provide sufficient air exchange and/or exhaust in work rooms.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

No smoking.

Keep in a dry, cool and well-ventilated place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm	CA QC OEL

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water. Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : light brown
Odour : solvent-like

Odour Threshold : No data available
pH : Not applicable
Melting point/freezing point : Not applicable
Boiling point : Not applicable

Flash point

Not applicable

Evaporation rate : No data available Flammability (solid, gas, : Flammable aerosol.

liquid)

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Density : 0.791 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : not determined

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

# **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

# Carcinogenicity:

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

## **Acute toxicity**

**Product:** 

Acute dermal toxicity : Acute toxicity estimate : 3,115 mg/kg

Method: Calculation method

**Components:** 

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

**Distillates (petroleum), hydrotreated heavy naphthenic:**Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

## Skin corrosion/irritation

**Product:** 

Remarks: May irritate skin.

## Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

# Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

**Further information** 

**Product:** 

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n- : Remarks: No data available

octanol/water Components:

butane:

Partition coefficient: n-

: Pow: 2.89

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological : No data available

information

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

Version 2.0 Revision Date 02/18/2024 Print Date 04/27/2025

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

### **SECTION 16. OTHER INFORMATION**

## WHMIS - GHS Label Information:

Hazard pictograms :



Flame

Signal word : Warning:

Hazard statements : Flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statements :

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50  $^{\circ}$ C/ 122

°F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	02/18/2024
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.