# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

000000000505202000 Material number

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information Compliance Services - 877-428-9937

For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Colour	light yellow
Odour	aromatic, hydrocarbon-like

## **GHS Classification**

Flammable liquids : Category 4 : Category 1 Skin sensitisation Serious eye damage/eye : Category 1

irritation

Skin irritation : Category 2 Acute toxicity : Category 5 Carcinogenicity : Category 2

Specific target organ toxicity -: Category 2 (Eyes, Blood, Liver)

repeated exposure

Specific target organ toxicity -

single exposure

: Category 1 (Blood, Eyes, respiratory tract irritation)

Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms







mark

Signal word : Warning Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Hazard statements : H227 Combustible liquid.

H315 Causes skin irritation.

H318 Causes serious eye damage. H351 Suspected of causing cancer. H371 May cause damage to organs. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or

repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

## Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician. P331 Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

## Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

#### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
Alcohols, C12-14-secondary, ethoxylated	84133-50-6	>= 30 - < 50
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 5 - < 10

# BJ1178 AISIN EFI TANK ADDITIVE 6.76 FL OZ 12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10
trimethylbenzene	25551-13-7	>= 1 - < 3
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 3
naphthalene	91-20-3	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice

Consult a physician after significant exposure.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways.

Suspected of causing cancer.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing : High volume water jet

## BJ1178 AISIN EFI TANK ADDITIVE 6.76 FL OZ 12CS

Revision Date 10/01/2023 Print Date 04/27/2025

media

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Nitrogen oxides (NOx)

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Environmental precautions** 

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

> Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours or spray mist.

Dispose of rinse water in accordance with local and national

# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
trimethylbenzene	25551-13-7	TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
		PEL	25 ppm 125 mg/m3	CAL PEL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
		PEL	0.1 ppm 0.5 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Safety glasses

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : light yellow

Odour : aromatic, hydrocarbon-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point :  $> 180 \, ^{\circ}\text{C}$ Flash point :  $79 \, ^{\circ}\text{C}$ 

Upper explosion limit : 7 %(V)

Lower explosion limit : 0.6 %(V)

Vapour pressure : No data available

Density : 0.938 g/cm3 (15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : > 400 °C

Viscosity

Viscosity, kinematic : 18.5 mm2/s (40 °C)

## BJ1178 AISIN EFI TANK ADDITIVE 6.76 FL OZ 12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon dioxide (CO2) Carbon monoxide

Amines Hydrocarbons

Smoke

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and

irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways.

Suspected of causing cancer.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

naphthalene 91-20-3

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

naphthalene 91-20-3

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

naphthalene 91-20-3

## **Acute toxicity**

## **Product:**

Acute oral toxicity : Acute toxicity estimate : 4,292 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

## **Components:**

Alcohols, C12-14-secondary, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: > 3,000 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

## Skin corrosion/irritation

## **Product:**

Remarks: May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

## Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

## **Aspiration toxicity**

# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

## **Further information**

## **Product:**

Remarks: Solvents may degrease the skin.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

**Product:** 

Partition coefficient: n- : Remarks: No data available

octanol/water **Components**:

Solvent naphtha (petroleum), heavy arom. : Partition coefficient: n- : log Pow: 4.2

octanol/water

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n- : Pow: 1

octanol/water

## Mobility in soil

No data available

## Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

# BJ1178 AISIN EFI TANK ADDITIVE 6.76 FL OZ 12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (POLYETHER

AMINE), 9, III, MP: (SOLVENT NAPHTHA, PETROLEUM, HEAVY AROM. (RH))

Transportation Regulation: IATA (Cargo Air):

UN3082, Environmentally hazardous substance, liquid, n.o.s., (POLYETHER AMINE), 9, III

Transportation Regulation: IATA (Passenger Air):

UN3082, Environmentally hazardous substance, liquid, n.o.s., (POLYETHER AMINE), 9, III

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

naphthalene 91-20-3

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

# BJ1178 AISIN EFI TANK ADDITIVE 6.76 FL OZ 12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
naphthalene	91-20-3	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol 112-34-5 6 % 1,2,4-trimethylbenzene 95-63-6 1.55 % naphthalene 91-20-3 1.05 %

## California Prop. 65



WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to

www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

# BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **Further information**

#### NFPA:

HEALTH	3
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Health hazard



Exclamation mark



Corrosion

Signal word Hazard statements Warning:

Combustible liquid. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

**Response:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get

# SAFETY DATA SHEET BJ1178 AISIN EFI TANK ADDITIVE\_6.76 FL OZ\_12CS

Version 1.1 Revision Date 10/01/2023 Print Date 04/27/2025

medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.