ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Material number : 00000000000688485

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear
Odour	solvent-like

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A

Specific target organ toxicity -

single exposure

: Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Health hazard



He

Exclamat

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Precautionary statements

: Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P235 Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
heptane	142-82-5	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Wash off immediately with plenty of water for at least 15

minutes.

Take off all contaminated clothing immediately.

If skin irritation persists, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration,

contact time).

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing : High volume water jet

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

media

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		С	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		PEL	400 ppm 1,600 mg/m3	CAL PEL
		STEL	500 ppm 2,000 mg/m3	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As	_	

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

	soon as	
	possible	
	after	
	exposure	
	ceases)	

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : solvent-like

Odour Threshold : No data available pH : No data available Melting point/freezing point : No data available

Boiling point : 73 - 76 °C

Flash point : -17.8 °C

Method: TCC

Evaporation rate : 2.5

Upper explosion limit : No data available Lower explosion limit : No data available

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Vapour pressure : 162.65 hPa (15.5 °C)

Relative vapour density : No data available

Density : 0.75 g/cm3

Solubility(ies)

Water solubility : No data available Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness,

paralysis, and convulsions.

Aspiration may cause pulmonary oedema and pneumonitis. Effects are dependent on exposure (dose, concentration,

contact time).

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

heptane:

Acute inhalation toxicity : LC50 Rat: 103 mg/l

Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

: Remarks: No data available

octanol/water Components:
heptane:

Partition coefficient: n-

: log Pow: 5

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (HEPTANE, ACETONE), 3, II

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ACETONE), 3, II

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (HEPTANE, ACETONE), 3, II

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (HEPTANE, ACETONE), 3, II

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (HEPTANE, ACETONE), 3, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

Print Date 04/27/2025 Version 3.1 Revision Date 10/01/2023

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	2
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Health hazard



mark

Signal word

Hazard statements Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and

SAFETY DATA SHEET ZEP BRAKE FLUSH (LOCK & KEY) 53GL

Version 3.1 Revision Date 10/01/2023 Print Date 04/27/2025

receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Keep cool. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.