# **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP RP#3 BRICK LUBRICANT

Material number : 00000000000429585

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

**Emergency telephone numbers** 

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

**Emergency** In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

#### **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Colour	tan
Odour	mild

## **GHS Classification**

Serious eye damage : Category 1
Carcinogenicity : Category 2
Specific target organ toxicity - : Category 2

repeated exposure (Oral)

**GHS** label elements

Hazard pictograms



Health hazard

Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure if swallowed.

Precautionary statements : **Prevention**:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention. **Disposal:** 

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
2,2'-iminodiethanol	111-42-2	>= 3 - < 5
Amides, coco, N,N-bis(hydroxyethyl)	68603-42-9	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Take off contaminated clothing and shoes immediately. Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Causes serious eye damage. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

Water

Carbon dioxide (CO2)

Foam

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Nitrogen oxides (NOx)

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not freeze.

Do not store near acids.

Oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2'-iminodiethanol	111-42-2	TWA (Inhalable fraction and vapor)	1 mg/m3	ACGIH
		TWA	3 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm	OSHA P0

# **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

		15 mg/m3	
	PEL	0.46 ppm	CAL PEL
		2 mg/m3	

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : tan
Odour : mild

Odour Threshold : No data available

pH : 9.2 - 10.2

Melting point/freezing point : No data available

Boiling point : 100 °C

Flash point :

Not applicable

Evaporation rate : 1

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapour pressure : No data available

# **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Relative vapour density : No data available

Density : 1.01 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: Nitrogen oxides (NOx)

Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling,

respiratory issues, and general pain.

Causes serious eye damage. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

# **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

exposure.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

2,2'-iminodiethanol 111-42-2 Amides, coco, N,N- 68603-42-9

bis(hydroxyethyl)

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

2,2'-iminodiethanol 111-42-2

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

## Skin corrosion/irritation

## **Product:**

Remarks: May irritate skin.

## Serious eye damage/eye irritation

#### **Product:**

Remarks: May cause irreversible eye damage.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

# **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

## **Aspiration toxicity**

No data available

#### **Further information**

**Product:** 

Remarks: No data available

**Components:** 

Amides, coco, N,N-bis(hydroxyethyl):

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: No data available

octanol/water **Components:** 

2,2'-iminodiethanol:

Partition coefficient: n- : Pow: 1.43

octanol/water

Amides, coco, N,N-bis(hydroxyethyl):

Partition coefficient: n- : Remarks: No data available

octanol/water

Mobility in soil

No data available

#### Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

## **ZEP RP#3 BRICK LUBRICANT**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Components:

Amides, coco, N,N-bis(hydroxyethyl):

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

(	Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2	2,2'-iminodiethanol	111-42-2	100	2056

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2,2'-iminodiethanol 111-42-2 4.8617 %

## California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, Amides, coco, N,N-

bis(hydroxyethyl), which is/are known to the State of California

to cause cancer. For more information go to

www.P65Warnings.ca.gov.

#### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

#### **Further information**

#### NFPA:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms





Health hazard

Signal word Hazard statements Danger:

Causes serious eye damage. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/ attention.

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ZEP RP#3 BRICK LUBRICANT

Version 2.1 Revision Date 10/01/2023 Print Date 04/27/2025

Version:	2.1
Revision Date:	10/01/2023
Print Date:	04/27/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.