ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP FORMULA 166_5 GAL

Material number : 0000000000142935

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	colourless, clear
Odour	hydrocarbon-like

GHS Classification

Flammable liquids : Category 3
Acute toxicity (Inhalation) : Category 4
Acute toxicity (Dermal) : Category 4
Skin irritation : Category 2
Serious eye damage : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :









Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H312 + H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

: Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
xylenes	1330-20-7	>= 50 - < 70
ethylbenzene	100-41-4	>= 10 - < 20

ZEP FORMULA 166 5 GAL

Version 4.1	Revision Date 10/01/2023	Print Date 04/25/2025

1,2-Benzenedicarboxylic acid, benzyl C7-9-branched and linear alkyl esters	68515-40-2	>= 1 - < 5
toluene	108-88-3	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

: Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

Causes skin irritation.

Causes serious eye damage. Suspected of causing cancer.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Do not breathe vapours or spray mist. Avoid contact with skin and eyes.

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

No smoking. Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline

materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	CAL PEL
		С	300 ppm	CAL PEL
		PEL	100 ppm 435 mg/m3	CAL PEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL

ZEP FORMULA 166_5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

	375 mg/m3	
ST	150 ppm 560 mg/m3	NIOSH REL
TWA	200 ppm	OSHA Z-2
CEIL	300 ppm	OSHA Z-2
Peak	500 ppm	OSHA Z-2
TWA	100 ppm 375 mg/m3	OSHA P0
STEL	150 ppm 560 mg/m3	OSHA P0
PEL	10 ppm 37 mg/m3	CAL PEL
С	500 ppm	CAL PEL
STEL	150 ppm 560 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ETIM DENZENE	100 11 1	_ '				ACCILIDEI
ETHYLBENZENE	100-41-4	Sum of	Urine	End of	0.15.g/g	ACGIH BEI
		mandelic		shift (As	creatinine	
		acid and		soon as		
		phenyl		possible		
		glyoxylic		after		
		acid		exposure		
				ceases)		
ETHYLBENZENE		Ethylbenzen	In end-	Not		ACGIH BEI
		е	exhaled air	critical		
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH BEI
				last shift		
				of		
				workwee		
				k		
METHYLBENZENE		Toluene	Urine	End of	0.03 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
METHYLBENZENE		o-Cresol	Urine	End of	0.3.mg/g	ACGIH BEI
				shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless, clear
Odour : hydrocarbon-like
Odour Threshold : No data available
pH : No data available
Melting point/freezing point : No data available

Boiling point : $138 \, ^{\circ}\text{C}$ Flash point : $26.6 \, ^{\circ}\text{C}$

Method: TCC

Evaporation rate : 0.8

Upper explosion limit : 7 %(V)

Lower explosion limit : 1 %(V)

Vapour pressure : 8.1 hPa
Relative vapour density : 3.7

Density : 0.897 g/cm3

Bulk density : No data available

Solubility(ies)

Water solubility : slightly soluble
Solubility in other solvents : partly soluble

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : 11 mm2/s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products

: Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Chronic effects are delayed and symptoms may not be

observed during an exposure.

Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

Causes skin irritation.

Causes serious eye damage. Suspected of causing cancer.

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : 13.07 mg/l

Exposure time: 4 h

Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 1,618 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

ZEP FORMULA 166_5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

toluene:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water
Components:
xylenes:

Partition coefficient: n-

octanol/water

ethylbenzene : Partition coefficient: n-

octanol/water toluene:

Partition coefficient: n-

Partition coefficient octanol/water

: Pow: 3.6

: Pow: 3.12

: Pow: 2.73

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: No data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to

aquatic life.

Components:

toluene:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN1993, Flammable liquids, n.o.s., (XYLENE), 3, III

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (XYLENE), 3, III

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (XYLENE), 3, III

Transportation Regulation: IATA (Passenger Air): UN1993, Flammable liquid, n.o.s., (XYLENE), 3, III

Transportation Regulation: TDG (Canada):

UN1993, FLAMMABLE LIQUID, N.O.S., (XYLENE), 3, III

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
xylenes	1330-20-7	100	147

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity
Reproductive toxicity

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

ethylbenzene 100-41-4 16.1471 %

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to

the State of California to cause birth defects or other reproductive harm. For more information go to

www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

Print Date 04/25/2025 Version 4.1 Revision Date 10/01/2023

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	3
FLAMMABILITY	3
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms







Health hazard

Corrosion

Signal word Hazard statements Danger:

Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. Suspected of

damaging fertility or the unborn child.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces,

SAFETY DATA SHEET ZEP FORMULA 166 5 GAL

Version 4.1 Revision Date 10/01/2023 Print Date 04/25/2025

sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	4.1
Revision Date:	10/01/2023
Print Date:	04/25/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.