

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Material number : J32835P3

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear, pale straw
Odour	characteristic

GHS Classification

Flammable liquids : Category 4

Skin sensitisation : Category 1

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 90 - < 100
d-limonene	5989-27-5	>= 3 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
Get medical attention.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
- In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

Aspiration may cause pulmonary oedema and pneumonitis.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical
Water
Foam

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : No smoking.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum),	64742-47-8	TWA	500 ppm	OSHA Z-1

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

hydrotreated light			2,000 mg/m3	
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
d-limonene	5989-27-5	TWA	30 ppm	US WEEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Safety glasses

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: clear, pale straw

Odour

: characteristic

Odour Threshold

: No data available

pH

: Not applicable

Melting point/freezing point

: No data available

Boiling point

: 177 °C

Flash point

: 61.11 °C

Method: closed cup

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Evaporation rate	: < 1
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.8 hPa
Relative vapour density	: No data available
Density	: 0.826 g/cm ³
Bulk density	: No data available
Solubility(ies)	
Water solubility	: slightly soluble
Solubility in other solvents	: soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 4.4 mm ² /s (20.0 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical	: None known.
--------------------	---------------

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Condition

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

Aspiration may cause pulmonary oedema and pneumonitis.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate : 2,673 mg/kg
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

d-limonene:

Acute oral toxicity : LD50 Oral Rat: 4,400 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Serious eye damage/eye irritation

Product:

Remarks: Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

d-limonene:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

d-limonene :

Partition coefficient: n-octanol/water : log Pow: 4.232

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL
--

Transportation Regulation: IMDG (Vessel): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Transportation Regulation: IATA (Cargo Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitisation
Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	2
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

SAFETY DATA SHEET

FY25 FALL DYNA-MATE 3 W/ZONE DEF PROMO

Version 3.1

Revision Date 10/01/2023

Print Date 04/28/2025

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Combustible liquid. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

Precautionary statements

:

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage: Store in a well-ventilated place. Keep cool.
Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	04/28/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.